




# BlueWave® MX-150 LED Spot-Curing Emitters

User Guide





## About Dymax

Light-curable adhesives. Systems for light curing, fluid dispensing, and fluid packaging.

Dymax manufactures industrial adhesives, light-curable adhesives, epoxy resins, cyanoacrylates, and activator-cured adhesives. We also manufacture a complete line of manual fluid dispensing systems, automatic dispensing systems, and light-curing systems. Light-curing systems include LED light sources, spot, flood, and conveyor systems designed for compatibility and high performance with Dymax adhesives. Dymax adhesives and light-curing systems optimize the speed of automated assembly, allow for 100% in-line inspection, and increase throughput. System designs enable stand-alone configuration or integration into your existing assembly line.

Please note that most dispensing and curing system applications are unique. Dymax does not warrant the fitness of the product for the intended application. Any warranty applicable to the product, its application, and use is strictly limited to that contained in the Dymax standard Conditions of Sale. Dymax recommends that any intended application be evaluated and tested by the user to ensure that desired performance criteria are satisfied. Dymax is willing to assist users in their performance testing and evaluation. Data sheets are available for valve controllers or pressure pots upon request.

# Contents

<b>Introduction .....</b>	<b>4</b>
Where to Get Help.....	4
<b>Safety .....</b>	<b>4</b>
<b>Product Overview .....</b>	<b>5</b>
Description of BlueWave MX-150 Emitters .....	5
<b>Unpacking.....</b>	<b>6</b>
Parts Included .....	6
<b>Installation .....</b>	<b>6</b>
Important Information.....	6
Mounting/Connections.....	7
<b>Troubleshooting &amp; Maintenance .....</b>	<b>8</b>
Product Cleaning and Care.....	9
<b>Spare Parts .....</b>	<b>9</b>
<b>Compatible Devices .....</b>	<b>10</b>
<b>Specifications .....</b>	<b>11</b>
<b>Declaration of Conformity .....</b>	<b>12</b>
<b>Warranty .....</b>	<b>14</b>
<b>Index .....</b>	<b>15</b>

# Introduction

This guide describes how to set up, use, and maintain BlueWave® MX-150 emitters safely and efficiently.

## Intended Audience

This user guide is meant for experienced process engineers, technicians, and manufacturing personnel. If you are new to high-intensity LED light sources and do not understand the instructions, contact Dymax Application Engineering for answers to your questions before using the equipment.

## Where to Get Help

Dymax Customer Support and Application Engineering teams are available by phone in the United States, Monday through Friday, from 8:00 a.m. to 5:30 p.m. Eastern Standard Time. You can also email Dymax at [info@dymax.com](mailto:info@dymax.com). Contact information for additional Dymax locations can be found on the back cover of this user guide. For more information about this product, visit [dymax.com](http://dymax.com).

## Safety



**WARNING!** *Under NO circumstances should the interconnect cable from the controller to the LED emitter be connected or disconnected while power to the unit is on. This procedure is usually called “hot swapping” and should not be performed as it could cause damage to the controller or the emitter. Always power down the equipment before disconnecting or connecting any of these devices.*

---



**WARNING!** *If you use this UV LED light source without first reading and understanding the information in the UV Light Safety Guide, SAF001, injury can result from exposure to high-intensity light. To reduce the risk of injury, please read and ensure you understand the information in that guide before assembling and operating the Dymax UV LED light source.*



### **Specific Safety statements for this device:**

*This device falls under IEC 62471 Risk Group 3 for UVA and Blue Light Emissions:*

**WARNING.** *UV emitted from this product. Avoid eye and skin exposure to unshielded products.*

**WARNING.** *Possibly hazardous optical radiation emitted from this product. Do not look at operating lamp. Eye injury may result.*

# Product Overview

## Description of BlueWave MX-150 Emitters

- When paired with a MX-series controller, BlueWave MX-150 emitters function as a high-intensity spot-curing system. The system can be set up in many configurations and can be used with a lightguide if needed.
- The BlueWave MX-150 emitter is air cooled using an axial fan.
- The BlueWave MX-150 emitter can be mounted using one of two hole-patterns in the housing body.

**Figure 1.**  
BlueWave MX-150 Emitter



# Unpacking

Upon arrival, inspect all boxes for damage and notify the shipper of box damage immediately. Open each box and check for equipment damage. If parts are damaged, notify the shipper and submit a claim for the damaged parts. Contact Dymax so that new parts can be shipped to you immediately.



***WARNING!*** *Until the BlueWave® MX-150 emitter is attached to a controller via the interconnect cable it is susceptible to ESD damage, handle according to ESD standards using a ground strap and do not touch exposed connector pins.*

The parts below are included in every package/order. If parts are missing from your order, contact your local Dymax representative or Dymax Customer Support to resolve the problem.

## Parts Included

- BlueWave MX-150 LED Emitter Assembly
- 5-mm Lightguide Simulator
- User Guide

# Installation

The BlueWave MX-150 emitter is part of a MX-series curing system and requires connection to a controller via an interconnect cable for proper operation.


## Important Information

- Do not connect any components while power is applied.
- Mount the BlueWave MX-150 emitter to a rigid support, such as the emitter stand PN 42390, prior to connecting the interconnect cable to prevent handling damage.
- Always keep the LED area covered by a lightguide, rod lens, or lightguide simulator. Assure that FOD cannot flow into the LED area.

## Mounting/Connections

- Each emitter has two sets of M3 x 0.5 mm holes (Figure 1) that align with Dymax stands and holders.
- When connecting the emitter to the controller, ensure proper strain relief to prevent pinching or kinking of the interconnect cable.
- The cooling air intake on top of unit must be free flowing, do not cover.
- Exhausting air on sides must be given at least 1 mm (0.04") of clear space to obstructions for safe use.

**Figure 2.**  
Bluewave MX-150 Emitter Dimensions



# Troubleshooting & Maintenance

Problem	Possible Cause	Corrective Action
BlueWave MX-150 LED does not produce light	LED intensity adjustment set to 0% or too low	Increase LED intensity setting.
	LED cycle time is set to 0 seconds	0 Seconds sets manual mode and requires a trigger.
	Interlock is open	Verify interlock jumpers are in place. Verify PLC command structure for PLC mode.
	Interface cable connections loose or damaged	Check connections and condition of interface cable.
	Trigger setting not matched to input	Trigger setting on admin screen should match the desired input trigger channel.
	LED head is not connected to the correct port/channel	Verify that the head is connected to the desired port/channel.
BlueWave MX-150 LED suddenly stops producing light	Lightguide not inserted	Ensure the lightguide simulator or any lightguides installed with the unit are fully seated into the Wolf connector.
	Over-temperature shutdown was triggered	Verify alarms.
	Footswitch defective	Activate unit using the front control panel. Replace the footswitch if the unit operates from the front control panel.
	Interlock is open	Verify interlock jumpers are in place. Verify PLC command structure for PLC mode.
BlueWave MX-150 LED provides only low-intensity light	LED intensity adjustment set to minimum	Increase LED intensity setting on admin settings or I/O input for PLC mode.
	Contaminated/dirty lens optics	Clean the surface of the lens.



## Product Cleaning and Care

- Product cleaning is limited to wiping the outside of the product with a damp cloth. Do not soak. Isopropanol Alcohol or household cleaners may be used for cleaning the product.
- Keep the LED array free from dust and debris (FOD). Contamination can lead to loss of performance or failure. Protect the LED array by always keeping a light guide, rod lens, or light guide simulator installed.
- Do not insert tools or cleaning devices into the LED opening, and do not attempt to clean the LED array. Disruption from touching, and exposure to cleaning materials can damage the array.
- Do not use compressed air to remove particle debris inside the emitter as it may damage the LED array or the high-speed cooling fan.

## Spare Parts

Item	Part Number
5-mm Lightguide Simulator	36987

# Compatible Devices

Item	Part Number
<b>Controllers</b>	
BlueWave® MX 2-Channel Controller/Power Supply - Power Cord (Type G)	43186
BlueWave® MX 4-Channel Controller/Power Supply - Power Cord (Type G)	43183
<b>Emitters</b>	
BlueWave MX-150, VisiCure® (405 nm)	42338
BlueWave MX-150, PrimeCure® (385 nm)	42337
BlueWave MX-150, RediCure® (365 nm)	42336
<b>BlueWave MX Series System Components</b>	
Interconnect Cable Assembly - 12 Inches	43453
Interconnect Cable Assembly - 2 meter	42287
Interconnect Cable Assembly - 5 meter	42889
Extended Interconnect Cable - 10 meter*	43010
Extended Interconnect Cable - 20 meter*	43011
5-mm Lightguide Simulator	36987
5-mm x 1,000-mm Liquid Lightguide	35102
3-mm x 1,000-mm Bifurcated Guide (5-mm Rod)	37043
Adjustable Focusing Lens	41148
<b>Radiometer</b>	
ACCU-CAL™ 50-LED Radiometer	40505
<b>Stands</b>	
<b>Array Stand</b>	43070
Single Emitter Mounting Stand	42390
Dual Emitter Mounting Bracket for MX Controller	60868
<b>Personal Protection Equipment</b>	
Three-Sided Acrylic Shield	41395
Protective Goggles — Green**	35286
Protective Goggles — Gray (standard model included with unit)**	35285
Face Shield**	35186

\* Intended for machine installations only. | \*\* For data sheets related to these products, please refer to the manufacturer. (35285 – MCR Safety, TK112; 35286 – MCR Safety, 98150; 35186 – Oberon, 171AFR)


# Specifications



Property	Specification		
Emitter	RediCure	PrimeCure	VisiCure
Output Frequency	365 nm	385 nm	405 nm
Typical Intensity Output*	24 W/cm <sup>2</sup>	38 W/cm <sup>2</sup>	36 W/cm <sup>2</sup>
Emitter Dimensions (W x D x H)	1.97" x 1.97" x 7.9" [5 cm x 5 cm x 20.06 cm]		
Weight	1.4 lbs. [0.64 kg]		
Unit Warranty	1 year from purchase date		
Operating Environment	10 to 40°C (50°F to 104°F), 0-80% relative humidity, non-condensing		

\* Measured using an ACCU-CAL™ 50-LED radiometer with a 5-mm lightguide at a distance of 0 mm.

**Figure 3.**  
BlueWave MX Series Spectral Output



# Declaration of Conformity

**Figure 4.**  
Declaration of Conformity - CE



### EU Declaration of Conformity

**Manufacturer:**  
Dymax Corporation  
210 South 4th Lane  
Farmington, CT 06030, USA

**Product Description:**  
Audio System

**Model:** BW-MX-150 (150) Dual-Channel System  
**Version:** BW-MX-150 (150) Series

This product complies with the following relevant European Standards:

Applicable CE Directives	Applicable Harmonized Standards
Electromagnetic Compatibility Directive (2014/53/EU)	EN 55032:2015 (EMC Class B)
Low Voltage Directive (2014/35/EU)	EN 60950-1:2012 (Safety)
RoHS Directive (2011/65/EU)	EN 60950-1:2012 (RoHS)

**Declaration:**  
I, the undersigned, declare under sole responsibility of the manufacturer that the product complies with the CE mark requirements.

*[Signature]* **3/20/2015 Farmington, CT**  
Date Place Location

**Authorized Signatory:**  
Robert J. Gagnier  
Engineering Manager, Equipment  
Dymax Corporation  
Farmington, CT, USA

www.dymax.com

Declaration of Conformity (DoC) is a statement by the manufacturer that the product complies with the requirements of the applicable CE mark standards. It is a legal requirement for all products placed on the market in the EU. The DoC must be signed by the manufacturer or its authorized representative. The DoC must be kept for 10 years after the last date of production of the product. The DoC must be made available to the competent authorities upon request. The DoC must be drawn up in a language easily accessible to the authorities. The DoC must be in the same language as the technical documentation. The DoC must be in the same language as the user manual. The DoC must be in the same language as the product label. The DoC must be in the same language as the product packaging. The DoC must be in the same language as the product warranty. The DoC must be in the same language as the product invoice. The DoC must be in the same language as the product receipt. The DoC must be in the same language as the product return form. The DoC must be in the same language as the product complaint form. The DoC must be in the same language as the product feedback form. The DoC must be in the same language as the product survey form. The DoC must be in the same language as the product evaluation form. The DoC must be in the same language as the product improvement form. The DoC must be in the same language as the product innovation form. The DoC must be in the same language as the product development form. The DoC must be in the same language as the product testing form. The DoC must be in the same language as the product validation form. The DoC must be in the same language as the product certification form. The DoC must be in the same language as the product registration form. The DoC must be in the same language as the product distribution form. The DoC must be in the same language as the product sales form. The DoC must be in the same language as the product marketing form. The DoC must be in the same language as the product promotion form. The DoC must be in the same language as the product advertising form. The DoC must be in the same language as the product public relations form. The DoC must be in the same language as the product corporate social responsibility form. The DoC must be in the same language as the product environmental management form. The DoC must be in the same language as the product quality management form. The DoC must be in the same language as the product risk management form. The DoC must be in the same language as the product security management form. The DoC must be in the same language as the product privacy management form. The DoC must be in the same language as the product data protection form. The DoC must be in the same language as the product intellectual property form. The DoC must be in the same language as the product trademark form. The DoC must be in the same language as the product patent form. The DoC must be in the same language as the product copyright form. The DoC must be in the same language as the product trademark form. The DoC must be in the same language as the product patent form. The DoC must be in the same language as the product copyright form.

**Figure 5.**  
Declaration of Conformity - UKCA



### UK Declaration of Conformity

**Manufacturer:**  
Dymax Corporation  
219 Industrial Lane  
Torrington CT 06790, USA

**Product description:**  
Model number:

**BlueWave® 9-100W 1200 Super-Gain® System**  
**BlueWave® MX-150 1200 1x1x1x1**

This product complies with the following relevant CE Declaration:

**Applicable UK Legislation:**  
Electromagnetic Compatibility Regulations 2012

**Electrical Equipment Safety Regulations 2016**

This restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012

**Other Regulatory Compliance:**

**Applicable Harmonized Standards:**  
EN 50371-1:2014/EN 50371-2:2014  
EN 50371-3:2014 Class A  
EN 50371-4:2014  
EN 50371-5:2014  
EN 50371-6:2014/AM2:2019

EN 60950-1:2012

**Photobiological Safety**  
IEC 62471:2006

**Declaration:**  
This declaration of conformity is issued under the sole responsibility of the manufacturer:  
Signed for and on behalf of:

 4/26/2015 Torrington, CT, USA

**Affirmed Declaration:**  
Robert Sutcliffe  
Engineering Manager, Compliance  
Dymax Corporation  
Torrington CT, USA



www.dymax.com

Model number: 9-100W 1200, 1x1x1x1 Super-Gain® System  
EN 50371-1:2014/EN 50371-2:2014  
EN 50371-3:2014 Class A  
EN 50371-4:2014  
EN 50371-5:2014  
EN 50371-6:2014/AM2:2019

USER GUIDE | BLUEWAVE MX-150 EMITTERS

13

# Warranty

From date of purchase, Dymax Corporation offers a one-year warranty against defects in material and workmanship on all system components with proof of purchase and purchase date. Unauthorized repair, modification, or improper use of equipment may void your warranty benefits. The use of aftermarket replacement parts not supplied or approved by Dymax Corporation, will void any effective warranties and may result in damage to the equipment.

***IMPORTANT NOTE: DYMAX CORPORATION RESERVES THE RIGHT TO INVALIDATE ANY WARRANTIES, EXPRESSED OR IMPLIED, DUE TO ANY REPAIRS PERFORMED OR ATTEMPTED ON DYMAX EQUIPMENT WITHOUT WRITTEN AUTHORIZATION FROM DYMAX. THOSE CORRECTIVE ACTIONS LISTED ABOVE ARE LIMITED TO THIS AUTHORIZATION.***

# Index

Cleaning .....	9	Product Overview .....	5
Compatible Devices.....	10	Safety.....	4
Components .....	5	Spare Parts .....	9
Connections.....	7	Specifications .....	11
Declaration of Conformity .....	12	Spectral Output.....	11
Help.....	4	Support.....	4
Installation .....	6	Troubleshooting .....	8
Maintenance .....	8	Unpacking .....	6
Mounting .....	7	Warranty.....	14
Parts List.....	6		

Americas: +1.860.482.1010 | Europe: +49 611.962.7900 | Asia: +65.67522887



[www.dymax.com](http://www.dymax.com)

© 2019-2025 Dymax Corporation. All rights reserved. All trademarks in this guide, except where noted, are the property of, or used under license by Dymax Corporation, U.S.A.

**Please note that most curing system applications are unique.** Dymax does not warrant the fitness of the product for the intended application. Any warranty applicable to the product, its application and use is strictly limited to that contained in Dymax standard Conditions of Sale published on our website. Dymax recommends that any intended application be evaluated and tested by the user to ensure that desired performance criteria are satisfied. Dymax is willing to assist users in their performance testing and evaluation by offering equipment trial rental and leasing programs to assist in such testing and evaluations.

MAN097DA 7/3/2025