

LPD Side Light Frame Set



A beautiful and versatile new frame-set that allows you the look of a custom-built door-set at the price of a ready-made product and as it is a universal frame which would cover lots of different styles you may have more sections than you require.

Kit Components: This door and frame set with side screen aperture(s) and inset(s) is sold in kit form.

The door is available in a selection of different options and always includes fitted glass where shown, the frame side screen aperture(s) are unglazed. The main frame is in kit form ready to assemble and to house the chosen door and aperture(s).

Sizes: The frame and side screen aperture(s) can be adjusted on site to suit the 1981x762mm, 1981x838mm, 2032x813mm, 2085x865mm and 2135x915mm high door sizes, the latter two are subject to availability and are not available for all door types.

The overall frame height for any 1981mm door height is 2058mm high, 2109mm for the 2032mm high door, 2159mm for the 2085mm high door and 2209mm to maximum of 2236mm for the 2135mm high door, possible widths are anything up to 2291mm, the overall width is up to you to decide and is all without any clearances for the door or fittings, **two small holes may require filling in the lintol depending on the door size/configuration chosen.**

Adjustment Possible: The overall height required is to suit the chosen door and frame dimensions and any additional **Exitex** type weather bar that can be fitted between the door and frame sill.

All beading/stops are provided and it is possible to open the door out.

Availability: 4 – 7 Working days anywhere within mainland UK, islands by arrangement.

Thickness of door: 45mm.

Hardware: Any ironmongery such as locks, handles, hinges, **Exitex** weather bar, etc. are an extra to the cost of these door and frame sets.

Handing: All doors can be Left or Right hinge opening inwards when viewed from outside, you decide when fitting and they can also be set to allow the door to open in or out.

Timber Cill: Cill is 130mm broad and 39mm thick but our **Exitex** weather bar may be required to be on top of this thickness to give proper draught proofing.

Thickness: Frame is 68mm broad from inside of house to the outside.

Weather bar: Neoprene gasket draught proofing is fitted to the frame legs, mullion and lintol for the door.

Overall Frame Size: Nominal manufactured joinery sizes, these can vary 4mm.

Construction: The door has Dowel or Mortice & Tenon joints (depending on door choice) with a heavy veneer on a solid core, the frame and cill are also a veneered oak on a solid timber.

Colour/Grain: This door may be shown with or without any decoration, if you "Choose Fittings" this will give you all our fittings options, any decoration by yourself may not achieve a perfect colour match between the door and the frame but will be a suitable contrast.

Guarantee: 12 months.

Important Note: There will be a certain amount of joinery work required to make the frame suit your ironmongery and draught proofing and this could involve cutting the door and frame heights to suit draught excluders, fitting lock, fitting hinges, etc.