



SANTA-FE™
INDOOR AIR QUALITY SOLUTIONS

PRODUCT CATALOG



PIONEERS OF INDOOR AIR QUALITY SOLUTIONS.

**AT SANTA FE, WE ARE FOCUSED ON THE FRONT LINE IN DEFENSE –
THE BIG 3: DEHUMIDIFICATION, FILTRATION AND VENTILATION.**

DEHUMIDIFICATION

When a home has too much moisture, it becomes a breeding ground for pests and a trigger for indoor pollutants such as dust, pollen, mold spores and bacteria. It can also put the home's structural integrity, as well as the occupant's health and comfort, at risk.

Our innovative dehumidifiers properly maintain humidity levels — regardless of how hot it is outside and how much moisture is already in your home. At the same time, our superior filtration helps remove indoor pollutants.



VENTILATION

Santa Fe's Ultra Series whole house ventilating dehumidifiers provide the additional benefit of outdoor mechanical supply ventilation that is filtered through a MERV-13 filter.

INDUSTRY-LEADING WARRANTY.

To say we stand behind our products is an understatement. While most manufacturers offer only a 1-year warranty, every Santa Fe dehumidifier is backed with an industry-leading total peace of mind 6-year warranty that includes five years full replacement plus one year parts.

FILTERED TO THE HIGHEST STANDARDS OF FRESH.

Over a 6-year period, MERV-13 filters will remove two pounds of dust, pollen, mold spores, pet dander, and bacteria from the air in a home.* In comparison, big-box units have MERV-4 or washable filters, which only remove 7 ounces of material from the air over the same period of time.

*Based on regularly changing your air filter: see instructional manual for more information.

The **Santa Fe Portable Series** offers a wide variety of superior dehumidification options. Designed with basement and crawl space applications in mind, our portable dehumidifiers are professional-grade, high-efficiency and easy to install.

► COMPACT70



- + **MODEL:** 4044110
- + **OPERATING TEMPERATURE:** 49°F - 95°F
- + **FILTER:** MERV-13
- + **CRAWLSPACE SIZING:** UP TO 1,800 SQ. FT. - 2,600 SQ. FT.
- + **BASEMENT SIZING:** UP TO 1,800 SQ. FT. - 2,200 SQ. FT.
- + **DIMENSIONS:** 12"W X 12"H X 21"D
- + **@80°F / 60%RH**
PINT CAPACITY: 70 PINTS / 8.75 GALLONS PER DAY
ENERGY FACTOR: 2.6 L/KWH
- + **@65°F / 60%RH**
PINT CAPACITY: 43.7 PINTS / 5.4 GALLONS PER DAY
ENERGY FACTOR: 1.96 L/KWH
- + **HVAC SYSTEM INTEGRATION:** NO
- + **VENTILATION:** NO
- + **CONTROL:** ON-BOARD DEHUMIDISTAT

► OASIS105



- + **MODEL:** 4044510
- + **OPERATING TEMPERATURE:** 49°F - 95°F
- + **FILTER:** MERV-13
- + **CRAWLSPACE SIZING:** UP TO 3,300 SQ. FT.
- + **BASEMENT SIZING:** UP TO 2,600 SQ. FT.
- + **DIMENSIONS:** 24"W X 14.5"H X 16"D
- + **@80°F / 60%RH**
PINT CAPACITY: 102 PINTS / 12.75 GALLONS PER DAY
ENERGY FACTOR: 3.54 L/KWH
- + **@65°F / 60%RH**
PINT CAPACITY: 67 PINTS / 8.37 GALLONS PER DAY
ENERGY FACTOR: 2.81 L/KWH
- + **HVAC SYSTEM INTEGRATION:** NO
- + **VENTILATION:** NO
- + **CONTROL:** ON-BOARD DEHUMIDISTAT OR LOW-VOLTAGE CONTROLLER



► ADVANCE DRY110



- + **MODEL:** 4047010
- + **OPERATING TEMPERATURE:** 49°F - 95°F
- + **FILTER:** MERV-13
- + **CRAWLSPACE SIZING:** UP TO 2,800 SQ. FT. - 3,600 SQ. FT.
- + **BASEMENT SIZING:** UP TO 2,500 SQ. FT. - 2,900 SQ. FT.
- + **DIMENSIONS:** 14.35"W X 24"H X 29"D
- + **@80°F / 60%RH**
PINT CAPACITY: 110 PINTS / 13.75 GALLONS PER DAY
ENERGY FACTOR: 3.66 L/KWH
- + **@65°F / 60%RH**
PINT CAPACITY: 70 PINTS / 8.75 GALLONS PER DAY
ENERGY FACTOR: 2.81 L/KWH
- + **HVAC SYSTEM INTEGRATION:** NO
- + **VENTILATION:** NO
- + **CONTROL:** ON-BOARD DIGITAL

► IMPACT155



- + **MODEL:** 4031470
- + **OPERATING TEMPERATURE:** 49°F - 95°F
- + **FILTER:** MERV-13
- + **CRAWLSPACE SIZING:** UP TO 3,600 SQ. FT. - 4,400 SQ. FT.
- + **BASEMENT SIZING:** UP TO 3,800 SQ. FT. - 4,000 SQ. FT.
- + **DIMENSIONS:** 20.25"W X 21.75"H X 38"D
- + **@80°F / 60%RH**
PINT CAPACITY: 155 PINTS / 19.375 GALLONS PER DAY
ENERGY FACTOR: 3.4 L/KWH
- + **@65°F / 60%RH**
PINT CAPACITY: 104 PINTS / 13 GALLONS PER DAY
ENERGY FACTOR: 2.89 L/KWH
- + **HVAC SYSTEM INTEGRATION:** NO
- + **VENTILATION:** NO
- + **CONTROL:** ON-BOARD DEHUMIDISTAT

► CLASSIC



- + **MODEL:** 4044710
- + **OPERATING TEMPERATURE:** 56°F - 95°F
- + **FILTER:** MERV-13
- + **BASEMENT SIZING:** UP TO 2,500 SQ. FT. - 2,900 SQ. FT.
- + **DIMENSIONS:** 20"W X 36"H X 17"D
- + **@80°F / 60%RH**
PINT CAPACITY: 116 PINTS / 14.5 GALLONS PER DAY
ENERGY FACTOR: 3.43 L/KWH
- + **@65°F / 60%RH**
PINT CAPACITY: 76 PINTS / 9.5 GALLONS PER DAY
ENERGY FACTOR: 2.8 L/KWH
- + **HVAC SYSTEM INTEGRATION:** NO
- + **VENTILATION:** NO
- + **CONTROL:** ON-BOARD DEHUMIDISTAT

The **Ultra Series** offers the ultimate protection. Designed with dedicated ducting for whole house dehumidification and ventilation options.

▶ ULTRA70



- + **MODEL:** 4044100
- + **OPERATING TEMPERATURE:** 49°F - 95°F
- + **FILTER:** MERV-13
- + **SIZING:** UP TO 1,800 SQ. FT. / 18,000 CU. FT.
- + **DIMENSIONS:** 12"W X 12"H X 28"D
- + **@80°F / 60%RH**
PINT CAPACITY: 70 PINTS / 8.75 GALLONS PER DAY
ENERGY FACTOR: 2.6 L/KWH
- + **@73°F / 60%RH**
PINT CAPACITY: 52.45 PINTS / 6.55 GALLONS PER DAY
ENERGY FACTOR: 2.04 L/KWH
- + **HVAC SYSTEM INTEGRATION:** YES
- + **VENTILATION:** OPTIONAL
- + **CONTROL:** ON-BOARD DEHUMIDISTAT OR LOW-VOLTAGE CONTROLLER

▶ ULTRA98



- + **MODEL:** 4044300
- + **OPERATING TEMPERATURE:** 49°F - 95°F
- + **FILTER:** MERV-13
- + **SIZING:** UP TO 2,300 SQ. FT. / 23,000 CU. FT.
- + **DIMENSIONS:** 14.5"W X 19.5"H X 32.4"D
- + **@80°F / 60%RH**
PINT CAPACITY: 100 PINTS / 12.5 GALLONS PER DAY
ENERGY FACTOR: 2.89 L/KWH
- + **@73°F / 60%RH**
PINT CAPACITY: 71.4 PINTS / 8.9 GALLONS PER DAY
ENERGY FACTOR: 2.2 L/KWH
- + **HVAC SYSTEM INTEGRATION:** YES
- + **VENTILATION:** OPTIONAL
- + **CONTROL:** LOW-VOLTAGE CONTROLLER REQUIRED

▶ ULTRA120



- + **MODEL:** 4044400
- + **OPERATING TEMPERATURE:** 49°F - 95°F
- + **FILTER:** MERV-13
- + **SIZING:** UP TO 3,000 SQ. FT. / 30,000 CU. FT.
- + **DIMENSIONS:** 14.4"W X 21"H X 32.2"D
- + **@80°F / 60%RH**
PINT CAPACITY: 118 PINTS / 14.75 GALLONS PER DAY
ENERGY FACTOR: 2.7 L/KWH
- + **@73°F / 60%RH**
PINT CAPACITY: 88 PINTS / 11 GALLONS PER DAY
ENERGY FACTOR: 2.1 L/KWH
- + **HVAC SYSTEM INTEGRATION:** YES
- + **VENTILATION:** OPTIONAL
- + **CONTROL:** LOW-VOLTAGE CONTROLLER REQUIRED

► ULTRA V155



- + **MODEL:** 4047300
- + **OPERATING TEMPERATURE:** 34°F - 105°F
- + **FILTER:** MERV-13
- + **SIZING:** UP TO 3,500 SQ. FT. / 35,000 CU. FT.
- + **DIMENSIONS:** 14.35"W X 24"H X 39.25"D
- + **@80°F / 60%RH**
PINT CAPACITY: 155 PINTS / 19.3 GALLONS PER DAY
ENERGY FACTOR: 3.35 L/KWH
- + **@73°F / 60%RH**
PINT CAPACITY: 128 PINTS / 16 GALLONS PER DAY
ENERGY FACTOR: 3.08 L/KWH
- + **HVAC SYSTEM INTEGRATION:** YES
- + **VENTILATION:** OPTIONAL
- + **CONTROL:** ON-BOARD DEHUMIDISTAT OR LOW-VOLTAGE CONTROLLER

► ULTRA V205



- + **MODEL:** 4046180
- + **OPERATING TEMPERATURE:** 40°F - 104°F
- + **FILTER:** MERV-13
- + **SIZING:** UP TO 5,000 SQ. FT. / 50,000 CU. FT.
- + **DIMENSIONS:** 26.75"W X 20.75"H X 38"D
- + **@80°F / 60%RH**
PINT CAPACITY: 205 PINTS / 25.625 GALLONS PER DAY
ENERGY FACTOR: 3.5 L/KWH
- + **@73°F / 60%RH**
PINT CAPACITY: 173 PINTS / 21.6 GALLONS PER DAY
ENERGY FACTOR: 3.0 L/KWH
- + **HVAC SYSTEM INTEGRATION:** YES
- + **VENTILATION:** OPTIONAL
- + **CONTROL:** ON-BOARD DEHUMIDISTAT OR LOW-VOLTAGE CONTROLLER

MAKE THE ENTIRE HOME COMFORTABLE.

Buildup of indoor pollution in today's homes is a direct result of our efforts to conserve energy and save money. As the techniques and materials used to insulate and seal our homes have improved, the result is stale and polluted air trapped inside.

Fresh air supply ventilation systems, such as a Santa Fe Whole House Ventilating Dehumidifier, allow improved control and treatment of the air that enters the house. By slightly pressurizing the house, these systems minimize outdoor pollutants in the living space and reduce the potential for back-drafting of combustion gases from fireplaces and appliances. Santa Fe Whole House Ventilating Dehumidifiers filter outdoor air before introducing it into the home.

The **UltraMD33** is the first true in-wall dehumidifier. Featuring a tamper-proof cover, this unit runs independently of the HVAC system and creates a comfortable, healthier living environment for residents. Ideal for apartments, ductless mini-split applications, basements, and other space dehumidification needs. The MD33 can also be installed on a wall with the Surface Mount Kit and partially through a wall with the Bezel Kit.

▶ **ULTRAMD33**



- ✦ **MODEL:** 4044610
- ✦ **OPERATING TEMPERATURE:** 49°F - 95°F
- ✦ **FILTER:** WASHABLE
- ✦ **SIZING:** UP TO 1,200 SQ. FT. / 12,000 CU. FT.
- ✦ **DIMENSIONS:** 14.19"W X 30"H X 5.75"D
- ✦ **@80°F / 60%RH**
PINT CAPACITY: 37 PINTS / 4.6 GALLONS PER DAY
ENERGY FACTOR: 2.4 L/KWH
- ✦ **@65°F / 60%RH**
PINT CAPACITY: 22 PINTS / 2.75 GALLONS PER DAY
ENERGY FACTOR: 1.64 L/KWH
- ✦ **HVAC SYSTEM INTEGRATION:** NO
- ✦ **VENTILATION:** NO
- ✦ **CONTROL:** ON-BOARD DEHUMIDISTAT

SURFACE MOUNT KIT

PART NUMBER: 4037766

The Ultra Series Surface Mount Kit can be used to permanently install the Ultra Series MD33 In-Wall Dehumidifier to masonry or CMU block when through-the-wall installation is not available.



2X4 WALL MOUNTING BEZEL KIT

PART NUMBER: 4037767

The Ultra Series 2X4 Wall Mounting Bezel Kit can be used to permanently install the Ultra Series MD33 In-Wall Dehumidifier in a 2X4 cavity without having to cut a hole in both sides of the drywall. The powder-coated metal bezel wraps around the front face of the dehumidifier giving it a completely polished look to blend into any environment.



COMMITTED TO YOUR SUCCESS.

At Santa Fe, we are committed to partnering with you. After all, when you succeed, we succeed. And that's why we're with you every step of the way as you become a dealer of Santa Fe and our line of dehumidifiers.

WHAT YOU CAN EXPECT FROM US

- + Comprehensive product training
- + Application and installation guidance
- + Field service and warranty repairs
- + Marketing and product literature
- + Customer service excellence



The Santa Fe Difference:

- + **WARRANTY/QUALITY/LOW MAINTENANCE**
Industry-Leading 5-Year Warranty
- + **AIR FILTRATION**
Industry-Leading MERV-13 Filters

- + **ENERGY SAVINGS AND EFFICIENCY**
Up to 36% More Efficient than Competitors
- + **SALES SUPPORT**
Dedicated Support Nationwide
- + **HEADQUARTERED IN MADISON, WI**
Engineered and Supported in the USA



FILTERS

► COMPACT70 / ULTRA70



MERV-13

- + SIZE: 11" x 9" x 1"
- + PART NUMBER: 4037724
- + COMPATIBLE DEHUMIDIFIERS:
 - Compact70
 - Ultra70



PRE-FILTER

- + SIZE: 11" x 9" x .25"
- + PART NUMBER: 4027168
- + COMPATIBLE DEHUMIDIFIERS:
 - Compact70

► COMPACT70



WASHABLE

- + SIZE: 11.4" x 9" x 0.75"
- + PART NUMBER: 4044385

► OASIS™ 105



MERV-13

- + SIZE: 14" x 12" x 1"
- + PART NUMBER: 4042005

► CLASSIC / IMPACT155



MERV-13

- + SIZE: 16" x 20" x 2"
- + PART NUMBER: 4039391

► ULTRA98 / ULTRA120



MERV-13

- + SIZE: 14" x 17.5" x 1"
- + PART NUMBER: 4037722

► ADVANCE DRY110 / ULTRA V155



MERV-13

- + SIZE: 17.5" x 14" x 1.75"
- + PART NUMBER: 4037722-01

► ULTRA V205



MERV-13

- + SIZE: 17.5" x 17.5" x 1.75"
- + PART NUMBER: 4042787

► ULTRAMD33



WASHABLE

- + SIZE: 11" x 12.6" x 0.1"
- + PART NUMBER: 4037714

Santa Fe dehumidifiers are equipped with the best filtration on the market. Our standard MERV-13 filters capture harmful contaminants in the air and keep the units running at peak efficiency.



INSTALLATION ACCESSORIES

► DEH 3000 / 3000R CONTROL



- + **DEH 3000 PART NUMBER:** 4028539
- + **DEH 3000R PART NUMBER:** 4028407
- + **COMPATIBLE DEHUMIDIFIERS:**
 - All Ultra Series except the UltraMD33

► SMARTAIRE™ REMOTE SENSOR



- + **PART NUMBER:** 4044000
- + **COMPATIBLE DEHUMIDIFIERS:**
 - Advance Dry110 and Ultra V155

► HANG KITS



- + **PART NUMBER:** 4036695
- + **COMPATIBLE DEHUMIDIFIERS:**
 - Compact70
 - Ultra70
 - Ultra98
 - Ultra120



- + **PART NUMBER:** 4042835
- + **COMPATIBLE DEHUMIDIFIERS:**
 - Oasis105
 - Impact155



- + **PART NUMBER:** 4044745
- + **COMPATIBLE DEHUMIDIFIERS:**
 - Advance Dry110
 - Ultra V155

► CONDENSATE PUMPS



- + **PART NUMBER:** 4022220
- + **COMPATIBLE DEHUMIDIFIERS:**
 - All Santa Fe dehumidifiers except the Ultra MD33

► DEHUMIDIFIER RISERS



- + **PART NUMBER:** 4042109
1-Pack (4 Risers/Pack)
- + **PART NUMBER:** 4041602
10-Pack (4 Risers/Pack)
- + **COMPATIBLE DEHUMIDIFIERS:**
 - All except the Classic and UltraMD333

► SMARTAIRE™ POWER DAMPER



- + **PART NUMBER:** 4042960
- + **COMPATIBLE DEHUMIDIFIERS:**
 - All Ultra Series dehumidifiers except the UltraMD33

► DUCT KITS



- + **COMPACT70**
- + **RETURN DUCT KIT**
PART NUMBER: 4030204
- + **SUPPLY DUCT KIT**
PART NUMBER: 4030203



- + **OASIS™105**
- + **SUPPLY DUCT KIT PART**
NUMBER: 4042275
- + **SUPPLY AND RETURN**
DUCT KIT PART NUMBER:
4042265



- + **ADVANCE DRY110**
- + **SUPPLY DUCT KIT**
PART NUMBER: 4033039



- + **IMPACT155**
- + **RETURN DUCT KIT**
PART NUMBER: 4028610
- + **SUPPLY DUCT KIT**
PART NUMBER: 4028607



- + **CLASSIC**
- + **SUPPLY DUCT KIT PART**
NUMBER: 4020623
- + **SUPPLY AND RETURN**
DUCT KIT PART NUMBER:
4021453

PRODUCT

SET IT + FORGET IT.

Santa Fe offers a full line of free-standing dehumidifiers. What does this mean? It means a quick solution to protect your investment. With no buckets to empty.

Applications include:



- + Basements
- + Crawl Spaces
- + Garages
- + Theater/Multi-Use Areas
- + Workshops
- + Storage Rooms
- + Exercise Rooms



SANTA-FE™

6-YEAR TOTAL PEACE OF MIND WARRANTY

5-YEAR FULL REPLACEMENT + 1-YEAR PARTS

	COMPACT70	OASIS105
		
@ 80°F / 60%RH WATER REMOVAL	70 PINTS/DAY 8.75 GALLONS/DAY	102 PINTS/DAY 12.75 GALLONS/DAY
EFFICIENCY	5.5 PINTS/KWH	7.5 PINTS/KWH
ENERGY FACTOR	2.6 L/KWH	3.54 L/KWH
@ 65°F / 60%RH WATER REMOVAL	43.7 PINTS/DAY 5.4 GALLONS/DAY	67 PINTS/DAY 8.37 GALLONS/DAY
EFFICIENCY	4.1 PINTS/KWH	5.95 PINTS/KWH
ENERGY FACTOR	1.96 L/KWH	2.81 L/KWH
CURRENT DRAW	3.7 AMPS*	6.1 AMPS*
REFRIGERANT	R454B	R454B
AIR FILTER	MERV-13	MERV-13
DIMENSIONS	12" W 12" H 21" D	24" W 14.5" H 16" D
WEIGHT	55 LBS.	59 LBS.
SIZED FOR CRAWL SPACES	UP TO 2,600 FT ² TIGHTLY SEALED UP TO 2,200 FT ² MODERATELY SEALED UP TO 1,800 FT ² LOOSELY SEALED	UP TO 3,300 FT ² TIGHTLY SEALED UP TO 2,900 FT ² MODERATELY SEALED UP TO 2,500 FT ² LOOSELY SEALED
SIZED FOR BASEMENTS	UP TO 2,200 FT ² TIGHTLY SEALED UP TO 2,000 FT ² MODERATELY SEALED UP TO 1,800 FT ² LOOSELY SEALED	UP TO 2,600 FT ² TIGHTLY SEALED UP TO 2,400 FT ² MODERATELY SEALED UP TO 2,200 FT ² LOOSELY SEALED
WARRANTY	6 YEARS	6 YEARS

*@ 65°F / 60%RH

** @ 80°F / 60%RH



LINE UP

ADVANCE DRY110



CLASSIC



IMPACT155



ULTRAMD33



110 PINTS/DAY
13.75 GALLONS/DAY

7.7 PINTS/KWH

3.66 L/KWH

70 PINTS/DAY
8.75 GALLONS/DAY

5.92 PINTS/KWH

2.81 L/KWH

4.1 AMPS*

R454B

MERV-13

14.35" W
24" H
29" D

102 LBS.

UP TO **3,600** FT²
TIGHTLY SEALED
UP TO **3,200** FT²
MODERATELY SEALED
UP TO **2,800** FT²
LOOSELY SEALED

UP TO **2,900** FT²
TIGHTLY SEALED
UP TO **2,700** FT²
MODERATELY SEALED
UP TO **2,500** FT²
LOOSELY SEALED

6 YEARS

116 PINTS/DAY
14.5 GALLONS/DAY

7.27 PINTS/KWH

3.43 L/KWH

76 PINTS/DAY
9.5 GALLONS/DAY

5.9 PINTS/KWH

2.8 L/KWH

4.5 AMPS*

R454B

MERV-13

20" W
36" H
17" D

110 LBS.

NOT
APPLICABLE
TO CRAWL SPACES

UP TO **2,900** FT²
TIGHTLY SEALED
UP TO **2,700** FT²
MODERATELY SEALED
UP TO **2,500** FT²
LOOSELY SEALED

6 YEARS

155 PINTS/DAY
19.375 GALLONS/DAY

7.3 PINTS/KWH

3.4 L/KWH

104 PINTS/DAY
13 GALLONS/DAY

6.1 PINTS/KWH

2.89 L/KWH

8.0 AMPS**

R410A

MERV-13

20.25" W
21.75" H
38" D

140 LBS.

UP TO **4,400** FT²
TIGHTLY SEALED
UP TO **4,000** FT²
MODERATELY SEALED
UP TO **3,600** FT²
LOOSELY SEALED

UP TO **4,000** FT²
TIGHTLY SEALED
UP TO **3,800** FT²
MODERATELY SEALED
UP TO **3,600** FT²
LOOSELY SEALED

6 YEARS

@ 80°F / 60%RH
WATER REMOVAL

EFFICIENCY

ENERGY FACTOR

@ 65°F / 60%RH
WATER REMOVAL

EFFICIENCY

ENERGY FACTOR

CURRENT DRAW

REFRIGERANT

AIR FILTER

DIMENSIONS

WEIGHT

SIZED FOR
IN-WALL
APPLICATIONS

WARRANTY

37 PINTS/DAY
4.6 GALLONS/DAY

5.1 PINTS/KWH

2.4 L/KWH

22 PINTS/DAY
2.75 GALLONS/DAY

3.46 PINTS/KWH

1.64 L/KWH

2.2 AMPS*

R454B

WASHABLE

14.19" W
30" H
5.75" D




39 LBS.

UP TO **1,200** FT²

6 YEARS



The UltraMD33 In-Wall Dehumidifier is ideal for multi-family applications, basements, hotels and other spaces needing dehumidification.

PRODUCT

	ULTRA70	ULTRA98	ULTRA120
			
@ 80°F / 60%RH WATER REMOVAL	70 PINTS/DAY 8.75 GALLONS/DAY	100 PINTS/DAY 12.5 GALLONS/DAY	118 PINTS/DAY 14.75 GALLONS/DAY
EFFICIENCY	5.5 PINTS/KWH	6.12 PINTS/KWH	5.7 PINTS/KWH
ENERGY FACTOR	2.6 L/KWH	2.89 L/KWH	2.7 L/KWH
@ 73°F / 60%RH WATER REMOVAL	52.5 PINTS/DAY 6.5 GALLONS/DAY	71.4 PINTS/DAY 8.9 GALLONS/DAY	88 PINTS/DAY 11 GALLONS/DAY
EFFICIENCY	4.3 PINTS/KWH	4.68 PINTS/KWH	4.45 PINTS/KWH
ENERGY FACTOR	2.04 L/KWH	2.22 L/KWH	2.1 L/KWH
CURRENT DRAW	4.1 AMPS*	5.6 AMPS*	7.4 AMPS*
REFRIGERANT	R454B	R454B	R454B
BLOWER	150 CFM @ 0.0" WG 140 CFM @ 0.2" WG 130 CFM @ 0.4" WG	320 CFM @ 0.0" WG 297 CFM @ 0.2" WG 215 CFM @ 0.4" WG	350 CFM @ 0.0" WG 285 CFM @ 0.2" WG 210 CFM @ 0.4" WG
AIR FILTER	MERV-13	MERV-13	MERV-13
DIMENSIONS	12" W 12" H 28" D	14.5" W 19.5" H 32.4" D	14.4" W 21" H 32.2" D
WEIGHT	55 LBS.	81 LBS.	91 LBS.
SIZING	UP TO 1,800 FT. ²	UP TO 2,300 FT. ²	UP TO 3,000 FT. ²
WARRANTY	6 YEARS	6 YEARS	6 YEARS



LINE UP

ULTRA V155	ULTRA V205
	
155 PINTS/DAY 19.3 GALLONS/DAY	205 PINTS/DAY 25.625 GALLONS/DAY
7.1 PINTS/KWH	7.5 PINTS/KWH
3.35 L/KWH	3.5 L/KWH
128 PINTS/DAY 16 GALLONS/DAY	173 PINTS/DAY 21.6 GALLONS/DAY
6.5 PINTS/KWH	6.3 PINTS/KWH
3.08 L/KWH	3.0 L/KWH
7.1 AMPS**	12.5 AMPS**
R454B	R454B
435 CFM @ 0.0" WG 395 CFM @ 0.2" WG 360 CFM @ 0.4" WG	550 CFM @ 0.0" WG 515 CFM @ 0.2" WG 470 CFM @ 0.4" WG
MERV-13	MERV-13
14.35" W 24" H 39.25" D	26.75" W 20.75" H 38" D
112 LBS.	148 LBS.
UP TO 3,500 FT. ²	UP TO 5,000 FT. ²
6 YEARS	6 YEARS

*@ 73°F / 60%RH
** @ 80°F / 60%RH

DUCT + VENTILATE.

The Ultra Series, formerly the Ultra Aire brand, focuses on providing dehumidification to the whole house or project. In addition, it provides the option to ventilate a home, with the purpose of maintaining a healthy and safe living environment.



SANTA-FE™

6-YEAR TOTAL PEACE OF MIND
WARRANTY

5-YEAR FULL REPLACEMENT + 1-YEAR PARTS



SANTA-FE™
INDOOR AIR QUALITY SOLUTIONS



Contact us:

Santa-Fe-Products.com or 800-533-7533

©2024 Therma-Stor LLC
TS-2073 05/25 Rev D