

# 60cm Series 9 Contemporary Warming Drawer

Series 9 | Contemporary

Stainless Steel



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Contemporary styling.

- A companion product, designed to match with other Contemporary style Fisher & Paykel products
- Space to keep six standard-sized place settings evenly warm
- Easy to clean smooth-glass base

- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

## DIMENSIONS

|        |        |
|--------|--------|
| Height | 140 mm |
| Width  | 596 mm |
| Depth  | 567 mm |

## FEATURES & BENEFITS

### Complementary Design

Our Warming Drawer comes in either a stylish black reflective glass or brushed stainless steel, for seamless pairing with our matching ovens.

### Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

### Easy To Clean

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

### Easy To Use

Handle-free, push-to-open with capacitive touch controls, our Warming Drawer gives you the freedom to keep plates or cups warm while you continue to cook.

### Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

### Safe And Sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

## SPECIFICATIONS

### Capacity

|                          |        |
|--------------------------|--------|
| Cappuccino cups          | 20     |
| Espresso cups            | 42     |
| Maximum allowable weight | 25 kg  |
| Place settings           | 6      |
| Usable depth             | 408 mm |
| Usable height            | 98 mm  |
| Usable width             | 535 mm |

### Cleaning

- Easy clean smooth-glass base

### Controls

- Audio feedback
- Automatic pre-set temperatures
- Automatic timers30', 45', 1h, 2h, 4h, 6h
- Delayed start
- Electronic capacitive touch controls
- On/Off indicator
- Pre-set heating functions
- Push-to-open drawer
- Standby mode

|                     |   |
|---------------------|---|
| Functions           |   |
| Cups                | • |
| Dehydrate           | • |
| Number of functions | 6 |
| Plates              | • |
| Rapid proof         | • |
| Slow cook           | • |
| Warm                | • |

|                           |           |
|---------------------------|-----------|
| Performance               |           |
| Heated glass base and fan | •         |
| Low temperature cooking   | •         |
| Temperature levels        | 6         |
| Temperature range         | 35°C-85°C |

|                    |                           |
|--------------------|---------------------------|
| Power requirements |                           |
| Amperage           | 10 A                      |
| Power cord length  | 1800 mm                   |
| Power outlet       | 3-prong<br>grounding-type |
| Supply frequency   | 50 Hz                     |
| Supply voltage     | 220 V                     |

|                                                                 |        |
|-----------------------------------------------------------------|--------|
| Product dimensions                                              |        |
| Adjustable front door panel to align with surrounding cabinetry | •      |
| Depth                                                           | 567 mm |
| Height                                                          | 140 mm |
| Width                                                           | 596 mm |

|                                   |   |
|-----------------------------------|---|
| Safety                            |   |
| Automatic turn off after 12 hours | • |
| Full extension slides             | • |
| SKU 82107                         |   |

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at [fisherpaykel.com](https://fisherpaykel.com)

- ↓ 2D-DWG Warming Drawer
- ↓ 2D-DXF Warming Drawer
- ↓ Archicad Warming Drawer
- ↓ Data Sheet Warming Drawer
- ↓ Service & Warranty
- ↓ Installation Guide
- ↓ Revit Warming Drawer
- ↓ Rhino Warming Drawer
- ↓ Sketchup Warming Drawer
- ↓ User Guide Warming Drawer
- ↓ User Guide

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



**A PEACE OF MIND SALE**  
**24 Hours 7 Days a Week Customer Support**  
T 1300 650 590 W [www.fisherpaykel.com](https://www.fisherpaykel.com)