

# HEATING & COOLING

FROM ONE  
COMPACT UNIT

Air | Side-Discharge  
Heat Pump  
RD16AY



## ENDEAVOR®

### Ruud® Endeavor® Line *Achiever Plus® Series*

Expertly engineered to deliver high efficiencies year-round, the Ruud Endeavor Line *Achiever Plus* Series RD16AY Side-Discharge Heat Pump features a compact footprint, making it the perfect solution when space is at a premium.

[Ruud.com/Endeavor](http://Ruud.com/Endeavor)



Most Efficient  
**2025**  
[www.energystar.gov](http://www.energystar.gov)

  
Sound and Space  
Constraint Solution



RELY ON RUUD.™



# Comfort & Efficiency

## Innovation You Can Count On

Patented industry-first features and 360+1 design make the Ruud Endeavor RD16AY a smart choice.



### Peace-Of-Mind Performance

Relax, you're covered by one of the best warranties in the industry<sup>1</sup>—10 Year Conditional Parts when installed as a heat pump only or as part of a system.



### Less Environmental Impact

The 7mm condenser coil reduces refrigerant requirements up to 15%. This lowers the amount of greenhouse gases emitted while contributing to our sustainability goal of a 50% reduction in our greenhouse gas footprint.<sup>4</sup> A win for all of us.



### Energy Savings

Just like a vehicle's MPG rating, the higher the SEER2, EER2 and HSPF2 rating (Seasonal Energy Efficiency Ratio / Energy Efficiency Ratio / Heating Seasonal Performance Factor), the higher the efficiency of your heat pump—resulting in more energy savings. Keep in mind, other factors such as system matching, sizing, ductwork and installation also impact the overall efficiency. By working with a properly trained contractor, you can be confident that you are choosing the best heating and cooling system for your home's comfort—and your finances.



### Space-Saver Solution

Part of our Sound & Space Constraint Solution, the *Achiever Plus* Series Side-Discharge Heat Pump is the ideal product for when installation locations are cramped. It features a small footprint with size options as low as 31.8" tall and 19.8" wide. This unit was designed to deliver whole-home comfort quietly and efficiently—further proof that good (and quiet) things come in small packages.



### Rugged Curb Appeal

Steel panels provide excellent support and protection to internal components, while the overall modern cabinet aesthetics, including the powder coat paint system and rust-resistant screws, allow your unit to put its best face forward for years to come.



### Ultimate Comfort

Inverter driven, variable speed, twin rotary compressor technology features fully variable cooling and heating operation between 45% and 100% of capacity<sup>2</sup> to continuously meet your ever-changing needs. You'll enjoy exact temperature and advanced humidity control that combine to exceed your optimal comfort expectations.



### Quiet Operation

Efficient home comfort shouldn't be noisy. That's why our heat pumps are designed with acoustics in mind. Sound-dampening features such as refrigerant tubing design, fan blade approach and innovative compressor and drive technologies ensure that as efficiency goes up, sound levels stay low—as low as 50 dBA.<sup>5</sup>

#### SOUND RATING

THIS MODEL

|    |                     |
|----|---------------------|
| 30 | Soft Whisper        |
| 40 | Light Rain          |
| 50 | Refrigerator Hum    |
| 60 | Normal Conversation |
| 70 | Washing Machine     |
| 80 | Alarm Clock         |

ENDEAVOR



To learn more visit  
[Ruud.com/Endeavor](http://Ruud.com/Endeavor)

# Made Simple



## A Smart Way to Live Both Comfortably & Sustainably

Many Ruud products have sustainability features, but the RD16AY has earned our Sustainability Standout® seal, indicating it's among the best of the best. We created the seal to help you more easily find the products that save energy, save money and save the planet.



## Among Heat Pumps, This One's A Star<sup>7</sup>

Earning ENERGY STAR® recognition means products meet strict energy efficiency guidelines set by the U.S. Environmental Protection Agency. ENERGY STAR certified heating and cooling equipment can enhance the comfort of your home while saving energy—which saves money on utility bills and protects our climate by reducing harmful carbon pollution and other greenhouse gases.



# ENDEAVOR®

### AVAILABLE MODELS

| Model No.     | Description |
|---------------|-------------|
| RD16AY24AJVCA | 2 ton       |
| RD16AY36AJVCA | 3 ton       |
| RD16AY48AJVCA | 4 ton       |
| RD16AY60AJVCA | 5 ton       |




The Ruud Endeavor RD16AY—when installed as part of a complete AHRI-matched, Ruud EcoNet-enabled system—operates with the easy-to-use EcoNet Smart Thermostat, which optimizes system performance and provides a new level of protection and precision comfort **with features like:**

- Communication with latest sensor technology
- Control of your thermostat from anywhere via the EcoNet App<sup>8</sup>
- Alerts sent directly to your phone or email



EcoNet Mobile App



EcoNet Smart Thermostat



# General Data

ENDEAVOR®



To learn more visit  
[Ruud.com/Endeavor](http://Ruud.com/Endeavor)



| GENERAL DATA                         |               |               |               |               |
|--------------------------------------|---------------|---------------|---------------|---------------|
| Model No.                            | RD16AY24AJVCA | RD16AY36AJVCA | RD16AY48AJVCA | RD16AY60AJVCA |
| Nominal Tonnage                      | 2             | 3             | 4             | 5             |
| Valve Connections                    |               |               |               |               |
| Liquid Line O.D. – in.               | 3/8           | 3/8           | 3/8           | 3/8           |
| Suction Line O.D. – in.              | 3/4           | 3/4           | 7/8           | 7/8           |
| Refrigerant (R-454B) Furnished oz.   | 76            | 141           | 194           | 222           |
| Coil Type                            | 7mm           | 7mm           | 7mm           | 7mm           |
| Outdoor Coil                         |               |               |               |               |
| Net Face Area – Outer Coil – sq. ft. | 11.0          | 15.1          | 17.2          | 17.2          |
| Net Face Area – Inner Coil – sq. ft. | N/A           | 15.1          | 17.2          | 17.2          |
| Tube Diameter – in.                  | 0.276         | 0.276         | 0.276         | 0.276         |
| Number of Rows                       | 1             | 2             | 3             | 3             |
| Fins Per Inch                        | 18            | 18            | 16            | 16            |
| Outdoor Fan                          |               |               |               |               |
| Diameter – in.                       | 26            | 28            | 24            | 24            |
| Number of Blades                     | 3             | 3             | 3             | 3             |
| Motor HP                             | 1/2           | 1/2           | 1/3           | 1/3           |
| Number of Fans                       | 1             | 1             | 2             | 2             |
| CFM                                  | 3,175         | 2,820         | 4,350         | 5,400         |
| RPM                                  | 550           | 450           | 550           | 675           |
| Watts                                | 115           | 106           | 191           | 327           |
| Shipping Weight – lbs.               | 205           | 272           | 347           | 354           |
| Operating Weight – lbs.              | 177           | 230           | 296           | 306           |



# Unit Dimensions &

ENDEAVOR

| UNIT DIMENSIONS      |                    |                    |                   |                    |                    |                   |
|----------------------|--------------------|--------------------|-------------------|--------------------|--------------------|-------------------|
| Model No.            | OPERATING          |                    |                   | SHIPPING           |                    |                   |
|                      | Height<br>in. (mm) | Length<br>in. (mm) | Width<br>in. (mm) | Height<br>in. (mm) | Length<br>in. (mm) | Width<br>in. (mm) |
| <b>RD16AY24AJVCA</b> | 31.8 (80.4)        | 40.4 (102.6)       | 19.8 (50.3)       | 38 (96.4)          | 48.43 (123)        | 22.05 (56)        |
| <b>RD16AY36AJVCA</b> | 31.8 (80.4)        | 40.4 (102.6)       | 19.8 (50.3)       | 38 (96.4)          | 48.43 (123)        | 22.05 (56)        |
| <b>RD16AY48AJVCA</b> | 36.6 (93)          | 40.4 (102.6)       | 19.8 (50.3)       | 43.3 (110)         | 48.43 (123)        | 22.05 (56)        |
| <b>RD16AY60AJVCA</b> | 46.4 (117.8)       | 42.3 (107.4)       | 22.8 (57.8)       | 53.94 (137)        | 50 (127)           | 25 (63.5)         |



**2 ton**

RD16AY24AJVCA



**3 ton**

RD16AY36AJVCA



**4 ton**

RD16AY48AJVCA



**5 ton**

RD16AY60AJVCA



To learn more visit  
[Ruud.com/Endeavor](http://Ruud.com/Endeavor)

# Available Accessories

| ACCESSORIES                                     |       |                |                |                |                |
|-------------------------------------------------|-------|----------------|----------------|----------------|----------------|
| Model No.                                       |       | RD16AY24AJVCA  | RD16AY36AJVCA  | RD16AY48AJVCA  | RD16AY60AJVCA  |
| Compressor Crankcase Heater                     |       | 44-103663-15   | 44-103663-15   | 44-103663-15   | 44-103663-15   |
| Base Pan Heater Connector Kit*                  |       | 45-110492-01   | 45-110492-01   | 45-110492-01   | 45-110492-01   |
| Low Ambient Control                             |       | Included       | Included       | Included       | Included       |
| Compressor Sound Cover                          |       | Included       | Included       | Included       | Included       |
| Low Pressure Control                            |       | Included       | Included       | Included       | Included       |
| High Pressure Control                           |       | Included       | Included       | Included       | Included       |
| Liquid Line Solenoid<br>(24 VAC, 50/60 Hz)      | Valve | 200RD2T3TVLC   | 200RD2T3TVLC   | 200RD2T3TVLC   | 200RD2T3TVLC   |
|                                                 | Coil  | 61-AMG24V      | 61-AMG24V      | 61-AMG24V      | 61-AMG24V      |
| Liquid Line Solenoid<br>(120/240 VAC, 50/60 Hz) | Valve | 200RD2T3TVLC   | 200RD2T3TVLC   | 200RD2T3TVLC   | 200RD2T3TVLC   |
|                                                 | Coil  | 61-AMG120/240V | 61-AMG120/240V | 61-AMG120/240V | 61-AMG120/240V |

\*Required for heating element commissioning.

## We Thought of Everything... & Then Some



We evaluate every detail of a product from top to bottom, inside and out and every angle in between. That's 360+1. And that's why you can count on this heat pump to bring you and your family years of efficient and dependable comfort.



## TESTED. TRUSTED. TOUGH.

From the smallest part to complete comfort systems, we engineer quality into everything we make to be sure it's tough enough to deliver the ultimate performance you count on day after day, year after year. That reliability is what makes Ruud different—and better.

# ENDEAVOR®



## Simplified Install & Service with Bluetooth Technology

Built-in Bluetooth® connectivity makes it faster and easier for your contractor to install and service your new system.<sup>9</sup> This can help lower your costs and help make your home comfortable again—fast.



## Designing for Sustainability with Low GWP

For 2025, the Environmental Protection Agency (EPA) has set a global warming potential (GWP) limit of 700 for refrigerant used in heating and cooling systems. This new requirement will result in a 78%<sup>10</sup> lower GWP than previous-generation refrigerants—with only minimal changes to system installation. For us, this is another step toward our continued sustainability goal of reducing greenhouse gas emissions, while still delivering an exceptional level of energy efficient, dependable comfort.

## Federal Incentives Available (conditions apply)

As part of the Inflation Reduction Act of 2022, homeowners may be eligible for up to \$2,000 for qualified heat pumps as part of the Energy Efficient Home Improvement Federal Tax Credit (Tax Section 25C). The RD16AY also meets the High Efficiency Electric Home Rebate Program criteria and may qualify for additional funds—dependent on state participation and household income.

Visit [Ruud.com/Federal-Incentives](https://Ruud.com/Federal-Incentives) for complete details and conditions.



[Ruud.com](https://Ruud.com)

## Innovating Since 1925

As the only brand bringing innovative air and water solutions to homes and businesses around the world, Ruud continues to deliver advanced comfort, savings and experiences to our customers—just as we've done since 1925.

## FEATURES AT A GLANCE

Cooling & Heating Efficiencies Up To:  
17 SEER2 / 10.5 EER2 / 8.5 HSPF2

Nominal Sizes: 2 to 5 Tons

Cooling & Heating Capacities:  
22.8 to 55.5 kBTU

EcoNet® Enabled: Yes<sup>11</sup>

Sound Rating<sup>9</sup>: As low as 50 dBA

Compressor Type: Inverter Driven,  
Variable Speed<sup>2</sup> Twin Rotary

Condenser Coil Type: 7mm

Operating Range:

Cooling: 50–125°F

Heating: -22–70°F

Refrigerant Type: R-454B

PlusOnes:



**PlusOne® Variable Speed Twin Rotary Compressor & Inverter Drive** – Variable speed operation with EcoNet® Smart Thermostat or legacy and other thermostats<sup>2,11</sup>



**PlusOne Diagnostics<sup>9</sup>** – Bluetooth technology aids in quick & easy service



**PlusOne Refrigerant Detection System™<sup>12</sup>** – Integrated, patented design providing system protection and homeowner peace-of-mind with low GWP refrigerant monitoring

## Additional Standard Features:

- Filter Drier (Field-installed)
- Front Seating Service Valves
- Internal Pressure Relief Valve
- Powder Coated Paint
- Rust-resistant Screws
- Optimized Venturi Airflow
- External Gauge Ports
- Easy Accessibility
- Base Pan Heating Element

(Commissioning Kit Required)

## Limited Warranty<sup>1</sup>:

Conditional Parts – 10 Years

(registration required—no AHRI-matched system requirement)



### Ruud USA

5600 Old Greenwood Road  
Fort Smith, Arkansas 72908



### Ruud Canada Ltd. / Ltée

125 Edgeware Road, Unit 1  
Brampton, Ontario L6Y 0P5

*Rheem Sales Company, Inc. manufactures the Ruud brand of residential heating & cooling products. In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.*

<sup>1</sup>For complete details of the limited and conditional warranties, including applicable terms and conditions, contact your local Contractor or go to [Ruud.com](https://Ruud.com) for a copy of the product warranty certificate; warranty applies to a heat pump only or system installation; Does not require the heat pump to be part of a properly matched system as specified by the Manufacturer and the Air Conditioning Heating & Refrigeration Institute (AHRI). <sup>2</sup>When installed with the EcoNet Smart Thermostat or with legacy and other thermostats when the utility 1 and 2 jumpers are installed. Features two-stage (70% and 100% capacity) operation when installed with legacy and other thermostats when the utility 1 and 2 jumpers are not installed; The 2-ton model features a single rotary compressor. <sup>3</sup>Residential Building Electrification in CA: Consumer economics, greenhouse gases and grid impacts, April 2019. <sup>4</sup>Rheem's goal is to release by 2025 a line of heating, cooling, and water heating products that reduce greenhouse gas emissions by 50% as compared to products available in 2019. Reduction calculations will be based on the products' use phase emissions only and utilize average emission factors to account for variability in electricity grids. Reduction calculations will not consider upstream or manufacturing impacts, but use phase emissions account for the majority of the products' impact. At this time, these figures have not been independently verified by a third party. <sup>5</sup>Based on Internal R&D Testing, 2024. Sound levels are also dependent on proper installation and location of outdoor product. <sup>6</sup>When installed as part of a complete AHRI-matched Ruud EcoNet-enabled system; Does not apply to coil-only matched systems. <sup>7</sup>Valid for qualifying AHRI-matched Ruud systems; Proper sizing and installation of equipment is critical to achieve optimal performance. Ask your contractor for details or visit [EnergyStar.gov](https://EnergyStar.gov). <sup>8</sup>Wi-Fi broadband internet connection required. Download the EcoNet® App from the App Store® or Google Play® to set up your EcoNet Smart Thermostat. Receipt of notifications depend on home Wi-Fi setup. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates. <sup>9</sup>When installed as part of a complete Ruud system where both the outdoor and indoor components feature Bluetooth technology. <sup>10</sup>When comparing the GWP of R-454B to R-410A refrigerant. <sup>11</sup>When installed as part of a complete AHRI-matched Ruud EcoNet-enabled system. <sup>12</sup>Factory- or field-installed in the furnace coil or air handler and is applicable to the complete heating and cooling system featuring Low GWP Refrigerant (A2L).



© 2025 Rheem Manufacturing Company. Ruud trademarks owned by Rheem Manufacturing Company.

Printed in the USA | 05/25 | QG | Form No. M22-3132