

## HCS-8300KMX2 Congress Gigabit Network Switcher



### Functions

- Based on TAIDEN originated GMC-STREAM Gigabit Multimedia Congress Stream technology
- Sync power on/off with the Congress Main Unit
- Built-in PoE switch to choose way of power supply:
  - ON: connecting DELEGATE port to tabletop congress terminals or the Distributor HCS-8368T/50 for power supply and transmission of control data and multimedia data
  - OFF: DELEGATE port supporting daisy-chain connection to HCS-8368/50 Series Paperless Multimedia Congress Terminal with power supply via 3 2P aviation plugs

### Interconnections

- 1 × RJ45 standard port for connection with Ethernet switcher
- 5 × RJ45 standard port for connection with HCS-8368/50 Series Paperless Multimedia Congress Terminal (via Cat.5e/Cat.6 cable)
- 2 × 6P-DIN interface for connection with the Congress Main Unit or cascading to another HCS-8300KMX2 (equipped with CBL6PP-01 - 1-meter 6-pin extension cable with two plugs)
- 3 × 2P aviation plug for supplying power to HCS-8368/50 series Multimedia Congress Terminal (equipped with CBL4PK-01 - 1-meter power adapter cable)

### Technical Specifications

#### Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz  
 Power output.....Four power outputs, each output 48V DC, 3A  
 Power consumption.....350 W

#### Mechanical

Mounting.....Tabletop or mounted in a 19" rack  
 Dimensions (h x w x d).....43 × 483 × 208 mm  
 (1U high, full rack width)  
 Weight.....3.6 kg  
 Color.....Gray (PANTONE 425 C)

### Ordering Information

HCS-8300KMX2.....Congress Gigabit Network Switcher  
 (for G3 multimedia congress terminal)

## HCS-8368T Distributor



### Functions

- Extension of HCS-8368/50 series tabletop congress terminal in PoE mode

### Interconnections

- 1 × RJ45 standard port for connection with HCS-8300KMX2
- 7 × RJ45 standard port for connection with HCS-8368/50 tabletop congress terminal on each port
- DC power socket for external power supply to guarantee a stable signal transmission
- If five or more output ports are used, please connect to external power adapter

### Technical Specifications

#### Electrical

Power supply.....DC 48 V, 2 A  
 Power consumption.....90 W

#### Mechanical

Mounting.....Tabletop  
 Dimensions (h x w x d).....40 × 150 × 100 mm  
 Color.....Gray (PANTONE 425 C)  
 Weight.....0.4 kg

### Ordering Information

HCS-8368T.....Distributor  
 (for G3 tabletop multimedia congress terminal)

## HCS-8368T/50 Distributor



### Functions

- Extension of HCS-8368/50 series tabletop congress terminal in PoE mode

### Interconnections

- 1 × RJ45 standard port for connection with HCS-8300KMx2
- 7 × RJ45 standard port for connection with HCS-8368/50 tabletop congress terminal on each port
- DC power socket (2P aviation socket) for external power supply to guarantee a stable signal transmission
- If five or more output ports are used, please connect to external power adapter

### Technical Specifications

#### Electrical

Power supply.....DC 48 V, 2 A  
Power consumption.....90 W

#### Mechanical

Mounting.....Tabletop  
Dimensions (h x w x d).....41 × 168 × 103 mm  
Color.....Black (PANTONE 419 C)  
Weight.....0.4 kg

### Ordering Information

HCS-8368T/50.....Distributor  
(for G3 tabletop multimedia congress terminal)