



30773505



IP55

Intermediate switch surface-mounted Berker W.1, grey/light grey matt

Technical features

Architecture

Type of control unit	single rocker
----------------------	---------------

Configuration

- intermediate

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Switching current	10 AX
-------------------	-------

Materials

RAL colour	RAL 7011 - Iron grey
Colour of design line	grey/light grey
Colour	dark grey
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	61,5 mm
Height	76 mm
Width	76 mm

Installation, mounting

- for screw fastening

Connection

Type of connection	Quickconnect
<ul style="list-style-type: none">- with two clip-in places for Wago 2-wire connection terminals in the housing floor- with Wago clip-in 2-wire connection terminal for wiring- with plug-in terminals	

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Pins of quick-release lock made of ZAMAK