


Programming Remote Directly to Motor

- 1. Press and hold buttons 1 and 2 (top 2 buttons) on the new remote simultaneously. The green indicator light on the remote will turn on. Continue holding both buttons until the light turns off (in about 5 seconds). remote will turn on. Continue holding both buttons until the light turns off (in about 5 seconds).
- 2. You have now successfully adjusted the frequency to match your motor's frequency.
- 3. Find the Code Set button on your motor. If your motor has a clear plastic cover over the buttons, remove it to access them.
- 4. Briefly press and release the Code Set button (labelled 'DOOR CODE') on the motor. A red LED on the motor will light up.
- 5. Press the desired button on the new remote that you want to pair with the motor. Hold it for 1-2 seconds. The red light on the motor will begin flashing.
- 6. Press that same button on the remote again. The flashing light on the motor will stop. Your remote is now successfully programmed and ready to operate the gate.



Motor Type 1 (DOOR CODE)



Motor Type 2 (CODE SET)



Product contains coin/button cell battery. Keep product and batteries away from children. The battery is hazardous and can cause severe or fatal injuries in 2 hours or less if awallowed or placed inside any part of the body. Seek mmediate medical attention if it as suspected that a coin/button cell battery has been exallowed or placed inside any part of the body.

