

# 1715IF16

Allen-Bradley 1715 Redundant IO 16AI Current



IN CABINET DISTRIBUTED IO



Allen-Bradley



|                |                                                            |
|----------------|------------------------------------------------------------|
| Component type | Fieldbus, decentr. periphery - analogue/digital I/O module |
| Range          | Redundant IO                                               |
| Model          | N/A                                                        |
| Product status | Existing                                                   |

## ELECTRICAL

|                                    |         |
|------------------------------------|---------|
| Type of voltage (input voltage)    | DC      |
| Resolution of the analogue inputs  | 12 Bit  |
| Analogue input signal configurable | No      |
| Supply voltage DC                  | 24-24 V |
| Analogue inputs configurable       | No      |
| Analogue input, current            | Yes     |

## CONSTRUCTION

|                               |    |
|-------------------------------|----|
| Suitable for safety functions | No |
| Number of analogue inputs     | 16 |

## DIMENSIONS

|        |        |
|--------|--------|
| Width  | 42 mm  |
| Height | 166 mm |
| Depth  | 118 mm |

## ENVIRONMENT

|                                        |             |
|----------------------------------------|-------------|
| Operating temperature                  | -25...60 °C |
| Storage temperature                    | -40...85 °C |
| Max. ambient humidity (non-condensing) | 95 %        |