



REF MP-15703-JA

7 Fr. 3 Lumen 20 cm catheter length .018 inch dia. spring-wire guide

Three-Lumen CVC

Contents:

- 1: Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm, Stylet

1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 23-5/8" (60 cm) (Angled Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer and hub

1: Catheter: 20 Ga. x 1-3/4" (4.45 cm) Radiopaque over 22 Ga. TW Introducer Needle

1: Injection Needle: 25 Ga. x 1-1/2" (3.81 cm)

1: Injection Needle: 22 Ga. x 1-1/2" (3.81 cm)

1: Introducer Needle: Echogenic 22 Ga. (0.72 mm) x 2-3/4" (7 cm) XTW

1: Introducer Needle: Echogenic 22 Ga. (0.72 mm) x 1-3/8" (3.5 cm) XTW

1: Syringe: 10 mL Luer-Slip

1: Syringe: 5 mL Luer-Slip

1: Syringe: 2 mL Luer-Slip

1: Tissue Dilator: 8 Fr. x 9.7 cm

3: Dust Cap: Non-Vented

1: SecondSite™ Adjustable Hub: Fastener

1: SecondSite™ Adjustable Hub: Catheter Clamp

1: Medicine Cup: 60 mL

1: SharpsAway® Disposal Cup
- 1: Drape: 35" x 50" (89 cm x 127 cm) with 4" (10 cm) fenestration, with adhesive

1: Needle Holder

1: Scalpel: #11

2: Stopcock: 4-way

1: Prep Sponge Swab

6: Gauze Pad: 4" x 4" (10 cm x 10 cm)

1: Dressing: OpSite® 4-3/4" x 4" (12 cm x 10 cm)

1: Suture: 3-0 Silk with Curved Needle

1: Tray: Prep

1: Y-hub

2: Guidewire Introducer

¹A registered trademark of T.J. Smith & Nephew, Limited.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Not made with natural rubber latex.

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

Fluid path components are non-pyrogenic.



Lumen

Priming Volume* (mL)

Gravity Flow Rate† (mL/hr)

Distal (16 Ga.)	0.47	2656
Medial (18 Ga.)	0.4	1245
Proximal (18 Ga.)	0.42	1328

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL057813 R00 (2021-10)

