



User Manual

before use and follow all instructions mentioned herein.

Caring For Your MOMAN Product

- Please keep the product in a dry, clean, dust-free environment.
- Keep corrosive chemicals, liquids and heat source away from the product to prevent mechanics damage.
- Use only a soft and dry cloth for cleaning the product.
- Malfunction may be caused by dropping, impact of external force.
- Do not attempt to disassemble the product. Doing so voids warranty.
- Please have the product checked or repaired by authorized technicians if any malfunctions happened
- Failure to follow all the instructions may result in mechanics damage.
- Warranty does not apply to human errors.

Package

Intercom x2

Hook and Loop Fasteners

(x1 for 1-Rider Kit)

USB Cable x2

(x1 for 1-Rider Kit)

(x1 for 1-Rider Kit)







Replaceable Hard Mid

and Soft Mic Speakers x2

Screw Driver x2


(x1 for 1-Rider Kit)



Headphone Velcro x8

(x4 for 1-Rider Kit)









Important Notice:

Product Introduction

@MOMAN



⑤ Knob









Before installing the headsets, follow the Quick Manual instructions to connect your phone and audition the sound and volume. If there is a large difference in sound effect and volume after installing it on the helmet, please adjust the position of the speaker in the helmet.

Headset Plug

(12) Replaceable soft mic

Operation

Power On/Off

ON: Press the ON/OFF key for 2 seconds.

OFF: Long Press the ON/OFF key for 4 seconds.


Reset: Under Power on mode, long Press the ON/OFF Key for 8 seconds.




↓ Voice prompt

OFF: The RED light flashes once.

2. Phone Control



3. Music Control





counterclockwise then HOLD IT.

Volume decrease: Turn the knob clockwise then HOLD IT

* There is voice alarm for too high and too low volume.

4. FM Radio

1) ON: Under Standby mode, double-click the Function Key twice.

2 OFF: Double-click the function key twice.


3 Select channels: Quickly ratate and release the knob to select and adjust.

If the signal is weak indoor, you could try to turn on the FM radio near window or in the open area.

When FM radio is turned on and there is a phone calling, the machine will cut off FM radio automatically and connect to the mobile phone. It gets back to the FM radio when the call ends.

Language Switch

Power on, press the ON/OFF key and ratate the knob at the same time. (English → Japanese → Italian)





7. Pairing and Disconnetion

7.1 With Mobile Phone:


- 1 After switching on press the On/Off Key and Function Key simultaneously for 4 seconds, BLUE light flashes twice, then RED and BLUE light flash
- ② Pairing:Turn on the bluetooth function .search "MOMAN H2 PRO" to connect.





7.2 Two Intercoms Pairing

- ① After switching on, press the On/Off Key and Function Key simultaneously for 4 seconds, BLUE light flashes twice, then RED and BLUE light flash alternatively.
- 2 Press the ON/OFF key of 1 intercom, the blue indicatior light flashes quickly.



Two intercoms pair successfully with BLUE light flash slowly.

Notes:

Voice prompt

"Intercom Search"

- 1. Automatic connection: Once the intercoms pair successfully, there is no need to pair repeatedly
- 2. After switching on, short press the On/Off Key under Standby mode to repair.

7.3 Reconnect&Disconnect

- Reconnect: Short press the ON/OFF Key → Voice prompt:"Di".
- ② Disconnec:Short press the ON/OFF Key → Voice prompt:"Di".



Within five minutes of disconnection, connects automatically:

More than five minutes, short press the On/Off Key to search.







Thank you for choosing MOMAN product. Please read this manual carefully



8. Music Sharing Bluetooth of Intercom A Short press the ON/OFF Kev of paired (A&B) intercom A

2 OFF: Press the Function Key of Intercom A for 2 seconds

Play music and Press the

for 2 seconds

Function Key of Intercom A

- Music can only shared by the main. The auxiliaries can't share music.
- (Judgment: Intercom A and Intercom B pair. The one who actively pairs is the

Music sharing

successfully

- 2 Only after restoring factory settings and re-pairing can you switch between the main and the auxiliaries.
- 3 After successful music sharing, if the music of Intercom A is paused and the music of Intercom B is playing, then Intercom A will play the music of Intercom B

9. Multi-Mode Switch

1) Between Intercom and Musci/FM Radio:



Voice prompt: "Di"

Exit Intercom mode

and enter Music/ FM Radio mode

Between Intercom and Mobile Phone:



A call

Automatically enter Intercom mode within

10. Funcition Priority

Level 1: Mobile Phone


Level 2: Intercom

Level 3: Music/FM Radio

1. Method 1: Install with Back Clip

Installation


- ① Use the screwdriver to loosen the screws of the back clip so that it can open to a proper extent.
- ② Open the helmet liner, insert the clip into the right position on the left side of the helmet and tighten the screw.
- ③ Slide the intercom into the back clip slot to make sure it locks firmly.
- 4 Open the helmet liner (ear position), clean the EPS surface of the helmet. and stick a piece of horn Velcro on the left and right sides of the helmet.
- (5) Stick the speaker on the fixed Velcro surface and the speaker with short line should be installed close to the machine. Fix the microphone and arrange the helmet lining and cable.
- (6) Insert the headset into the jack of the intercom and tie up the headset cable.













Method 2: Install with Velcro Clip

Separate the hook and loop fasteners. First stick the hook onto the Velcro clip; choose the right installation position on the helmet and stick the loop to the position. Install the intercom onto the Velcro clip.

The installation of speakers can refer to the description above.











2. How to Remove the Intercom from Helmet

First unplug the headset, then press the fixed buckle in the middle of the back clip with one finger (push towards the side of the helmet), so that the back clip hook is detached from the intercom, and push the intercom upwards to let it slide out of the back clip smoothly to complete the disassembly.





3. How to Fix the Headset Plug (If necessary)

Unscrew the screws on the back of intercom with screwdriver, open the buckle flap, plug in the headset plug and tighten the screws. If you need to plug out the headset, please open the buckle flap by unscrewing the screws.



Installation

- 1. Before using the Bluetooth intercom, please use the attached charging cable to charge the intercom. The small type-C interface on the charging line is connected to the USB charging interface of the Bluetooth intercom, and the large USB connector on the charging cable is connected to the following charging interface for power supply:
- A. USB interface of computer;
- B. A mobile power supply with DC 5V output:
- C. A USB power adapter with DC 5V output.
- 2. When charging, the red LED is always on, and when fully charged, the red light goes out slowly. It takes up to 2.5 hours to fully charge the unit.

up to 1000m

A2DP, AVRCP

Type-C

300H

900mAh

40mm

2.4GHz

-20~50°C

20H

Transmission Range Connection Distance with Mobile 20m Bluetooth Version Bluetooth Protocol Charging Port Working Time

Charging Time

Charging Voltage Speaker Diameter

Frequency Range

Temperature Range

Specifications

Notes

- 1. If you do not use intercom for up to one month or more, please charge the intercom once every two months in order to protect the lithium battery;
- 2. The storage temperature of this product is -20 °C to 50 °C, and do not store in the environment with too high or low temperature, otherwise, the service life of the product will be affected:
- 3. Do not expose this product to fire to avoid explosion;
- 4. Only two screws on the back of intercom can be opened. Do not open other screws to the intercom to avoid short circuit of main board or battery damage.

Moman (UK) Limited

- 9. Unit 25 Basepoint Business Centre, Aviation Park, West Christchurch, United Kingdom BH23 6NX
- € @ © @MomanGlobal
- # https://moman.co/voutube