



Duo Wide AC44



www.ecotap.nl
info@ecotap.nl

Specifications

General characteristics

Reference number	65345106 / 65004410 / 65020015 / 65020020
Dimension H x W x D (mm)	1400 x 360 x 240
Casing material	Steel 2,2 mm
Standard colour	Body: Ral 6018 / Cover: Ral 9016 for 65345106 / 65004410 Body: Ral 6018 / Cover: Ral 9016 for 65020015 / 65020020
Steel treatment	Anti-corrosion (KTL) and powder coating
Weight (kg)	76 kg
Number of charging points	2
Socket	Type 2
Cable	Type 2
Contactdoors	Type 2
Kabel	Type 2

Electrical characteristics

Power output per socket	0 to 44kW
Operating voltage (Ue) / Rates current (In A) for the charger	Single-phase cabling, phase + N 230V~ from 0 to 125A (determined at 20°C) Three-phase cabling, 3 phases + N 400V~ from 0 to 125A (determined at 20°C)
Operating voltage (Ue) / Rates current (In A) per charge point	Single-phase cabling, phase + N 230V~ from 0 to 63A (determined at 20°C) Three-phase cabling, 3 phases + N 400V~ from 0 to 63A (determined at 20°C)
Impulse voltage (Uimp)	4kV

Insulation voltage (Ui)	230V single-phase 500V three-phase
Frequency (fn)	50Hz/60Hz
Rated voltage	1 phase + N: 230V - 3 phases + N: 400V
Voltage tolerance (V) regardless of vehicle requirements	195V - 265V
Integrated protection system on charging station	Main switch 125A
Integrated protection system per charge point	MCB 80A curve C RCD 63A 30mA Type B
Conditional short-circuit	6000A IEC/EN 60898-1 10kA IEC/EN 60947-2
Allowable thermal stress in Short Circuit	16 000 A²s
Connection to the mains	Phase/Neutral, rigid cable, 2.5 to 50 mm², screw terminals HO7 V R/U Earth, rigid cable, 2.5 to 50mm², screw terminals HO7 V R/U
Type of load	Mode 3 charging terminal equipped with a locking system for Mode 3
Vehicle connection Mode 3 attache cable connector	Type 2 3P+N (single-phase compatible) with pilots compliant with IEC 62191-1 and IEC 62196-2. Use of extension and adapter prohibited. 10m straight 3x63A
Phase rotation on channel 2 (Rightside).	In the case of monophasic cabling (Ph+N) on the power source. Channel 2 will not be able to start charging sessions, until the phase rotation between contactor and socket are manually undone.
AC meters	MID certified, Class B according to EN 50470-1, -3
Back office protocol	OCPP 1.6 Json
Positioning	GPS
Connectivity Ethernet	RJ45 connector for 65345106 / 65020020

Environment

Operating temperature	-25°C / +50°C
Storage temperature	-25°C / + 80°C
Relative humidity	0 to 90% without condensation
Corrosivity class	C4 according to the IEC 9223 and IEC 12944 3C3/4C3 according to the IEC 60721-3
Protection rating	IP 54 (IEC 60529), IK 10 (EN 62262) Plugged in or not
Noise level	< 40 dBA at 1m
Product	IEC 61851-1, IEC TS 61439-7 (AEVCS)
Installation	Interior or exterior, limited access zone, intended for use by ordinary persons (DBO), assembly in cabinet (wall mounted), Pollution Degree 3, TNS, TT, compatible earthing system. In the event of an IT earthing system, this can be changed locally by adding an isolation transformer.
Electrical safety	Class 1 IEC 61140

Electromagnetic compatibility

European standards	Low Voltage Directive 2014 / 35EU / EMC Directive: 2014 / 30 / EU
Radio technology type	GSM 2G/3G/4G, GPRS, RFID
Suitable charging cards	Mifare, Ntag and iCODE SLI cards



Ecotap B.V.
Kruisbroeksestraat 23
5281 RV Boxtel
+31(0) 411 210 210
info@ecotap.nl
