



24V

RGB+W

SMD

INDOOR

# RibbonFlex PRO<sup>®</sup> LED Tape Light

RGB+W LED strip lights combine RGB (red, green, blue) color with white to create a truly customizable lighting solution. The 30 + 30 and 60 + 60 LED/m Multicolor + White tape lights include both RGB and White LED diodes, delivering multiple color options and a pure soft white (3000K) light.

## Features

- Featuring ultra strong 3M peel & stick mounting adhesive for a long lasting and easy installation
- Requires 24 volt LED power supply (sold separately)
- Custom installations are easy with flexible LED tape light that can be cut to size and reconnected as needed
- Low voltage power makes 24V LED lights exceptionally energy efficient
- LED lights are fully dimmable from 0 to 100% brightness with compatible dimmer switches and controllers (sold separately)

## Includes

- LED tape light
- Low voltage power wire leads, 48 in. wire lead on one end, 8 in. wire lead on other end
- 1 Wire Lead Connector for bridging gaps
- 1 Splice Connector for extending tape strip lengths
- 2 Peel-and-stick Wire Support Clips
- Detailed planning and installation guide

	30+30 LEDs/m			60+60 LEDs/m		
Item #s	623210: 2.5m	623230: 5m	623250: 10m	624210: 2.5m	624230: 5m	624250: 10m
Type	Indoor			Indoor		
Dimension (L*W*H)	X*10mm*1mm			X*10mm*1mm		
IP Rating	IP20 (dry)			IP20 (dry)		
Lumen Flux	110 lumens/ft.			282 lumens/ft.		
Standard Length	2.5m, 5m, 10m			2.5m, 5m, 10m		
LED Type	SMD 2835 White & SMD 5050 RGB			SMD 2835 White & SMD 5050 RGB		
PCB Type	2 oz. copper FPC			2 oz. copper FPC		
Operating Ambient	Ta: -4 – 113° F			Ta: -4 – 113° F		
Warranty	3 years			3 years		
Lifespan	65,000 hours			65,000 hours		
Certification	UL E527208			UL E527208		
Maximum Straight Run Length	5 meters			5 meters		
Power +/- 10%	11W/m			18W/m		
Input Voltage	24V DC			24V DC		
CCT	RGB+3000K			RGB+3000K		
CRI	Ra>80			Ra>80		
Beam Angle	120			120		
Mounting Method	9495MP 3M adhesive			9495MP 3M adhesive		
Cut Distance	4 in.			2 in.		
Input connection type	Flying wire leads			Flying wire leads		

\*Luminous flux for CCT can fluctuate up to 10% the cooler the temperature is

\*All reels come equipped with a splice connector & 6in tape to tape connector

\* Includes 1.2m 20AWG on one end, and 0.2m of 20AWG wire on the other