

DESCRIPTION

Featuring a low-profile design, these UFO LED high bays are a cost-effective solid state solution for high bay applications, providing a one-for-one replacement of existing metal halide fixtures.

FEATURES

- Up to 151 LPW ultra-high efficiency delivers superior performance over older HID high bays
- Efficiently replaces up to a 1000W metal halide fixture
- 6' power cord standard for more installation flexibility
- 0-10V dimming
- Optional u-bracket available for surface mounting; see Mounting Accessories section for more information

LISTINGS

- UL rated for wet locations
- IP65
- DesignLights Consortium® 5.1 Premium - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance

PERFORMANCE

- CRI: >80
- CCT: 4000K and 5000K
- LED L70 Life Hours: 149,000 hours
- Philips Lumileds SMD LEDs

THERMAL

- -40°F to 122°F (-40° to 50°C) operating temperature

ELECTRICAL

- THD: ≤20%
- Power Factor: ≥0.9
- Input Voltage: 120-277V
- Surge Protection: 6kV

INSTALLATION

- Suspended mounting with included 10mm ring or surface mounting (u-bracket sold separately); see installation instructions for more information

CONSTRUCTION

- Slim, lightweight die-cast aluminum construction allows for quick and easy installation
- PC lens protects LEDs while evenly distributing light
- Black or white finish

project name	type
catalog number	
comments	voltage
approved by	date



WARRANTY

- 5 year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Warehouses
- Manufacturing Plants
- Distribution Centers
- Grocery Stores
- Gymnasiums
- Indoor Recreational Facilities
- Cold Storage
- Big Box Retail
- Service Repair Centers


PERFORMANCE SUMMARY

Item #	Model	Watts	Lumens	LPW	CCT	CRI	Dimming	Voltage	Replaces	Finish	DLC #	DLC Level
PLT-12561	UFO	100	15,190	151	5000K	>80	0-10V	120-277V	MH250	White	PLTSN1B61412	5.1 Premium
PLT-12565	UFO	150	22,544	150	5000K	>80	0-10V	120-277V	MH400	White	PLTSN1B81412	5.1 Premium
PLT-12569	UFO	240	36,458	151	4000K	>80	0-10V	120-277V	MH1000	White	PLTSN1B71411	5.1 Premium
PLT-12558	UFO	100	15,190	151	4000K	>80	0-10V	120-277V	MH250	Black	PLTSN1B61421	5.1 Premium
PLT-12563	UFO	150	22,544	150	5000K	>80	0-10V	120-277V	MH400	Black	PLTSN1B81422	5.1 Premium
PLT-12566	UFO	240	36,458	151	4000K	>80	0-10V	120-277V	MH1000	Black	PLTSN1B71421	5.1 Premium

MOUNTING ACCESSORIES

SKU	Description
PLTS-12377	Adjustable U-Bracket - White
PLTS-12378	Adjustable U-Bracket - Black

DIMENSIONS



100W & 150W DIMENSIONS


Height with ring mount: 5.67"

Height w/ bracket: 7.20"

Diameter: 11.22"

Weight: 3.97 lbs

Ring Mount Thread Size: 10MM



240W DIMENSIONS

Height with ring mount: 6.50"


Height w/ bracket: 7.72"

Diameter: 12.80"


Weight: 5.73 lbs

Ring Mount Thread Size: 10MM

100W PHOTOMETRICS



150W PHOTOMETRICS



240W PHOTOMETRICS

