

CS661	0.8 inch PT camera, 3MP, Dual light sources, Red and blue alarm	
		Chip
		Ingenic T31
		Sensor
		GC2083
		WiFi
		8188FTV
	Pixel	3MP
	Brand	VSTARCAM

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/3.02 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens/Viewing angle	4mm@F2.3/101°(Diagonal)
	Night vision	IR-CUT with auto-switching, 6 pcs LED lights, 6 pcs IR LED lights, Irradiation distance: 15~25 m, Red and blue lights alarm
	Compression standard	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Data Rate	Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Substream:360p(640×360)@15fps

Shenzhen VStarcam Technology Co., Ltd

	Bit rate/Maximum frame rate	128~4096kbps/30fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in -38dB microphone
	Output	Built-in 8Ω1W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/64kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2Petc.
	Wireless network	IEEE802.11b/g/n; Support AP mode
	Wireless frequency	2.4~2.4835GHz
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK Data encryption
Pan & Tilt	Pan & Tilt	Pan 350° /Tilt 95°
	Preset position	Supports 16 (Mobile phone App supports 5) preset positions
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage; NVR; NAS
Alarm	Alarm detection	Motion detection; Humanoid detection; Humanoid tracking; Smoke sound detection; Absence detection; Alarm voice prompt , flash & irradiation; LED light timing ON & OFF
Physical Indicators	Rated voltage	DC12V±5%
	Operating condition	Temperature: -10~50℃, Humidity: <90%
	Weight	(Note: in kind prevail)