

TESLA TA36FFLL-12410A



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Top plate/cover improved, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Ionizer filter, I FEEL

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			CoolingHeating
Rated capacity		W	33003450
Power input		W	1028955
Current input		A	4.474.15
EER-COP		W	3.213.61
Energy Class			AA
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1700
Max. current		A	8.5
Compressor	Model		ASM125V1VFT
	Type		ROTARY
	Brand		GMCC
Indoor	Fan motor	Model	YYK18-4B
		Power input	W18
		Capacity	uF1.5
		Indoor Fan Speed RPM	r/min1330
	Indoor fan	Dia. / Length	mmφ97.8*558
	Indoor Air Circulation		m³/h560
	Indoor Noise Level dB		dB(A)36/33/30/27
	Net Dimension (L×W×H)		mm800x300x197
	Packing Dimension (L×W×H)		mm870x370x282
	Net Weight/Gross Weight		Kg43687
Outdoor	Fan motor	Model	YDK25-6
		Power input	W25
		Capacity	uF1.5
		Outdoor Fan Speed RPM	r/min820
	Outdoor fan	Length	mmφ390*140
	Outdoor Noise Level dB		dB(A)52
	Net Dimension (L×W×H)		mm660x500x240
	Packing Dimension (L×W×H)		mm780x570x345
	Net Weight/Gross Weight		Kg29/34
	Refrigerant type/weight		gR410/660
Max. Discharge/Max. Suction pressure		Mpa4.15/1.15	
Refrigerant piping	Liquid side / Gas side	mm	φ6.35(0,5) /φ9.52(0,6)
	Max. refrigerant pipe length / Max. difference in level	m	18/6
Operation Temperature Range	Cooling	(min - max) °C	14~43 °C
	Heating		-7~30 °C