

# RACKS BRAX.

## COMPATIBILITY POCKET GUIDE

**FOR**



**MAXTRAX**

**FAST ON!  
FAST OFF!**

# AWNING AND ACCESSORY MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW  
TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

**MAXTRAX® LITE** ..... 3

**MAXTRAX® MINI** ..... 5

**MAXTRAX® MKII** ..... 7

**MAXTRAX® XTREME** ..... 9

**MAXTRAX® JAXBASE** ..... 11



# MAXTRAX<sup>®</sup> LITE

## ITEMS REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard <b>AND</b>
ALSO REQUIRED	8210 – HD Accessory Plate Gen 2; Use where brackets <b>cannot be located at 634mm</b> centres, the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run <b>TRANSVERSE</b> (across the width of the vehicle); <b>OR</b>  8173 – HD Accessory Bars Where brackets <b>can be located at 634mm</b> centres (typically for platform racks with slats that run <b>LONGITUDINAL</b> (along the length of the vehicle).

## BRACKETS REQUIRED FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
BRACKETS NEEDED	
✓ <b>FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)</b>	<p>8320 – HD 15 Degree Angle Brackets*</p> <p>For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>8304 – HD Adjustable Brackets Short (DOUBLE)**</p> <p>For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical); <b>OR</b></p>
✓ <b>FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)</b>	<p>8320 – HD 15 Degree Angle Brackets*</p> <p>For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>8306 – HD Adjustable Brackets Long (DOUBLE)**</p> <p>For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p>

\*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

\* These brackets are both height and angle adjustable.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts <sup>+</sup>  ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts <sup>+</sup>  ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

<sup>+</sup>NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

MAXTRAX<sup>®</sup> MINI

ITEMS REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard AND
ALSO REQUIRED	8173 – HD Accessory Bars Where brackets <b>can be located at 634mm</b> centres (typically for platform racks with slats that run <b>LONGITUDINAL</b> (along the length of the vehicle).

BRACKETS REQUIRED FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
BRACKETS NEEDED	
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8320 – HD 15 Degree Angle Brackets*  For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  8304 – HD Adjustable Brackets Short (DOUBLE)**  For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical); OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8320 – HD 15 Degree Angle Brackets*  For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  8306 – HD Adjustable Brackets Long (DOUBLE)**  For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).

\*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

+ These brackets are both height and angle adjustable.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts <sup>+</sup>  ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts <sup>+</sup>  ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

<sup>+</sup>NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

MAXTRAX<sup>®</sup> MKII

## ITEMS REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard <b>AND</b>
ALSO REQUIRED	8210 – HD Accessory Plate Gen 2; Use where brackets <b>cannot be located at 634mm</b> centres, the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run <b>TRANSVERSE</b> (across the width of the vehicle); <b>OR</b> 8173 – HD Accessory Bars Where brackets <b>can be located at 634mm</b> centres (typically for platform racks with slats that run <b>LONGITUDINAL</b> (along the length of the vehicle).

## BRACKETS REQUIRED FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
BRACKETS NEEDED	
✓ <b>FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)</b>	<p>8320 – HD 15 Degree Angle Brackets*</p> <p>For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>8304 – HD Adjustable Brackets Short (DOUBLE)**</p> <p>For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical); <b>OR</b></p>
✓ <b>FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)</b>	<p>8320 – HD 15 Degree Angle Brackets*</p> <p>For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>8306 – HD Adjustable Brackets Long (DOUBLE)**</p> <p>For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p>

\*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

\* These brackets are both height and angle adjustable.

**WALL MOUNTS** OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts <sup>+</sup>  ✓ <b>LOCKED GARAGES</b> ✓ <b>WORKSHOP WALLS</b>
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts <sup>+</sup>  ✓ <b>OPEN CARPORTS</b> ✓ <b>PUBLIC/SHARED GARAGE AREA</b>

<sup>+</sup>NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.



# MAXTRAX<sup>®</sup> XTREME

## ITEMS REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard <b>AND</b>
ALSO REQUIRED	8210 – HD Accessory Plate Gen 2; Use where brackets <b>cannot be located at 634mm</b> centres, the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run <b>TRANSVERSE</b> (across the width of the vehicle); <b>OR</b>  8173 – HD Accessory Bars Where brackets <b>can be located at 634mm</b> centres (typically for platform racks with slats that run <b>LONGITUDINAL</b> (along the length of the vehicle).

## BRACKETS REQUIRED FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
BRACKETS NEEDED	
✓ <b>FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)</b>	<p>8320 – HD 15 Degree Angle Brackets*</p> <p>For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>8304 – HD Adjustable Brackets Short (DOUBLE)**</p> <p>For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical); <b>OR</b></p>
✓ <b>FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)</b>	<p>8320 – HD 15 Degree Angle Brackets*</p> <p>For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>8306 – HD Adjustable Brackets Long (DOUBLE)**</p> <p>For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p>

\*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

\* These brackets are both height and angle adjustable.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts <sup>+</sup>  ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts <sup>+</sup>  ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

<sup>+</sup>NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

MAXTRAX® JAXBASE

☹️ **SADLY NOT COMPATIBLE** ☹️