

# Quiet Vortex Cooler Type 4X, 5000BTU, Lt Gray, Polycarbonate

## CATALOG NUMBER

**VA501604X**



Vortex A/C Enclosure Coolers keep enclosures cool, clean and protected even in the harshest environments. Offering flexible installation, these enclosure coolers are ideal in space-restrictive areas where compressed air is readily available. With almost no moving parts, these enclosure coolers are highly reliable and virtually maintenance free.

## INDUSTRY STANDARDS

Maintains UL/cUL Type 4, 4X when properly installed on a UL/cUL Type 4, 4X enclosure. (Type 4, 4X Models)

UL508 Listed; Type 4, 4X; File No. E249700 (Type 4, 4X Models)

Maintains UL/cUL Type 12 when properly installed on a UL/cUL Type 12 enclosure. (Type 12 Models)

UL508 Listed; Type 12; File No. E249700 (Type 12 Models)

NEMA Type 4,4X Models:

IP66

NEMA Type 12 Models:

IP54

## FEATURES

Quieter operation with noise level of 60-75 dB

Top, side, and front mount allows for versatile installation in confined areas

Operates in environments up to 175 F (80 C)

Cooling capacities up to 5000 BTU/Hr. (1465 W)

Mechanical thermostat reduces energy consumption

NEMA Type 4,4X models are polycarbonate and stainless steel exterior; aluminum and brass internal components

NEMA Type 12 models are polycarbonate and aluminum exterior; aluminum and brass internal components

Supplied with five-micron, automatic drain compressed air filter, cold ducting kit, and cold air muffler

## PRODUCT ATTRIBUTES

Article Number: 26947

Height: 6.44in

Width: 9.44in

Depth: 5.56in

Nominal Capacity Btu/h: 5000Btu/h

Nominal Capacity Watts: 1465W

Material: Polycarbonate

Finish: Smooth Matte

Color: Light Gray

Color Code: RAL 7035

Weight: 11.4lb

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY**

**ERICO**

**HOFFMAN**

**ILSCO**

**SCHROFF**

**TRACHTE**