

# RF EXPOSURE EXEMPT REPORT

**APPLICANT**: Anker Innovations Limited

**PRODUCT NAME**: eufy Panic Button E10

MODEL NAME : T90P0

**BRAND NAME**: eufy

FCC ID : 2AOKB-T90P0

**STANDARD(S)** : 47 CFR Part 2(2.1093)

**RECEIPT DATE** : 2025-03-05

**TEST DATE** : 2025-03-12 to 2025-04-02

**ISSUE DATE** : 2025-06-25

Edited by:

Leng Xiagying (IX

Approved by:

Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn

E-mail: service@morlab.cn





## **DIRECTORY**

1.	Technical Information	. 3
1.1	Applicant and Manufacturer Information	. 3
1.2	Equipment Under Test (EUT) Description	. 3
1.3	Applied Reference Documents	. 3
2.	Device Category and RF Exposure Limit	٠ 4
3.	Maximum Average Power Summary	. 5
4.	RF Exposure Evaluation	٠ 6
An	nex A Testing Laboratory Information ······	. 7

Change History			
Version Date		Reason for Change	
1.0 2025-06-25		First edition	



## 1. Technical Information

Note: Provide by applicant.

## 1.1 Applicant and Manufacturer Information

Applicant:	Anker Innovations Limited	
Applicant Address:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road,	
Applicant Address.	Hong Kong	
Manufacturer:	Anker Innovations Limited	
Manufacturer Address	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road,	
Manufacturer Address:	Hong Kong	

## 1.2 Equipment Under Test (EUT) Description

Product Name:	eufy Panic Button E10
Sample No.:	5#, 6#
Hardware Version:	V2.0
Software Version:	V1.1.1.0
Operating Frequency:	920.0MHz, 920.2MHz, 920.4MHz, 920.6MHz, 920.8MHz
Channel Number:	5
Antenna Type:	Metal Monopole Antenna
Antenna Gain:	-2.01dBi

**Note 1:** The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 1.3 Applied Reference Documents

Leading reference documents for testing:

Identity	Document Title	Remark	
47 CED Dort 2/2 1002)	Radio Frequency Radiation Exposure	,	
47 CFR Part 2(2.1093)	Assessment: Portable devices	/	
KDB 447498 D01v06	General RF Exposure Guidance	1	
<b>Note 1:</b> Any additions, deviation, or exclusions from the method shall be noted in the "Remark".			



# 2. Device Category and RF Exposure Limit

Based on 47 CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

#### **Portable Devices:**

47 CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

## **General Population/Uncontrolled Exposure:**

47 CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.





# 3. Maximum Average Power Summary

Fraguenov/MHz)	Max. Emission	Max. Emission	Time-averaging
Frequency(MHz)	E(dBµV/m)	(V/m)	EIRP (mW)
920.4	92.90	0.0442	0.5850

**Note 1:** According to KDB 447498, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

Note 2: The maximum average emission refers to report (Report No.: SZ25030028W01).





# 4. RF Exposure Evaluation

#### Standalone Transmission SAR Evaluation:

- 1. According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances≤ 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[ $\sqrt{f(GHz)}$ ] ≤ 3.0.
  - · f(GHz) is the RF channel transmit frequency in GHz
  - · Power and distance are rounded to the nearest mW and mm before calculation
  - · The result is rounded to one decimal place for comparison
- 2. Standalone SAR measurement is not required for the EIRP is less than the exempt condition according to KDB 447498 D01v06 4.3.2).

#### Simultaneous SAR Evaluation:

This device only incorporates one transmitter, therefore simultaneous SAR evaluation is not required.





# **Annex A Testing Laboratory Information**

## 1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.	
	FL.3, Building A, FeiYang Science Park, No.8 LongChang	
Laboratory Address:	Road, Block 67, BaoAn District, ShenZhen, GuangDong	
	Province, P. R. China	
Telephone:	+86 755 36698555	
Facsimile:	+86 755 36698525	

## 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.	
	FL.3, Building A, FeiYang Science Park, No.8 LongChang	
Address:	Road, Block 67, BaoAn District, ShenZhen, GuangDong	
	Province, P. R. China	

#### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

END OF REPORT	



Tel: 86-755-36698555

Http://www.morlab.cn