

A3 Black & White Photocopier

MX-M266NV

Flexible, adaptable, affordable – our A3 black & white MFP is ideal for any office



- Print, Copy, Scan, Fax, File
- Paper capacity: Std 1100 Max 2100 sheets
- Standard Reversing Single Pass Feeder and standard duplex module
- 7.0 inch touchscreen colour LCD control panel with thumbnail previews
- Pages per minute: 26 B/W
- Standard network printing and colour network scanning
- Space-saving inner finisher option

Specifications

GENERAL

Engine speed: A4 B/W (ppm)	26
Engine speed: A3 B/W (ppm)	15
Paper size: Min.-Max.	A6 - A3
Paper weight (g/m ²)	55 - 200
Paper capacity: Std. (sheets)	1100
Paper capacity: Max. (sheets)	2100
Warm Up Time (sec.)	20
Memory general: Min./Max. (GB)	2
Memory printer: Min./Max. (GB)	2
Harddisk	OPT
Harddisk capacity (GB)	250
Duplex	STD
Power requirements - rated local AC voltage (Hz)	220 - 240V, 50 / 60Hz
Power consumption (kW)	1,45
Dimensions (mm)	620 x 617 x 830
Weight (kg)	51

DOCUMENT FEEDER

Original capacity (sheets)	100
----------------------------	-----

DOCUMENT FILING

Document filing (Standard / Option)	OPT
Document filing capacity: main & custom folders (pages)	20.000
Document filing capacity: quick file folder (pages)	10.000
Stored jobs	Copy, print, scan, fax
Storage folders	Quick folder, main folder, custom folder
Confidential storage	•

FAX

Fax (Standard / Option)	OPT
Compression method	MH / MR / MMR / JBIG
Communication protocol	Super G3 / G3
Transmission time (sec.)	2
Modem speed (bps)	33.600 - 2.400
Transmission resolution (dpi)	STD: 203,2 x 97,8; Ultra fine: 406,4 x 391
Document size: Min.	A5
Document size: Max.	A3
Memory (MB)	512 - 1024
Grey scale (levels)	256
Dial registration: rapid/speed dial	1000
Broadcast transmission (Max. destinations)	500

WIRELESS LAN

Wireless LAN (Standard / Option)	OPT
Compliant regulation	IEEE802.11 b / g / n
Access mode	Infrastructure mode, Software AP mode
Security	WEP, WPA-PSK, WPA-EAP, WPA2-PSK, WPA2-EAP

COPIER

Original paper size: Max.	A3
First copy out time: B/W (sec.)	4,3
E-sort Std.	•
Continuous copy (Max. copies)	999
Scan resolution: B/W (dpi)	600 x 600; 600 x 400; 600 x 300
Scan resolution: Colour (dpi)	600 x 600; 600 x 400; 600 x 300
Print resolution (dpi)	600 x 600
Gradation: B/W (equivalent levels)	2
Gradation: Colour (equivalent levels)	256
Zoom range (%)	25 - 400
Preset copy ratios	10

SCANNER

Network Scanner (Standard / Option)	STD
Scan method Push scan and Pull scan	•
Push scan resolution (dpi)	100, 200, 300, 400, 600
Pull scan resolution (dpi)	75, 100, 150, 200, 300, 400, 600; 50 - 9600
File formats	XPS, PDF, Encrypted PDF, PDF / A-1b, JPEG, TIFF
Scan destination: Desktop	•
Scan destination: FTP, Email	•
Scan destination: Network folder	•
Scan destination: USB memory	•

PRINTER

Resolution (dpi)	1200 x 600; 600 x 600
Enhanced resolution (dpi)	1200 x 600; 600 x 600
Network Printer (Standard / Option)	STD
Interface: Std./Opt.	USB 2.0, 10-BaseT, 100Base-TX, 1000Base-T
Supported OS: Std.	Windows 8.1, 10. Windows Server 2012, 2012R2, 2016, 2019.
Supported OS: Opt.	Max OS X 10.4, 10.5, 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15
Network protocols	TCP / IP (IPv4, IPv6), IPX / SPX (NetWare), EtherTalk (AppleTalk)
Printing protocols	LPR, Raw TCP (port 9100), POP3, HTTP, FTP, EtherTalk, IPP
PDL: Std./Opt.	STD: PCL6 emulation / OPT: PostScript3 emulation
Available fonts	80 (PCL), 136 (PS3)

FINISHING

Output capacity: Max. (sheets)	500
Staple capacity: Max. (sheets)	50
Off-set shifting	STD

TONER YIELD

Black (pages at 6% coverage)	27500
------------------------------	-------

