

# **RACKS** **BRAX.**<sup>®</sup>

## **COMPATIBILITY POCKET GUIDE**

**FOR**

**TRED**  
TOTAL RECOVERY & EXTRACTION DEVICE

**FAST ON!  
FAST OFF!**

AWNING AND ACCESSORY  
MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW  
TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

TRED® GT, GT COMPACT ..... 3

TRED® HD, HD COMPACT ..... 5

TRED® MINIS 1:10 Scale..... 7

TRED® PRO..... 8

TRED® RV ..... 10

TRED® X ARB PRO ..... 11



# TRED® GT, GT COMPACT

## ITEMS REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard <b>AND</b>
ALSO REQUIRED	8210 – HD Accessory Plate Gen 2; Where brackets <b>cannot be located at recovery board pin centres</b> , the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run <b>TRANSVERSE</b> (across the width of the vehicle); <b>OR</b>  8173 – HD Accessory Bars Where brackets can be located at 890mm centres (typically for platform racks with slats that run <b>LONGITUDINAL</b> (along the length of the vehicle).

## BRACKETS REQUIRED FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
BRACKETS NEEDED	
✓ <b>FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)</b>	<p>8320 – HD 15 Degree Angle Brackets*</p> <p>For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>8304 – HD Adjustable Brackets Short (DOUBLE)**</p> <p>For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical); <b>OR</b></p>
✓ <b>FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)</b>	<p>8320 – HD 15 Degree Angle Brackets*</p> <p>For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>8306 – HD Adjustable Brackets Long (DOUBLE)**</p> <p>For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).</p> <p>*ROOF RACKS WITH PERIMETER LIPS REQUIRE <b>PACKERS</b> TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO <a href="#">ROOF RACK GUIDE</a> FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.</p> <p>* These brackets are both height and angle adjustable.</p>

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts <sup>+</sup>  ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts <sup>+</sup>  ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

<sup>+</sup>NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

TRED<sup>®</sup> HD, HD COMPACT

ITEMS REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard AND
ALSO REQUIRED	8210 – HD Accessory Plate Gen 2; Where brackets <b>cannot be located at recovery board pin centres</b> , the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run <b>TRANSVERSE</b> (across the width of the vehicle); OR  8173 – HD Accessory Bars Where brackets can be located at 890mm centres (typically for platform racks with slats that run <b>LONGITUDINAL</b> (along the length of the vehicle).

BRACKETS REQUIRED FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
BRACKETS NEEDED	
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8320 – HD 15 Degree Angle Brackets*  For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  8304 – HD Adjustable Brackets Short (DOUBLE)**  For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical); OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8320 – HD 15 Degree Angle Brackets*  For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  8306 – HD Adjustable Brackets Long (DOUBLE)**  For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  *ROOF RACKS WITH PERIMETER LIPS REQUIRE <b>PACKERS</b> TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO <a href="#">ROOF RACK GUIDE</a> FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS. + These brackets are both height and angle adjustable.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts <sup>+</sup>  ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts <sup>+</sup>  ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

<sup>+</sup>NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

TRED<sup>®</sup> MINIS *1:10 Scale*

☹️ **SADLY NOT COMPATIBLE** ☹️

TRED® PRO

ITEMS REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard AND
ALSO REQUIRED	8210 – HD Accessory Plate Gen 2; Where brackets <b>cannot be located 890mm centres</b> , the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run <b>TRANSVERSE</b> (across the width of the vehicle); OR  8173 – HD Accessory Bars Where brackets can be located at 890mm centres (typically for platform racks with slats that run <b>LONGITUDINAL</b> (along the length of the vehicle).

BRACKETS REQUIRED FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
BRACKETS NEEDED	
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8320 – HD 15 Degree Angle Brackets*  For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  8304 – HD Adjustable Brackets Short (DOUBLE)**  For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical); OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8320 – HD 15 Degree Angle Brackets*  For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  8306 – HD Adjustable Brackets Long (DOUBLE)**  For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  *ROOF RACKS WITH PERIMETER LIPS REQUIRE <b>PACKERS</b> TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO <a href="#">ROOF RACK GUIDE</a> FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS. + These brackets are both height and angle adjustable.



WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts <sup>+</sup>  ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts <sup>+</sup>  ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

<sup>+</sup>NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.



TRED® RV

☹️ **SADLY NOT COMPATIBLE** ☹️

TRED® X ARB PRO

ITEMS REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard AND
ALSO REQUIRED	8210 – HD Accessory Plate Gen 2; Where brackets <b>cannot be located at 890mm centres</b> , the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run <b>TRANSVERSE</b> (across the width of the vehicle); OR  8173 – HD Accessory Bars Where brackets can be located at 890mm centres (typically for platform racks with slats that run <b>LONGITUDINAL</b> (along the length of the vehicle).

BRACKETS REQUIRED FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
BRACKETS NEEDED	
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8320 – HD 15 Degree Angle Brackets*  For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  8304 – HD Adjustable Brackets Short (DOUBLE)**  For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical); OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8320 – HD 15 Degree Angle Brackets*  For storing recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  8306 – HD Adjustable Brackets Long (DOUBLE)**  For height adjustable storage recovery boards to nominally match the rake of the side of the vehicle (i.e. 15 degrees off-vertical).  *ROOF RACKS WITH PERIMETER LIPS REQUIRE <b>PACKERS</b> TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO <a href="#">ROOF RACK GUIDE</a> FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS. + These brackets are both height and angle adjustable.



WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts <sup>+</sup>  ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts <sup>+</sup>  ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

<sup>+</sup>NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.