



REF AK-17702-CDC

7^{Fr.} 2^{Lumen}

¹A registered trademark of CareFusion or one of its subsidiaries.

2: Gauze Pad: 2" x 2" (5 cm x 5 cm) 5: Gauze Pad: 4" x 4" (10 cm x 10 cm) 1: Suture: 3-0 Braided Silk with Straight Needle

20 cm catheter length 1032 inch dia. spring-wire guide

Two-Lumen CVC

Contents:

- Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm Spring-Wire Guide: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) Injection Needle: 25 Ga. x 1" (2.54 cm) Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW Blunt Fill Needle: 18 Ga. x 1-1/2" (3.81 cm) Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle with 5 mL Luer-Slip Syringe Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe Syringe: 3 ml. Luer-Lock

- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe Syringe: 3 mL Luer-Lock
 Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
 5 mL 1% Lidocaine HCI Solution and Alcohol Prep
 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®¹ One-Step Solution with Hi-Lite Orange™ Tint
 Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
 SharpsAway® II Locking Disposal Cup
 SharpsAway® Disposal Cup
 Drape: 41" x 55" with 4" fenestration
 Safety Scalpel: #11

КX	oni	у


Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

California Prop. 65

WARNING: Cancer and Reproductive Harm.
 www.P65Warnings.ca.gov
 Not made with natural rubber latex.

Store between 20 - 25°C (68 - 77°F) Sterilized using ethylene oxide unless otherwise indicated in the contents list.

Fluid path components are non-pyrogenic.



^{*} Priming volumes are approximate and are done without accessories.









Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL053650 R00 (2021-11)







20 cm catheter length 1032 inch dia. spring-wire quide









[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.