

Application

This wall luminaire with a wide spread light distribution can be used to illuminate ground surfaces along walls. Able to be installed in either direction for uplight or downlight applications.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.8 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage15.8 W
- System wattage21.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens2187 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)

☐ Silver (SLV)

☐ Natural Bronze (NTB)

☐ CUS:
- ☐ Bronze (BRZ)

☐ White (WHT)

☐ RAL:

Type:
BEGA Product:
Project:
Modified:

Available options

- ☐ ACD

☐ AMB

☐ CUS

☐ FSC

☐ MGU

☐ NTB

☐ RAL
- Acrylic diffuser

Amber LED


Custom finish

Fusing

Marine grade undercoat

Natural bronze (premium finish)

RAL finish



Wall washer · Lateral throw				
	LED	A	B	C
B22383	15.8 W	9 1/2	4 1/8	7 7/8

