

ProStat Training

May 2020









Economy Models



Non-Programmable

PRS3110 - 1 Heat / 1 Cool

PRS3210 - 2 Heat / 1 Cool



Compatibility

- Single Stage Conventional or Heat Pump Systems
- Multistage Conventional or Heat Pump Systems (PRS3210)
- 2-Wire Hydronic Zone Systems
- Millivolt Systems

- Large Display with Bright Blue Backlight
- Hardware Adjustable Temperature Limits
- Hardwire or Battery Powered
- Permanent Memory Retains Settings
- Front Access Reset Button
- Compressor Short Cycle Protection
- Fahrenheit or Celsius Display Mode
- Adjustable Temperature Differential
- ESD Guard Electronic Circuitry









Economy Models



Universal Programmable

PRS4110 – 1 Heat / 1 Cool **PRS4210** – 2 Heat / 1 Cool



Compatibility

- Single Stage Conventional or Heat Pump Systems
- Multistage Conventional or Heat Pump Systems (PRS4210)
- 2-Wire Hydronic Zone Systems
- Millivolt Systems

- 7-Day, 5-2 Day or Non-Programmable
- Hardware Adjustable Temperature Limits
- Temporary Program Override
- Programmable Extended Hold Mode
- Hardwire or Battery Powered
- Permanent Memory Retains Settings
- Filter Check Monitor
- Front Access Reset Button
- Adaptive Recovery Mode (ARMTM)
- Compressor Short Cycle Protection
- Fahrenheit or Celsius Display Mode
- Adjustable Temperature Differential
- ESD GuardTM Electronic Circuitry









Premier Models



Universal Programmable

PRS6110 – 2 Heat / 1 Cool **PRS6320** – 3 Heat / 2 Cool



Compatibility

- Single Stage Conventional or Heat Pump Systems
- Multistage Heat Pump Systems
- Multistage Conventional Systems (PRS6320)
- 2 or 3 Wire Hydronic Zone Systems
- Millivolt Systems

- 7 Day, 5-2 Day or Non-Programmable
- Residential or Commercial Modes
- Auto or Manual Changeover
- Hardwire or Battery Powered
- Permanent Memory Retains Settings
- Programmable and Circulating Fan Modes
- Separate User and Installer Reset Buttons
- User Selectable Service Monitors
- Indoor or Outdoor Remote Sensing
- Multi-Level Keypad Lockout
- Heat Pump Balance Points
- Programmable Extended Hold Mode
- Adaptive Recovery Mode (ARMTM)









Premier Models



Universal Programmable Touchscreen

PRS6420 – 4 Heat / 2 Cool



Compatibility

- Single Stage Conventional or Heat Pump Systems
- Multistage Conventional or Heat Pump Systems
- 2-Wire Hydronic Zone Systems
- Millivolt Systems

Features

- 7 Day, 5-2 Day or Non-Programmable
- Residential or Commercial Modes
- Auto or Manual Changeover
- Hardwire or Battery Powered
- Permanent Memory Retains Settings
- Programmable and Circulating Fan Modes
- Separate User and Installer Reset Buttons
- User Selectable Service Monitors
- Indoor or Outdoor Remote Sensing
- Multi-Level Keypad Lockout
- Heat Pump Balance Points
- Auto or Manual Humidification
- Dehumidification with Optional Overcooling
- Adaptive Recovery Mode (ARMTM)





CLEAN COMFORT INDOOR AIR ESSENTIALS



Premier Models



Universal Programmable Wifi



PRS7325WF – 3 Heat / 2 Cool

Compatibility

- Single Stage Conventional or heat Pump Systems
- Multistage Heat Pump Systems
- Multistage Conventional Systems
- 2-Wire Hydronic Zone Systems
- Millivolt Systems (If not using Wi-Fi)

- 7 Day, 5-2 Day or Non-Programmable
- Auto or Manual Changeover
- Hardwire or Battery Powered
- Permanent Memory Retains Settings
- Circulating Fan Mode
- Service Filter Monitor
- Multi-Level Keypad Lockout
- Auxiliary Heat Fossil Fuel Option
- Programmable Extended Hold Mode
- Adaptive Recovery Mode (ARMTM)
- 4-Wire Capable No Common (C) Wire Required
- SmartLimitTM Temperature Limits
- Separate User and Installer Lock Modes









Remote Sensors



Compatibility

- Works with models PRS6110, PRS6320, PRS6420
- Connect a maximum of one sensor to thermostat

Indoor Sensor Features

- Contemporary Style for any decor
- Sense remotely or average with thermostat
- Temperature sense range of 40° to 99° F
- Configured with thermostat Installer Settings
- Simple 2-wire installation

Remote Sensors

PRS6390 – Indoor Remote Sensor PRS6490 – Outdoor Remote Sensor

Outdoor Sensor Features

- Mounts outdoors up to 200 feet away
- View outdoor temperature from thermostat
- Enables the use of heat pump balance points
- Outdoor sense range of -40° to 120° F
- Automatically recognized by thermostat
- Simple 2-wire installation









Apps



- Free Contractor App
- Contractors send invitations to their existing BlueLink Customers requesting temporary or permanent access
- Once access is granted, contractors can view, modify and manage approved thermostats remotely
- Compatible with both Amazon Alexa or Google



- Compatible with popular smartphones, tablets or PC's
- Patented multi-color group programming
- Patented QuickEdit™ programming capability
- Patented QuickCopy[™] feature
- SmartData[™] energy reports
- Exclusive text or standard email alerts
- Dealer information screen
- Application help screens
- NEW! Geofencing capabilities
- NEW! Amazon[®] & Google[®] capabilities









Contractor Branding

Doors



- FREE Contractor branding program No minimums
- Absolutely NO COST to contractors
- Advertise 24/7 in customers' homes or businesses
- 3 lines of text (30 characters per line) neatly pad-printed on removable thermostat doors
- Contractor simply selects models, fills out branding form and faxes in branding request
- Unless a quantity is specified contractor will receive 50 branded thermostat doors
- Allow 2 3 weeks from receipt of branding form









Contractor Branding



Cards

- FREE Contractor branding program No minimums
- Absolutely NO COST to contractors
- Advertise 24/7 in customers' homes or businesses
- Color logos printed on Quick Reference cards that can be used in PROSTAT thermostats
- Requires high resolution contractor logo in TIF,
 JPG or EPS file formats see online order form
- Unless a quantity is specified contractor will receive 50 Quick Reference cards with full color logos printed on them
- Allow 2 3 weeks from receipt of high resolution logo












Sale Support Material

















Technical Support

- Assist Distributors and Contractors with choosing correct products
- Worksite assistance for Contractors diagnosing system control issues
- Aide Consumers in programming and usage of their ProStat products
- Provide assistance in obtaining product documentation or owner manuals
- •Staffed by industry professionals with over 50 years of combined experience

Toll Free Technical Support (855) 445-2466







