



Terrestrial and satellite signal combiner 2 inputs: MATV-SAT

2-input combiner that combines a terrestrial signal with a satellite signal into a single output.

Can be used as GSM filter, thanks to the high TV-SAT rejection

Ref.	4340
EAN13	8424450043400

Packaging info

Blister	1 pcs.
Box	6 pcs.

Physical data

Net weight	188.00 g
Gross weight	188.00 g
Width	98.00 mm
Height	66.00 mm
Depth	27.00 mm
Main product weight	188.00 g

Highlights

- High-screening Zamak chassis
- Current pass from the output to the SAT input, for LNB supply
- Indoor or outdoor installation (with ref. 4163 case)
- "F" connectors

Technical specifications : Ref. 4340

Connectors			"F" type
Number of inputs			2
Number of outputs			1
Frequency range	MHz	47 ... 790	950 ... 2400
IN (TERR) -> OUT attenuation	dB	1.5	> 30
IN (TERR) -> OUT A attenuation	dB	1.5	> 30
IN (TERR) -> OUT B attenuation	dB	1.5	> 30
IN (SAT) -> OUT attenuation	dB	> 30	1.8
IN (SAT A) -> OUT A attenuation	dB	> 30	1.8
IN (SAT B) -> OUT B attenuation	dB	> 30	1.8
Return losses (typ.)	dB	> 10	> 10
Operating temperature	°F		23 ... 113
Protection index (IP)			23