

# Quick Start Guide

Measures drive-thru lane events for comparison to your service time goals at up to eight detection points in the drive-thru lane. The Dashboard displayed below provides an example overview for a single-lane drive-thru with seven lane detectors (PRE-MENU, MENU 1, CASHIER, SERVICE, and three Pull-Forward detectors) as well as two independent detectors (Mobile Pickup).

White number by car indicates total time car has been in lane. Car color changes based on Total Time goals.

**Event time**  
The amount of time car has spent at a detection point.

The target goal time for a detection point.

Average time car has spent at a detection point.

Click to open sidebar menu (see Dashboard image on page 2).

Zones awaiting orders off the drive-thru lane or at a PF window help keep the lane fluid and free from congestion. (While PF zones are now supported using Vision AI,\*\* PF windows are not.)

Parking zones reserved for mobile orders.\* These are independent detectors (not part of the drive-thru lane) and are now also supported using Vision AI.\*\*




*\* Mobile Ordering is a service that allows you to place orders using a smart device.*

**\*\* Vision AI requires additional equipment.**

Using a camera, Vision AI\*\* gives you the ability to monitor the area before the Pre-Menu for Drive Offs along with other enhanced metrics.

Is the Total Time tracked from a starting detection point (usually the first detector in the lane, "MENU 1" in this example) to the departure from the last detection point in the lane ("SERVICE" in this example). Cars will display "0:00" until they arrive/depart the first detection point.

Color-coded cars and values provide an easy method for identifying how a metric is performing against a preset goal. Goals are used to motivate performance.

- A green car or value like this  0:29 indicates you are exceeding your goal.
- A yellow car or value like this  2:01 indicates you are meeting your goal.
- A red car or value like this  0:32 indicates you are not meeting your goal.

Total number of cars served for the current hour.

- **Prev:** The result of the previous hour.

- **Best:** Best result ever achieved for an hour.


- Pace:** Predicts the final result for the hour based on current count.


- Point: First detection point, others include CASHIER & SERVICE.

- **Goal:** The target result desired for the hour.



## How to make changes to your ZOOM Nitro Timer

1. To edit your Dashboard, use a mouse connected to the USB port on the CU or use a back-office PC if configured on the same network. Click on  to open screen below.
2. Click on the **SECURITY**
3. Log in to the system.  
Note: The manager assigns permissions and passwords. If you do not have a password, contact HME Technical Support at the number below to obtain a temporary Manager password.
4. Once logged in, click on **DASHBOARD SETTINGS** in the sidebar menu to edit.



### Language

The default language is English. Click on Canadian flag for French.

### Dashboard Layout

Click to open pane and select your desired layout.

### Lane and Data Section Graphics

Click on a graphical element on the Dashboard to open it for editing.

In this example, use the fields or toggles under the **Section Settings** to edit what is displayed.

Drive Offs and Pre-Menu Stack are enabled and therefore displayed here on the Dashboard (also see page 1 image).

## Drive-Thru Leaderboard®

The Drive-Thru Leaderboard shows the top three and bottom three stores ranked against others in your network. Your store will be outlined and displayed with its closest competitors.

### Top 3 Stores

Top 3 performing stores in your network.


### Your Store

Your store will always be outlined and displayed with its closest competitors.



Also, visit the **HME Training Portal** at:

<https://www.hme.com/training>



## Your System

### Timer Signal Processor (TSP)

Receives event data from car detections in a drive-thru lane or reserved parking location.



TSP Mounted location: \_\_\_\_\_

**Control Unit (CU)** Receives and processes data from the TSP to provide information for the ZOOM Dashboard display.



CU Mounted location: \_\_\_\_\_

## Need more help?



A copy of this guide and more information can be found by scanning this QR code above. When you land on the web page, navigate to Drive-Thru Timer Systems and click/tap on ZOOM Nitro to expand. Or go to: <https://www.hme.com/qsr/drive-thru-user-manuals>

Need help? Call **1-800-848-4468, options 1,2,3** or email us at [support@hme.com](mailto:support@hme.com)

### HME, INC.

2848 Whiptail Loop, Carlsbad, CA 92010 USA  
Fax: 858-552-0172 | [www.hme.com](http://www.hme.com)