

FINEPIX S2950

Take your photography skills one step further

Fujifilm's extensive range of 'bridge cameras' are renowned for their ease-of-use and outstanding telephoto capabilities. This year's newest addition is the S2950. It houses an impressive 14 megapixel high resolution sensor, a large 3.0" LCD screen, can capture Full 1080p HD images and 720p HD videos (30fps), and features a 28mm wide-angle, 18x Fujinon optical zoom lens. This digital camera is perfect for photography enthusiasts looking for an all-round camera with generous zoom capabilities.



Key Features

- 14 megapixel CCD sensor
- 18x Fujinon optical zoom (28-504mm)
- 3.0" LCD screen (230,000 dot resolution)
- EVF (200,000 dot resolution)
- NEW Easy Web Upload to Facebook & YouTube
- Full HD 1080p stills (Full HD) and 720p HD video recording (30 fps)
- Mini HDMI port for easy image display on any HDTV
- Up to ISO 6400 (at reduced resolution)
- Face Detection, Blink detection and Smile and shoot mode
- SR Auto (Scene Recognition Auto)
- Full Manual Controls
- Tracking Auto Focus
- Motion Panorama mode
- Image Search function with Photobook Assist
- Auto Image Rotate
- Powered by 4 x AA batteries



Dedicated Accessories

S2950 PREMIUM CASE



AC-5VX POWER ADAPTOR



- | | |
|------------------------|-------------|
| • S2950 Premium Case | P10N079870A |
| • CP-04 Coupler | P10NA00390A |
| • AC-5VX Power Adaptor | P10N076270A |

Included Accessories

- | | |
|----------------------------------|------------------------------|
| • 4 x AA type alkaline batteries | • Lens cap and Lens cap cord |
| • Shoulder strap | • CD-ROM |
| • USB-A/V cable | • Owner's manual |

Universal Accessories

STORAGE MEDIA CARDS



WORLDTRIP DUAL USB CHARGER & TRAVEL ADAPTER



SD™/SDHC™ MEMORY CARDS

- | | |
|---|-------------|
| • SD™/SDHC™ Memory Cards (2GB-32GB) | |
| • S Series Case and 4GB SDHC Card Pack | P10NA02810A |
| • WorldTrip Dual USB Charger & Travel Adapter | P10NA00870A |
| • PowerSafe Earthed Travel Adapter | P10NA00890A |
| • World Adapter | P10N075440A |
| • World Adapter with USB Charger | P10N077520A |
| • SD™/SDHC USB Card Reader | P10NUSBSD0A |
| • Gorillapod (small) | P10NA00290A |
| • Premium Mini Multi-purpose Case | P10N076160A |
| • 3.0" Screen Protector Pack | P10NA00440A |
| • Lens Cleaning Kit | P10N076350A |
| • HD Player HDP-L1* | P10NA01760A |
| • Mini-HDMI/HDMI Cable | P10NA02930A |

* HDMI cable required (sold separately)

Technical Specification

Number of effective pixels	14.0 million pixels		
Image sensor	1/ 2.3" CCD with primary colour filter		
Storage media	Internal memory (none) SD™/SDHC™ memory card		
File format Still image	JPEG (Exif Ver 2.3) / (Design rule for Camera File system compliant / DPOF-compatible)		
Movie	AVI (Motion JPEG)		
Sound	WAVE format, Monaural sound		
Number of recorded pixels	L: (4:3) 4288 x 3216 (3:2) 4288 x 2864 (16:9) 4288 x 2416 M: (4:3) 3072 x 2304 (3:2) 3072 x 2048 (16:9) 3072 x 1728 S: (4:3) 2048 x 1536 (3:2) 2048 x 1360 (16:9) 1920 x 1080		
Lens	Fujinon 18 x optical zoom lens		
Focal length	f=5.0 – 90.0 mm, equivalent to 28 – 504mm on a 35 mm camera		
Full-aperture	F3.1 (Wide) – F5.6 (Telephoto)		
Constitution	11 groups 14 lenses		
Digital zoom	Approx. 6.7 x (up to approx. 120.6 x, with 18x optical zoom)		
Aperture	F3.1/ F6.4 (Wide) F5.6/F11 (Telephoto) with ND filter		
Focus distance (from lens surface)	Normal:	Wide:	Approx. 40cm (1.3ft) to infinity
		Telephoto:	Approx. 2.5 m (8.2 ft) to infinity
	Macro:	Wide:	Approx. 5 cm – 3m /2.0in. – 9.8ft.
		Telephoto:	Approx. 1.8m – 3m /5.9ft. – 9.8ft
	Super Macro:	Wide:	Approx. 2cm – 1.0m /0.8in. – 3.3ft.
Sensitivity	Auto, Equivalent to ISO 64/100/200/400/800/1600/3200*/6400* (Standard Output Sensitivity) *ISO3200/6400 is effective in S mode.		
Exposure control	TTL 256 – zones metering ; Spot, Multi, Average		
Exposure mode	Programmed AE, Shutter Priority AE, Aperture Priority AE, Manual exposure		
Shooting modes	SP :Zoom Bracketing, Natural Light & with Flash, Natural Light, Portrait, Baby, Smile, Landscape, Sport, Night, Night (Tripod), Fireworks, Sunset, Snow, Beach, Party, Flower, Text,		
Mode Dial	SR AUTO, AUTO, P, S, A, M, Custom, Movie, Panorama, SP		
Image Stabiliser	CCD shift type		
Face Detection	Yes		
Exposure compensation	– 2.0EV, +2.0EV, 1/3EV step		
Shutter speed	Auto mode:	1/4 sec. to 1/2000 sec.	
	All other modes:	8 sec. to 1/2000 sec. with mechanical shutter	
Continuous shooting (TOP)	TOP – 3 max. 1.2 fps; TOP – 10 max. 3.3 fps; size (M, S) TOP – 20 max. 8 fps; size (S)"		
(LAST)	LAST3: max. 1.2 fps; last 3 frames recorded		
(others)	LONG PERIOD: max. 1.2 fps; maximum number of frames varies with image size and available memory		
Auto bracketing	AE Bracketing ±1/3EV, ±2/3EV, ±1EV		
Focus	Single AF/Continuous AF (SR AUTO, Movie)		
(Type)	TTL contrast AF, AF assist illuminator available		
(AF frame selection)	Centre, Multi, Area, Tracking		
White balance	Automatic scene recognition Preset: Fine, Shade, Fluorescent light (Daylight), Fluorescent light (Warm White), Fluorescent light (Cool White), Incandescent light, Custom		
Self-timer	Approx. 10 sec. – 2 sec. Delay		
Flash	Auto flash (i-flash)		
	Effective range:	(ISO AUTO)	
	Normal	Wide:	approx. 40 cm–8.0 m/1.3 ft.–26.2 ft.
		Telephoto:	approx. 2.5 m–4.4 m/8.2 ft.–14.4 ft.
	Macro	Wide:	approx. 30 cm–3.0 m/1 ft.–9.8 ft.
		Telephoto:	approx.1.8 m–3.0 m/5.9 ft.–9.8 ft.

FUJIFILM



Flash modes	Red-eye removal OFF: Auto, Forced Flash, Suppressed Flash, Slow Synchro. Red-eye removal ON: Red-eye Reduction Auto, Red-eye Reduction & Forced Flash, Suppressed Flash, Red-eye Reduction & Slow Synchro.
Hot shoe	–
Electronic Viewfinder	0.2", approx. 200, 000 dots, colour LCD viewfinder, approx. 97% coverage
LCD monitor	3.0", approx. 230, 000 dots, TFT colour LCD monitor, approx. 97% coverage
Movie recording	1280 x 720 pixels / 640 x 480 pixels / 320 x 240 pixels (30 fps) with monaural sound. Zoom function can be used.
Photography functions	SR AUTO, Instant zoom, Face Detection, Auto red-eye removal, Framing guideline, blink detection, Frame No. memory, histogram display, motion panorama,
Playback functions	Face Detection, Auto red-eye removal, Multi-frame playback (with micro thumbnail), Protect, Crop, Resize, Slide show, Image rotate, voice memo, histogram display, exposure warning, Photobook assist, image search, Favourites, Mark for upload, Panorama, Erase selected frames
Other functions	PictBridge, Exif Print, 35 Languages, Time difference, Silent mode
Terminal	NTSC/PAL selectable with monaural sound
(Digital interface)	USB 2.0 High-Speed
(HDMI output)	HDMI Mini connector
Power supply	4x AA type alkaline batteries (included) / 4x AA type Ni-MH rechargeable batteries (sold separately) 4x AA type lithium batteries (sold separately)
Dimensions	110.2 (W) × 73.4 (H) × 81.4 (D) mm
Weight	Approx. 341g / 12.0oz. (excluding accessories, batteries and memory card) Approx. 437g / 15.4oz. (including accessories, batteries and memory card)
Operating Temperature	0°C – 40°C
Operating Humidity	10% – 80% (no condensation)
Battery Life	Alkaline batteries: Approx. 300 frames Ni-MH rechargeable batteries: Approx. 500 frames Lithium batteries: Approx. 700 frames

Number of images

Mode	Recording media	4GB		8GB		16GB	
		FINE	NORMAL	FINE	NORMAL	FINE	NORMAL
Still images	L 4:3	570	1120	1170	2310	2360	4640
	L 3:2	630	1250	1310	2580	2640	5190
	L 16:9	750	1470	1550	3040	3120	6100
	M 4:3	1070	2080	2220	4300	4460	8640
	M 3:2	1200	2330	2490	4840	5000	9640
	M 16:9	1420	2720	2930	5610	5880	11270
	S 4:3	2330	4340	4800	8960	9640	17980
	S 3:2	2600	4820	5370	9940	10780	19960
Movies ¹	S 16:9	3400	6160	7020	12700	14100	25490
	HD1280 ²	17 min.		35 min.		73 min.	
	640	53 min.		107 min.		22 min.	
	320	112 min.		226 min.		908 min.	

¹ Individual movie files cannot exceed min. 9 minutes. ² Use a class 4 card or better when shooting HD movie.Product Code
P10NC03860ABarcode
4547410150544Colour
Black
PictBridge

Specifications are subject to change without notice. All trademarks are the property of their respective holders.