

# Instek GPD-3303S

Multiple Output Programmable Linear D.C. Power Supply



Limited Availability  
New From Surplus Stock

Open Web Page

<https://www.artisanTG.com/63263-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source  
for quality pre-owned  
equipment.

**Artisan Technology Group**

(217) 352-9330 | [sales@artisanTG.com](mailto:sales@artisanTG.com) | [artisanTG.com](http://artisanTG.com)

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

MULTIPLE OUTPUT PROGRAMMABLE LINEAR D.C. POWER SUPPLY



GPD-3303S/3303D




The GPD-3303S / GPD-3303D series inherits the superior technology and high quality, which GW Instek has established through its long history of power supply design and manufacturing. The GPD-3303S / GPD-3303D series provides 195W output power, three isolated output channels, high resolution output (GPD-3303S ), digital control panel, 4 sets of setup memory, USB remote control, smart cooling fan control, high reliability, and compact size. The GPD-3303S / GPD-3303D establish a new benchmark for economic programmable linear D.C. power supply market segment. The most remarkable feature of this series product with minimum 1mV / 1mA resolution of GPD-3303S, which right fits into the applications needing accurate control of power source.GPD-3303D, another member of the family, is considered a digitally-upgraded version of GPS-3303. Besides the same power output features and the common specifications of GPS-3303, that GPD-3303S / GPD-3303D has a bigger display for Voltage and Current readings, a digital panel, and a USB port, which lifts up the product to a programmable device at a little additional cost.

FEATURES


- \* Three Independent Output : (30V/3A x 2),(2.5V/3.3V/5V)/3A x 1 (Fixed)
- \* 4 LED Display Sets : 3 Digits After Decimal Point
- \* Minimum Resolution : 1mV/1mA( GPD-3303S ),100mV/10mA(GPD-3303D)
- \* Digital Panel Control (Rotary Encoder Switch, Rubber Key With Indicator)
- \* User-Friendly Operation, Coarse/Fine Volume Control
- \* 4 Sets Save/Recall
- \* Key-Lock
- \* Warning Buzzer
- \* Output ON/OFF
- \* Tracking Series and Parallel Mode
- \* Smart Cooling Fan Achieving Low Noise
- \* Compact Design

SPECIFICATIONS		
	GPD-3303S	GPD-3303D
OUTPUT		
Voltage	0~30.0V x 2 , 2.5V/3.3V/5.0V x 1	
Current	0~3.0A x 2 , 3.0A (Fixed)	
CONSTANT VOLTAGE OPERATION		
Regulation	Line regulation $\leq 0.01\%+3mV$ Load regulation $\leq 0.01\%+3mV$ (rating current $\leq 3A$ ) $\leq 0.02\%+5mV$ (rating current $>3A$ )	
Ripple & Noise	$\leq 1mVrms$ (5Hz~1MHz)	
Recovery Time	$\leq 100 \mu s$ (50%Load change, Minimum load 0.5A)	
Temp.Coefficient	$\leq 300ppm / ^\circ C$	
Output Range	0 to rating voltage continuously adjustable	
CONSTANT CURRENT OPERATION		
Regulation	Line regulation $\leq 0.2\%+3mA$ Load regulation $\leq 0.2\%+3mA$	
Ripple Current	$\leq 3mA_{rms}$	
Output Range	0 to rating current continuously adjustable	
TRACKING OPERATION		
Regulation of PAR.	Line regulation $\leq 0.01\%+3mV$ Load regulation $\leq 0.01\%+3mV$ (rating current $\leq 3A$ ) $\leq 0.02\%+5mV$ (rating current $>3A$ )	
Regulation of SER.	Line regulation $\leq 0.01\%+5mV$ Load regulation $\leq 300mV$ Tracking error $\leq 0.5\%\pm 10mV$ (10 ~ 30V no load) with load added $\leq 300mV$ $\leq 0.5\%\pm 30mV$ (0 ~ 9.99V no load) with load added $\leq 300mV$ )	
Tracking error	$\leq 0.5\% + 10mV$	$\leq 0.5\% + 50mV$
METER		
Display	Voltage : 4 3/4 digits 0.4" LED Display Current : 3 3/4 digits 0.4" LED Display	Voltage : 2 3/4 digits 0.4" LED Display Current : 2 3/4 digits 0.4" LED Display
Resolution	Voltage : 1mV Current : 1mA	Voltage : 100mV Current : 10mA
Program accuracy(25 $\pm$ 5 $^\circ$ C )	Voltage : $\pm(0.03\%$ of RDG +10 digits) Current : $\pm(0.3\%$ of RDG +10 digits)	Voltage : $\pm(0.5\%$ of RDG +2 digits) Current : $\pm(0.5\%$ of RDG +2 digits)
Readback accuracy(25 $\pm$ 5 $^\circ$ C )	Voltage : $\pm(0.03\%$ of RDG +10 digits) Current : $\pm(0.3\%$ of RDG +10 digits)	Voltage : $\pm(0.5\%$ of RDG +2 digits) Current : $\pm(0.5\%$ of RDG +2 digits)
CH3 SPECIFICATIONS		
Output Voltage	(2.5V/3.3V/5V) $\pm 8\%$	
Output Current	3A	
Regulation(25 $\pm$ 5 $^\circ$ C )	Line regulation $\leq 5mV$ Load regulation $\leq 15mV$	
Repple & Noise	$\leq 2mVrms$	
KEY LOCK		
Yes		
MEMERY SAVE/RECALL		
4 sets		
POWER SOURCE		
AC100V/120V/220V/230V $\pm 10\%$ , 50/60Hz		
DIMENSION & WEIGHT		
210(W) x 130 (H) x 265(D) mm ; Approx. 7kg		



GPD-3303S

Rear Panel



ORDERING INFORMATION

- GPD-3303S** Multiple Output High Resolution Programmable Linear D.C. Power Supply  
**GPD-3303D** Multiple Output Programmable Linear D.C. Power Supply

- ACCESSORIES :  
User Manual x1  
Power cord x1  
Test lead GTL-104 x 2, GTL-105 x 1  
European Test Lead GTL-203 x 1 , GTL-204 x 2

Optional Accessories

- GTL-246** USB Cable

MULTIPLE OUTPUT PROGRAMMABLE LINEAR D.C. POWER SUPPLY



GPD-3303S/3303D




FEATURES

- \* Three Independent Output : (30V/3A x 2),(2.5V/3.3V/5V)/3A x 1 (Fixed)
- \* 4 LED Display Sets : 3 Digits After Decimal Point
- \* Minimum Resolution : 1mV/1mA( GPD-3303S ),100mV/10mA(GPD-3303D)
- \* Digital Panel Control (Rotary Encoder Switch, Rubber Key With Indicator)
- \* User-Friendly Operation, Coarse/Fine Volume Control
- \* 4 Sets Save/Recall
- \* Key-Lock
- \* Warning Buzzer
- \* Output ON/OFF
- \* Tracking Series and Parallel Mode
- \* Smart Cooling Fan Achieving Low Noise
- \* Compact Design

The GPD-3303S / GPD-3303D series inherits the superior technology and high quality, which GW Instek has established through its long history of power supply design and manufacturing. The GPD-3303S / GPD-3303D series provides 195W output power, three isolated output channels, high resolution output (GPD-3303S ), digital control panel, 4 sets of setup memory, USB remote control, smart cooling fan control, high reliability, and compact size. The GPD-3303S / GPD-3303D establish a new benchmark for economic programmable linear D.C. power supply market segment. The most remarkable feature of this series product with minimum 1mV / 1mA resolution of GPD-3303S, which right fits into the applications needing accurate control of power source.GPD-3303D, another member of the family, is considered a digitally-upgraded version of GPS-3303. Besides the same power output features and the common specifications of GPS-3303, that GPD-3303S / GPD-3303D has a bigger display for Voltage and Current readings, a digital panel, and a USB port, which lifts up the product to a programmable device at a little additional cost.

SPECIFICATIONS		
	GPD-3303S	GPD-3303D
OUTPUT		
Voltage	0-30.0V x 2 , 2.5V/3.3V/5.0V x 1	
Current	0-3.0A x 2 , 3.0A (Fixed)	
CONSTANT VOLTAGE OPERATION		
Regulation	Line regulation ≤ 0.01%+3mV Load regulation ≤ 0.01%+3mV(rating current≤ 3A) ≤ 0.02%+5mV(rating current >3A)	
Ripple & Noise	≤ 1mVrms (5Hz~1MHz)	
Recovery Time	≤100 μ S (50%Load change, Minimum load 0.5A)	
Temp.Coefficient	≤300ppm / °C	
Output Range	0 to rating voltage continuously adjustable	
CONSTANT CURRENT OPERATION		
Regulation	Line regulation≤ 0.2%+3mA Load regulation≤ 0.2%+3mA	
Ripple Current	≤3mA rms	
Output Range	0 to rating current continuously adjustable	
TRACKING OPERATION		
Regulation of PAR.	Line regulation ≤ 0.01%+3mV Load regulation≤ 0.01%+3mV (rating current≤ 3A) ≤ 0.02%+5mV (rating current >3A)	
Regulation of SER.	Line regulation ≤ 0.01%+5mV Load regulation≤ 300mV Tracking error ≤ 0.5%±10mV (10 ~ 30V no load) with load added≤ 300mV) ≤ 0.5%±30mV (0 ~ 9.99V no load) with load added ≤ 300mV)	
Tracking error	≤ 0.5% + 10mV	≤ 0.5% + 50mV
METER		
Display	Voltage : 4 3/4 digits 0.4" LED Display Current : 3 3/4 digits 0.4" LED Display	Voltage : 2 3/4 digits 0.4" LED Display Current : 2 3/4 digits 0.4" LED Display
Resolution	Voltage : 1mV Current : 1mA	Voltage : 100mV Current : 10mA
Program accuracy(25±5℃ )	Voltage : ±(0.03% of RDG +10 digits) Current : ±(0.3% of RDG +10 digits)	Voltage : ±(0.5% of RDG +2 digits) Current : ±(0.5% of RDG +2 digits)
Readback accuracy(25±5℃ )	Voltage : ±(0.03% of RDG +10 digits) Current : ±(0.3% of RDG +10 digits)	Voltage : ±(0.5% of RDG +2 digits) Current : ±(0.5% of RDG +2 digits)
CH3 SPECIFICATIONS		
Output Voltage	(2.5V/3.3V/5V)±8%	
Output Current	3A	
Regulation(25±5℃ )	Line regulation ≤5mV Load regulation ≤15mV	
Repple & Noise	≤2mVrms	
KEY LOCK		
Yes		
MEMERY SAVE/RECALL		
4 sets		
POWER SOURCE		
AC100V/120V/220V/230V ± 10%, 50/60Hz		
DIMENSION & WEIGHT		
210(W) x 130 (H) x 265(D) mm ; Approx. 7kg		



GPD-3303S

Rear Panel



ORDERING INFORMATION

- GPD-3303S** Multiple Output High Resolution Programmable Linear D.C. Power Supply  
**GPD-3303D** Multiple Output Programmable Linear D.C. Power Supply

ACCESSORIES :  
User Manual x1  
Power cord x1  
Test lead GTL-104 x 2, GTL-105 x 1  
European Test Lead GTL-203 x 1 , GTL-204 x 2

Optional Accessories

- GTL-246** USB Cable

# Artisan Technology Group is an independent supplier of quality pre-owned equipment

## Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

**We're here to make your life easier. How can we help you today?**

(217) 352-9330 | [sales@artisanng.com](mailto:sales@artisanng.com) | [artisanng.com](https://www.artisanng.com)

