QUICK REFERENCE GUIDE > WB60SMB1-SET

60cm Series 9 Minimal Warming Drawer

Series 9 | Minimal

Black Glass




Serve meals hot and directly from a pre-heated plate thanks to our panel-ready, warming drawer.

- Integrates with surrounding cabinetry for a seamless look
- Space to keep six standard-sized place settings evenly warm
- · Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	140 mm
Width	596 mm
Depth	567 mm



FEATURES & BENEFITS

Complementary design

Our Warming Drawer comes with the option of a stylish black glass panel or elegant grey glass panel, for seamless pairing with our Minimal or Contemporary style ovens. Door panel must be purchased separately.

Multi-function flexibility

Choose from six tailored functions including Rapid Proof for proofing dough, Dehydrate for drying foods such as meat, fruit and herbs and Slow Cook, ideal for finishing of seared meats, casseroles, stews and braises.

Precise control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking. You can even rest meat after a traditional roast in the oven and proof dough for bread making and pizza.

Added convenience

Handle-free, push-to-open with intuitive touch controls, our warming drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Easy to clean

Cleaning and care of the warming drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Safe and sound

With automatic switch-off and delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

Sized to suit

With enough room to gently heat six place settings, 20 cappuccino cups or 42 espresso cups, our 60cm warming drawer is an ideal kitchen companion.

SPECIFICATIONS

Capacity Cappuccino cups Espresso cups 42 Maximum allowable weight Place settings 6

QUICK REFERENCE GUIDE > WB60SMB1-SET

Date: 24.03.2025 > 2

Usable depth	408 mm	
Usable height	98 mm 535 mm	
Usable width		
Cleaning		
Easy clean smooth-glass base	•	
Controls		
Audio feedback	•	
Automatic pre-set temperatures	•	
Automatic timers	30', 45', 1h, 2h, 4h, 6h	
Delayed start	•	
Electronic capacitive touch controls	•	
On/Off indicator	•	
Pre-set heating functions	•	
Push-to-open drawer	•	
Standby mode	•	
Functions		
Cups	•	
Dehydrate	•	
Number of functions	6	
Plates	•	
Rapid proof	•	
Slow cook	•	
Warm	•	

Heated glass base and fan	
Low temperature cooking	
Temperature levels	
Temperature range	35°C-85°
Power requirements	
Amperage	10 /
Power cord length	1800 mr
Supply frequency	50 H
-	
Supply frequency	
Supply frequency Supply voltage Product dimensions Adjustable front door panel to align with	50 H 220
Supply frequency Supply voltage Product dimensions Adjustable front door panel to align with surrounding cabinetry	220
Supply frequency Supply voltage Product dimensions Adjustable front door panel to align with surrounding cabinetry Depth	220 567 mi 140 mi
Supply frequency Supply voltage Product dimensions Adjustable front door panel to align with surrounding cabinetry Depth Height	220 567 mi
Supply frequency Supply voltage Product dimensions Adjustable front door panel to align with surrounding cabinetry Depth Height Width	220 567 mi 140 mi

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

<u></u>	2D-DWG Warming Drawer
\overline{ullet}	2D-DXF Warming Drawer
$\underline{\downarrow}$	Declaration of Conformity
<u>_</u>	Service & Warranty
$\overline{\downarrow}$	Planning Guide EN - 60cm Ovens and Companions - Minimal
$\overline{\downarrow}$	Planning Guide - Handleless Ovens and Companions
<u>_</u>	Revit 20 Warming Drawer
<u>↓</u>	Rhino 6
$\overline{\downarrow}$	Sketchup 8
<u>_</u>	User Guide Warming Drawer DA
<u>_</u>	User Guide Warming Drawer DEU
\overline{ullet}	User Guide Warming Drawer DUT
^^^~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	User Guide Warming Drawer
<u>_</u>	User Guide Warming Drawer FIN
<u>_</u>	User Guide Warming Drawer FR
<u></u>	User Guide Warming Drawer HEB
$\overline{\downarrow}$	User Guide Warming Drawer ITA
$\overline{1}$	User Guide Warming Drawer NOR

Where applicable:

84225

User Guide Warming Drawer SWE

SKU

QUICK REFERENCE GUIDE > WB60SMB1-SET

Date: 24.03.2025 > 3

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 08000886605 Wwww.fisherpaykel.com