

## Alphacool Eiszapfen L-connector 45° G1/4 IT to G1/4 IT - black

Alphacool article number: 17592



### Quick Info

Alphacool's Eiszapfen Connector Series is the high-end execution of these tried-and-true connectors! Every requirement you could have of a connector is met with this series: highflow, form, processing and colour. A refusal to compromise in development and production has made the Eiszapfen series into what it is. Components are available in brilliant chrome or a deep, matte black, which will fit excellently into any system.

- Highflow performance fitting
- High-quality design and discreetly noble colouring

### Scope of delivery

1x Alphacool Eiszapfen L-connector 45° G1/4 IT to G1/4 IT, black

## Technical data

L x W x H	21 x 20 x 21mm
Material	brass
Angle	45°
Thread depth/height	5mm
Threads	2x G1/4" inner thread
Weight	17g
Color	black

## Download links

Product pictures	<a href="#">17592_Alphacool_Eiszapfen_L-connector_45_G1-4_IT_to_G1-4_IT_-_black_pics.zip</a>
------------------	--

## Packaging dimensions per unit

L x W x H	63 x 63 x 30 mm
Weight	27 g

## Other data

Certificates	CE, FC, RoHS
EAN	4250197175920
Customs code	74198090990

## Article text

Alphacool's Eiszapfen Connector Series is the high-end execution of these tried-and-true connectors! Every requirement you could have of a connector is met with this series: highflow, form, processing and colour. A refusal to compromise in development and production has made the Eiszapfen series into what it is. Components are available in brilliant chrome or a deep, matte black, which will fit excellently into any system.

A special procedure binds the outer coating firmly to the surface, improving the longevity of the intense colour and preventing any chipping or peeling of the coating. Every connector now has the Alphacool logo, which along with their distinctive shape makes them unmistakable!

### Version

This 45° angled adapter has a G1/4" female thread on both sides. This 45° angled connection is used in water circuits where there is limited space for tubing and a special solution is needed.