

# Entrant™ HF CRT-D

CDHFA300B



Compatible with  
myMerlinPulse™ app

## Product Highlights

- Bluetooth® Low Energy (LE) communication enabling Smartphone Connectivity through data encryption.
- SyncAV™ CRT technology offers dynamic AV timing with customizable programming to ensure BiV pacing.
- Cold can programmability provides an additional RV-SVC shock configuration to decouple the can from the shocking vector parameters in cases of lead problems.
- DeFT Response™ Technology offers noninvasive programming options to optimize rescue therapy to each patient's unique physiology and changing conditions.
- VF Therapy Assurance decreases time to treatment for arrhythmias in patients who are likely to be hemodynamically unstable.
- Antitachycardia pacing (ATP) while charging and prior to charging in the VF zone further extends the programming options for terminating tachyarrhythmias without a high-voltage shock.
- ShockGuard™ technology with DecisionTx™ programming designed to reduce inappropriate therapy and minimize the need for programming adjustments at implant.
  - SecureSense™ RV lead noise discrimination detects sustained lead noise and short bursts of oversensing that would otherwise go unnoticed or potentially lead to one or more inappropriate shocks.
  - Far Field MD™ morphology discrimination and Chamber Onset discrimination enhance SVT and VT discrimination for reduced inappropriate therapies.
- SenseAbility™ sensing algorithm feature provides the flexibility to fine-tune programming around T-wave oversensing without decreasing sensitivity.
- DynamicTx™ over-current detection algorithm automatically changes shock configurations to ensure delivery of high-voltage therapy when high current is detected.
- MRI-Ready device tested in combination with MR Conditional leads for full-body scans using a 1.5T or 3T (Tesla) field strength MRI Scanner\*.
- Premature Atrial Contraction (PAC) Response to avoid pacing the atrium in a vulnerable zone.
- Physiologic rate responsive AV Delay and PVARP.
- QuickOpt™ timing cycle optimization provides quick and effective optimization at the push of a button.
- Dual patient notification: audio notification through the device and visual notification via myMerlinPulse™ app.
- The CorVue™ thoracic impedance feature measures transthoracic impedance changes over time to provide additional insight into the patient's heart failure condition.

## Ordering Information

Contents: Cardiac Pulse Generator

| MODEL NUMBER | DIMENSIONS (L × W × H) (MM) | WEIGHT (G) | VOLUME (CC) | CONNECTOR DEFIBRILLATION | CONNECTOR SENSE/PACE | CONNECTOR PACE - LEFT VENTRICLE |
|--------------|-----------------------------|------------|-------------|--------------------------|----------------------|---------------------------------|
| CDHFA300B    | 79 × 51 × 12                | 79         | 37          | DF-1                     | IS-1                 | IS-1                            |

\*See MRI Scan Parameters in MRI-Ready Systems Manual.



## Product Specifications

| PARAMETER SPECIFICATIONS               |   |
|--|---|
| <b>Model</b>                           | <b>CDHFA300B</b>  |
| Telemetry                              | Bluetooth® LE Communication   |
| Delivered/Stored Energy                | 36/39 J   |
| Volume                                 | 37 cc   |
| Weight                                 | 79 g  |
| Size                                   | 79 × 51 × 12 mm   |
| Defibrillation Lead Connection         | DF-1  |
| Atrial Sense/Pace Lead Connection      | IS-1 in-line bipolar  |
| Ventricular Sense/Pace Lead Connection | IS-1 in-line bipolar  |
| Left Ventricular Pace Lead Connection  | IS-1  |
| High Voltage Can                       | Electrically active titanium can  |
| <b>Parameter</b>                       | <b>Settings</b>   |
| <b>Biventricular Pacing</b>            |   |
| V. Triggering                          | On; Off   |
| V-V Timing                             | Simultaneous <sup>1</sup> ; RV First; LV First  |
| Interventricular Pace Delay            | RV First 10-80/LV First 15-80 ms  |
| Ventricular Sensing                    | RV only (not programmable)  |
| Ventricular Pacing Chamber             | RV only; Biventricular  |
| SyncAV™ CRT Technology Delta           | -10 to -120 ms; Off   |
| <b>Sensing/Detection</b>               |   |
| SenseAbility™ Sensing Algorithm        | Automatic sensitivity control adjustment for atrial and ventricular events  |
| Low Frequency Attenuation              | On; Off   |
| Threshold Start                        | Post-Sensed: 50; 62.5; 75; 100%;<br>Post-Paced; Atrial: 0.2-3.0 mV<br>Post-Paced; Ventricular: Auto: 0.2-3.0 mV   |
| Decay Delay                            | Post-Sensed: 0-220 ms<br>Post-Paced; Atrial: 0-220 ms<br>Post-Paced; Ventricular: Auto: 0-220 ms  |
| Ventricular Sense Refractory           | 125; 157 ms   |
| Detection Zones                        | 3 zone programming - 1 zone; 2 zones or 3 zones<br>(VT-1; VT-2; VF)   |
| SVT Discriminators                     | AV Rate Branch; Arrhythmia Onset (Chamber Onset or Sudden Onset); Interval Stability; AV Association Morphology; Discrimination (Far Field MD™ Morphology Discrimination or Original MD) with Automatic Template Update |
| Monitor Mode                           | Detection; discrimination and diagnostics; no therapy delivery (VT or VT-1 zone)  |
| Discrimination Modes                   | On; Passive; Off  |

## Product Specifications

| Parameter   | Settings  |
|---|---|
| <b>Sensing/Detection</b>                            |   |
| SVT Upper Limit                                     | 150-240 bpm   |
| SVT Discrimination Timeout                          | 20s-60 min; Off   |
| Reconfirmation                                      | Continuous sensing during charging  |
| SecureSense™ RV Lead Noise Discrimination Algorithm | On; On with Timeout; Passive; Off   |
| VF Therapy Assurance                                | On; Off   |
| <b>Antitachycardia Pacing Therapy</b>               |   |
| ATP Configurations                                  | Ramp; Burst; Scan; 1 or 2 schemes per VT zone   |
| ATP in VF Zone                                      | ATP While Charging; ATP Prior to Charging; Off  |
| ATP Upper Rate Cutoff                               | 150-300 bpm   |
| Burst Cycle Length                                  | Adaptive (50%-100%); Fixed (200-550 ms)   |
| Min. Burst Cycle Length                             | 150-400 in increments of 5 ms   |
| Readaptive  | On; Off   |
| Number of Bursts/Stimuli                            | 1-15 with 2-20 Stimuli  |
| Add Stimuli per Burst                               | On; Off   |
| ATP Pulse Amplitude                                 | 7.5 V independent from Bradycardia and Post-Therapy Pacing  |
| ATP Pulse Width                                     | 1.0 or 1.5 ms independently programmable from Bradycardia and Post-Therapy Pacing   |
| <b>High-Voltage Therapy</b>                         |   |
| DynamicTx™ Over-Current Detection Algorithm         | On; Off   |
| DeFT Response™ Technology                           | Programmable pulse width for P1/P2 and tilt   |
| High-Voltage Output Mode                            | Fixed Pulse Width; Fixed Tilt   |
| Waveform  | Biphasic; Monophasic  |
| RV Polarity   | Cathode (-); Anode (+)  |
| Electrode Configuration                             | RV to Can; RV to SVC/Can; RV to SVC   |
| <b>Bradycardia Pacing</b>                           |   |
| Permanent Modes                                     | DDD(R); DDT(R); DDI(R); VVT(R); VVI(R); AAI(R); Off   |
| Temporary Modes                                     | DDD; DDT; DDI; VVT; VVI; AAI; AAT; DOO; VOO; AOO; Off   |
| Rate-Adaptive Sensor                                | On; Off; Passive  |
| Programmable Rate and Delay Parameters              | Off; Base Rate (bpm); Rest Rate (bpm); Maximum Tracking Rate (bpm); Max Trigger Rate (bpm) Maximum Sensor Rate (bpm); Paced AV Delay (ms); Sensed AV Delay (ms); Rate Responsive AV Delay; Hysteresis Rate (bpm); Rate Hysteresis with Search |
| Pulse Amplitude                                     | 0.25-7.5 V  |
| Pulse Width   | 0.05; 0.1-1.5 ms  |
| LVCap™ Confirm Feature                              | Setup; On; Monitor; Off   |
| RVCap™ Confirm Feature                              | Setup; On; Monitor; Off   |
| ACap™ Confirm Feature                               | On; Monitor; Off  |
| Auto Mode Switch (AMS)                              | DDI(R); DDT(R); VVI(R); VVT(R); Off   |
| Atrial Tachycardia Detection Rate                   | 110-300 bpm   |
| AMS Base Rate                                       | 40; 45; ... 135 bpm   |
| Auto PMT Detection/Termination                      | Atrial Pace; Passive; Off   |
| Rate Responsive PVARP                               | Low; Medium; High; Off  |
| Rate Responsive V Pace Refractory                   | On; Off   |
| PAC Response  | On; Off   |
| PAC Response Interval                               | 200-400 ms  |
| Shortest AV Delay                                   | 25-120 ms   |

## Product Specifications

| Parameter  | Settings  |
|--|---|
| <b>Post-Therapy Pacing (Independently programmable from Bradycardia and ATP)</b> |   |
| Post-Shock Pacing Mode   | AAI; VVI; DDI; or DDD; Off  |
| Post-Shock Base Rate   | 30-100 bpm  |
| Post-Shock Pacing Duration   | 0.5; 1; 2.5; 5; 7.5; or 10 min; Off   |
| <b>Device Testing/Induction Methods</b>  |   |
| DC Fibber™ Induction Method Pulse Duration                                       | 0.5-5.0 sec   |
| BurstFibberCycle Length  | 20-100 ms   |
| Noninvasive Programmed Stimulation (NIPS)  | 2-25 stimuli with up to three extra stimuli   |
| <b>Patient Notifiers</b>   |   |
| Programmable Notifiers (On; Off)   | BatteryAssurance™ alert; Possible HV circuit damage; HV charge timeout; Long charge time for Capacitor Maintenance; Device at ERI; Right ventricular pacing lead impedance out of range; Left ventricular lead impedance out of range; High-voltage lead impedance out of range; AT/AF episode duration; AT/AF Burden; High ventricular rate during AT/AF; SecureSense™ lead noise detection; Non-sustained ventricular oversensing; Biventricular pacing percentage lower than limit |
| Device Parameter Reset   | On  |
| Entry into Backup VVI Mode   | On  |
| Auditory Duration  | 2; 4; 6; 8; 10; 12; 14; 16 sec  |
| Number of Audio Alerts per Notification  | 2   |
| Number of Notifications  | 1-16  |
| Time Between Notifications   | 10; 22 hours  |
| <b>Electrograms and Diagnostics</b>  |   |
| Stored Electrograms  | Up to 15 minutes (2 user programmable + discrimination channel); up to one minute programmable pre-trigger data per VT/VF electrograms; additional triggers include lead noise detection; non-sustained ventricular oversensing; morphology template updates; atrial episode; PMT termination; PAC response; magnet reversion; noise reversion  |
| Therapy Summary  | Diagram of therapies delivered  |
| Episodes Summary   | Directory listing of up to 60 episodes with access to more details including stored electrograms  |
| Lifetime Diagnostics   | History of bradycardia events and device-initiated charging   |
| AT/AF Burden Trend   | Trend data and counts   |
| Ventricular HV Lead Impedance Trend  | Multi-Vector Trend Data   |
| Histograms and Trends  | Event Histogram; AV Interval Histogram; Mode Switch or AT/AF Duration Histogram; Peak Filtered Atrial Rate Histogram; Atrial Heart Rate Histogram; Ventricular Heart Rate Histogram; AT/AF Burden; Exercise and Activity Trending; V Rates During AMS; DirectTrend™ reports up to 1 year  |
| PMT Data   | Information regarding PMT detections  |
| Real-Time Measurements (RTM)   | Pacing lead impedances; high-voltage lead impedances; and signal amplitudes   |
| CorVue Thoracic Impedance  | On; Off   |
| CorVue Thoracic Impedance  | Threshold 8-18 days   |
| <b>MRI Settings</b>  |   |
| Tachy Therapy  | Disabled  |
| MRI Mode   | DOO; VOO; AOO; Pacing Off   |
| MRI Base Rate  | 30-100 bpm  |
| MRI Paced AV Delay   | 25-110 ms   |
| MRI RA and RV Pulse Amplitude  | 5.0 or 7.5 V  |
| MRI RA and RV Pulse Width  | 1.0 ms  |
| MRI RA and RV Pulse Configuration  | Bipolar   |
| MRI V Pacing Chamber   | RV Only   |
| MRI Timeout  | 3; 6; 9; 12; 24 hours; Off  |

Product Specifications

| MRI SCAN PARAMETERS <sup>‡</sup>             |                |                             |             |
|--|----------------|-----------------------------|-------------|
| Lead Model                                   | Magnet (Tesla) | RF Transmit Conditions      | Scan Region |
| <b>Durata™ Defibrillation Lead</b>           | 1.5 T / 3 T    | Normal<br>Operating<br>Mode | Full-body   |
| 7120 (Lead lengths: 65 cm)                   |                |                             |             |
| 7122 (Lead lengths: 60, 65 cm)               |                |                             |             |
| <b>Optisure™ Lead</b>                        | 1.5 T / 3 T    |                             |             |
| LDA210 (Lead lengths: 65 cm)                 |                |                             |             |
| <b>Tendril™ STS Pacing Lead</b>              | 1.5 T / 3 T    |                             |             |
| 2088TC<br>(Lead lengths: 46, 52, 58 cm)      |                |                             |             |
| <b>UltiPace™ Pacing Lead</b>                 | 1.5 T / 3 T    |                             |             |
| LPA1231<br>(Lead lengths: 46, 52, 58, 65 cm) |                |                             |             |

<sup>†</sup> LV first with 10 ms interventricular delay.

<sup>‡</sup> For additional information about specific MR Conditional CRT-Ds and leads, including scan parameters, warnings, precautions, adverse conditions to MRI scanning, and potential adverse events, please refer to the Abbott MRI-Ready Systems Manual at [manuals.eifu.abbott](https://manuals.eifu.abbott).

**Brief Summary:** This product is intended for use by or under the direction of a Physician. Prior to using these devices, please review the Instructions for Use for a complete listing of indications, contraindications, warnings, precautions, potential adverse events and directions for use.

**Abbott**  
15900 Valley View Court, Sylmar, CA 91342  
Tel: +1 818 362 6822  
[Abbott.com](https://www.abbott.com)

<sup>™</sup> Indicates a trademark of the Abbott group of companies.

<sup>‡</sup> Indicates a third party trademark, which is property of its respective owner.

