

PORTABLE AC

MODEL AP0819CR1W, AP0721CR1W/ AP0721CRW, AP08CR1RNX-N, AP0821CR1W, AP-12DR2SFTS10



- 3 in 1 modes with cooling, fan & dry
- Removes moisture from the air and helps prevent mould and bacteria
- Digital LED display
- Built-in wheels for greater portability
- window mounting kits
- Drain-free operation (self-evaporating)



Low Noise Airflow System

High performance centrifugal fan ensures quiet operation as low as 47dB(A)



Filter Monitor

Washable filter helps to reduce bacteria, odors, and particles



Warranty

2-Year Exchange

Cool comfort

The Hisense Portable Air Conditioner is best suited for medium rooms, delivering coverage of up to 350 sq. ft. It provides three modes of comfort – cooling, fan or dehumidifier allowing you to choose the comfort you want at any time. The convenient drain-free design means you never need to worry about removing condensed moisture, and its efficient design provides quiet operation for your peace of mind.





MODEL AP0819CRIW, AP0721CRIW/ AP0721CRW, AP08CR1RNX-N, AP0821CRIW, AP-12DR2SFTS10











	4 D 0 0 1 0 0 D 1 1 1 1	4 D 6 T 6 4 6 D 4 1 1 1	4 D 4 6 6 D 4 D 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	100001000111	4.0.400.0000000000000000000000000000000
Model #	AP0819CR1W	AP0721CR1W/ AP0721CRW	AP08CR1RNX-N	AP0821CR1W	AP-12DR2SFTS10
Performance					
DOE Cooling Capacity (BTU/h) SACC	5500	7000	8000	8000	8000
DOE Cooling Efficiency Ration (CEER)	5.4	6.9	7.2	7.2	7.2
Rated Sound (dBA) (Low-High)	47-49 dBA	49-52 dBA	50-53 dBA	47-50 dBA	47-50 dBA
Appx Square Foot cooling (sq. ft.)	250 sq. ft.	Up to 300 sq. ft.	Up to 350 sq. ft.	Up to 350 sq. ft.	Up to 350 sq. ft.
General Features					
Air Flow on High (CFM)	170	241	241	230	230
Compressor Type	Rotary	Rotary	Rotary	Rotary	Rotary
Unit Control Type	Electronic	Electronic	Electronic	Electronic	Electronic
Display Type	LED	LED	LED	LED	LED
Fan	Yes - 2 Speed	Yes - 3 Speed	Yes - 3 Speed	Yes - 3 Speed	Yes - 3 Speed
Cooling Speed selections	2	3	3	3	3
Air Swing (Motor Up/Down Motion)	No	Yes	Yes	Yes	Yes
Flexible Condenser Air Hose (included)	Yes (1-5.9"Dia x 59" Length) Grey	Yes (1-5.9"Dia x 59" Length) Grey	Yes (1-5.9"Dia x 60" Length) Grey	Yes (1-5.9"Dia x 59" Length) Grey	Yes (1-5.9"Dia x 59 Length) Grey
Electrical					
Voltz, Frequency and Fuse Size (Amps)	115V, 60Hz, 13 Amps	115V, 60Hz, 15 Amps	115V, 60Hz, 15 Amps	115V, 60Hz, 15 Amps	115V, 60Hz, 15 Amps
Shipping					
Unit Dimension WxDxH (inch)	11.8" x 13" x 26.3"	16.9" x 12.8" x 27.3"	17.0" x 12.5" x 27.8"	17.4" x 12.5" x 29.0"	17.4" x 12.5" x 29.0'
Carton Dimension WxDXH (inch)	13.5" x 15.2" x 34.4"	18.9" x 15.0" x 35"	18.9" x 15.0" x 34.6"	19.6" x 15.2" x 34.8"	19.6" x 15.2" x 34.8'
Net Weight /Gross Weight (lbs)	52.9 lbs / 58.4 lbs	58.4 lbs /65.5 lbs	63.9 lbs / 70.5 lbs	66.1 lbs / 73.3 lbs	66.1 lbs / 73.3 lbs
Warranty/UPC					
Warranty (Exchange)	2 Years	2 Years	2 Years	2 Years	2 years
UPC	819130023595	819130027302 / 819130029108	810088360183	819130027371	819130026947

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2022 Hisense Canada Co., Ltd. All rights reserved.