Daikin One+ Smart Thermostat for Single & Multi-Zone Systems

Controls Product Marketing Group



Wiring and Mounting

Future Development

Reference


Agenda

Daikin One+ Smart Thermostat



DTST-ONE-ADA-A






















































Introduction

Daikin One+ Smart Thermostat












Daikin One+ Smart Thermostat for Ductless Product










New packaging and part number



DTST-ONE-ADA-A




What is in the box?






Wiring Overview

Indoor units that have a S21 connector



Not compatible with other wired or wireless remote controllers


- Indoor units that do not have a S21 connector
 - Require a separate Interface Adaptor



Indoor Unit Models	Interface Adaptor
FTX09NMVJU, FTX12NMVJU, FTK09NMVJU, FTK12NMVJU	KRP067A41E
FTX15NMVJU, FTX18NMVJU, FTX24NMVJU, FTK18NMVJU,	KRP980B2E
FTK24NMVJU	



Wiring Overview






Thermostat terminal plate



Translation Adaptor Wiring




Wire Name	Туре	Connect to	Max length
High-voltage power line	3-wire, included in the package	Indoor unit power terminal or external	5 ½ ft
		power source (110-240VAC)	
Thermostat wire	Field-supplied, 18AWG, 4-conductor	Daikin One+ Thermostat	125 ft
	non-shielded stranded wire		
S21 cable	5-conductor wire with connectors,	S21 terminal on the indoor unit PCB or	6 ft
	included in the package	S21 terminal on the Interface adaptor	




Translation Adaptor Mounting

- Mounting using screws
 - Mount to the wall
 - Never use screws to mount to the indoor unit



Front Cover (Optional when mounting inside wall mount piping chase)

- Mounting using adhesive tape
 - Mount to the surface of indoor unit






Translation Adaptor Mounting Location

- Wall mounted indoor unit
 - Preferred installation: place translation adaptor inside piping chase to conceal it from view by the owner or on outside of the indoor unit.







- Ducted/Ceiling indoor unit
 - Preferred installation: place translation adaptor on the side, on top of the indoor unit, or above the ceiling using supplied double sided adhesive tape.






High quality cover for mounting outside



Future Development

- Daikin wireless temperature and humidity sensors (flush mount/wall mount)
- Daikin One Dealer Services
- Over-the-air (OTA) update
 - Logics
 - Aux Heater Oct 2020
 - Aux humidifier and dehumidifier
 - Compatibility with P1P2 indoor units- Oct 2020
 - FDMQ, FFQ, SkyAir, and VRV
 - Same device/part number
 - Peel off "VRV Support Coming Soon" sticker once software update is available





Reference

- https://daikinone.com/
- Documents will be available on Daikin City and daikinone.com:
 - Product Brochure/Flyer
 - Submittal Data Sheet
 - Installation Manual
- Available to order: Aug 2020

