

SUBMITTAL DATA: PLA-A24AA & PUY-A24NHA
24,000 Btu/h CEILING CASSETTE AIR-CONDITIONING SYSTEM

Job Name:	Location:	Date:
Purchaser:	Engineer:	
Submitted to:	For ☐ Reference ☐ Approval ☐ Construction	
Unit Designation:	Schedule No.:	

GENERAL FEATURES

- Limited Warranty – One year on parts and defects, six years on compressor
- Compact, side discharge outdoor unit
- Quiet operation – indoor and outdoor units
- Auto-restart following a power outage
- Self-check function – onboard diagnostics
- Advanced microprocessor control
- Built-in drain lift mechanism for condensate removal
- Zone control
- Hard-wired, wall-mounted, remote controller (PAR-21MAA)
- 2, 3, or 4 way air flow selection / 6" round or 4 X 14" rectangular branch duct connection
- 4" ventilation air inlet
- Washable filter

OPTIONAL FEATURES

- Multi-function casement
- High efficiency filter element
- Air outlet shutter plate(s)
- Wireless Remote Controller kit
- M-Net adapter
- Wind Baffle
- Air outlet guide

COOLING

Rated capacity 24,000 Btu/h
Minimum capacity 12,000 Btu/h
SEER 13.4 Btu/h/W
Total input 2500 W
Power supply 208 / 230V, 1 Phase, 60 Hz
Breaker size 25 A

VOLTAGE

Indoor - Outdoor S1-S2 AC 208/230V
Indoor - Outdoor S2-S3 DC 24V
Indoor - Remote Controller DC

NOTES:

*1. Rating conditions (cooling)-indoor : D.B. 80°F, W.B. 67°F
outdoor : D.B. 95°F, W.B. 75°F.

OPERATING RANGE

	Indoor intake air temp.	Outdoor intake air temp.
Cooling Max	D.B. 95°F, W.B. 71°F	D.B. 115°F
Min	D.B. 67°F, W.B. 57°F	D.B. 0°F *

* With wind baffle installed. If not installed, the minimum temperature will be 23°FDB.


INDOOR UNIT

MCA 1 A
Fan motor 0.79 F.L.A.
Fan motor output 70 W
Airflow (Lo-M1-M2-Hi) 530-570-640-710 Dry CFM
490-530-600-670 Wet CFM
Sound level (Lo-M1-M2-Hi) 28-30-32-34 dB(A)

DIMENSIONS	UNIT	PANEL
inches	W	33-1/16
	D	33-1/16
	H	10-3/16
mm	W	840
	D	840
	H	258

WEIGHT (unit/panel)

Pounds 53 / 11
Kg 24 / 5
Field drain pipe size I.D. (inches/mm) 1 / 25.4
Wall-mounted remote controller PAR-21MAA
(see data submittal sheet)

OUTDOOR UNIT



Compressor DC inverter/twin rotary
MCA 18
Fan motor 0.75 F.L.A.
Sound level 48 dB(A)

DIMENSIONS	INCHES	MM
W	37-3/8	950
D	13 + 1-3/19	330 + 30
H	37-1/8	943

Weight (lbs/Kg) 97 / 44
Refrigerant type R410A
Refrigerant pipe size O.D. (inches/mm)
gas side 5/8 / 15.88
liquid side 3/8 / 9.52
Max. refrigerant pipe length (ft/m) 165 / 50
Max. refrigerant pipe height difference (ft/m) 100 / 30
Connection method flared

Notes:


DIMENSIONS: PLA-A24AA & PUY-A24NHA



ARI Standard
210/240 UHP



HVAC Advanced Products Division
Mitsubishi Electric & Electronics USA, Inc.

3400 Lawrenceville Suwanee Rd
Suwanee, GA 30024
Tele: 678-376-2900 • Fax: 800-889-9904
Toll Free: 800-433-4822 (#3)

www.mehvac.com
Specifications are subject to change without notice.