



PANOVISTA™ EXTENDED CONVEX MIRRORS

- WARNING** This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.
- CAUTION** This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.
- ATTENTION** This indication alerts you to the fact that if you ignore this detail you will affect the performance or functionality of the product.

All Giro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation. Read completely and understand the instructions prior to starting installation.

NOTE: Giro products are designed and manufactured under very strict quality control. Giro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a limited lifetime warranty against LED failure. Giro will have no obligation if the customer cannot show proof of purchase. Warranty will not be granted unless the part is properly installed, unmodified and maintained. Giro will not be liable for any consequential and incidental damages, including labor, or non-Giro products. Please visit Ciro3d.com for our complete warranty policy.

Included Items:



Installation Instructions:

1. Park on level surface and shut off motorcycle. Ensure engine has time to cool before installation.
2. Pull out mirror at bottom edge until it stops. Fig. 1a
3. Pull mirror firmly at bottom. It will snap loose. Fig. 1b
4. Pull the top of mirror out until it stops. Lift disconnected bottom of mirror and pull down to release mirror. Fig. 2
5. Note the tabs on the mirror in Fig. 3. The tabs are the same on the new mirror and go on in the reverse order. At an angle shown in Fig. 2 slide the tabs in and up till engaged and push bottom of mirror in until clips snap onto bars and you hear a click.
6. Repeat steps 2-5 on other side of motorcycle.

ATTENTION When adjusting mirror always push mirror instead of pulling to avoid accidentally pulling mirror loose at the bottom.

