

PANTUM
The New Era for Printing

BP4200DW
Monochrome Laser Printer

EFFORTLESS HIGH-SPEED PRINTING

EFFICIENT PRO SERIES

BP4200DW



MONO



Highly efficient,
Reassuringly secure



Built to last,
print with confidence



Quick printing at your
fingertips



Toward a sustainable
future

1. Mopria, the Mopria Logo and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited.
2. Apple AirPrint is the trademark of Apple Inc., registered in the U.S. and other countries.



PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



BP4200DW

Monochrome Laser Printer

PRINTING

Print technology	Mono laser
Print speed	33ppm (A4) / 35ppm (Letter)
First print out time	8.5 seconds
Maximum monthly duty cycle	80,000 pages
Recommended monthly volume	1,000 to 10,000 pages
Processor speed	800 MHz
Memory	256 MB
Resolution(dpi)	Up to 1,200 x 1,200 dpi
Printer language	PCL5e, PCL6, PS3 emulation, PDF
Duplex mode	Auto
Control panel	2-Line LCD
Mobile print	Airprint, Mopria, PANTUM App, Android App, iOS App
Other function	Booklet, Poster, N-up, Watermark, Enhance fine line, Silent mode

PAPER HANDLING

Paper input tray	250 sheets
Multipurpose tray	1 sheet
Paper output tray	150 sheet
Media types	Paper (plain, thick, thin, recycled), Transparency, Cardstock, Label, Envelope
Media sizes	A4, A5, JIS B5, ISO B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2, Custom
Media weight	Input tray : 60-105g/m ² Multipurpose tray : 60-200g/m ²

GENERAL

Dimensions (W×D×H)	333x370x218 mm
Product weight (with cartridge)	9.7 kg.
Package size (W×D×H)	413x441x311 mm
Package weight (with cartridge)	10.9 kg.
Operating temperature range	10 ~ 32°C (50-90°F)
Operating humidity range	20% ~ 80% RH
Input voltage	110V: AC100-127V, 50/60Hz,9A 220V: AC220-240V, 50/60Hz, 4.5A
Noise level	Print≤ 52dB (A) Ready≤30dB (A)
Power consumption	Print average≤525W Ready≤50W Sleep≤1W
Operating system	Microsoft Windows : Server2012/Server2016/Server2019/Server2022/XP/Win7 /Win8.1/Win10/Win11(32/64 Bit) Mac : 10.10~14 Linux : Ubuntu16.04/18.04/20.04/22.04 Chrome : 99.0.4844.57 and 103.0.5060.114 Android : 6.0-13.0 Harmony iOS 1.0-3.0 iOS 13.0-18
Connectivity	High-speed USB 2.0; IEEE 802.3 10/100Base-Tx Ethernet; IEEE 802.3az(EEE), Dual-band WiFi (2.4G/5G) (IEEE 802.11a/b/g/n), Bluetooth*

SUPPLIES

Consumable type	Toner Cartridge & Drum Unit
Starter cartridge ⁽¹⁾	TL-C4201: 1,500 pages
Starter drum unit ⁽²⁾	DL-C4201: 25,000 pages
Standard cartridge ⁽¹⁾	TL-C4201H: 3,000 pages; TL-C4201X: 6,000 pages; TL-C4201U: 11,000 pages
Standard drum unit ⁽²⁾	DL-C4201: 25,000 pages

⁽¹⁾ Toner cartridge capacity is based on ISO 19752.

⁽²⁾ Drum unit lifetime is based on 3 average letter/A4-size pages per print job.

All the specifications are from Pantum internal test data. Actual specifications and performance are affected by different printing habits and printing environment.

*For Wi-Fi configuration via mobile