THINKWARE DASH CAM™

Quick Start Guide

XD100

Power the Dash Cam

Use one of the following options

The included cable options vary depending on the dash cam model purchased.



12V Power Cable



Hardwiring Cable*



OBD-II Cable*



*To enable Parking Surveillance mode, the dash cam needs to be powered by either the OBD-II Cable or Hardwiring Cable (professional installation recommended).

Download the App

Download the THINKWARE DASHCAM LINK App

On your smartphone, open the Google Play Store or Apple App Store and download and install **THINKWARE DASH CAM LINK.**



THINKWARE DASH CAM LINK



Apple Store (iOS)




Google Play Store (Android)

Connect to the App

Follow the on-screen instructions


1, Press the Wi-Fi ? button on the Dash Cam.






Won't connect to the App?


Install the Front Camera




· Green line with the front edge of the hood



Install the Rear View Camera



- · Green line with the trunk line



Dash Cam Settings in the App

Default settings out of the box

The default settings are as follows, and you have the option to adjust them according to your preference.

Options	Description
Voice Recording	Enabled
System Volume	0 1 2 3
Parking Mode	Disabled
Super Night Vision	Parking Mode
ADAS	Disabled
Speed Stamp	Enabled
Safety Camera	Enabled

FAQ & Help Desk

Still have questions or issues?

For further assistance or to report any issues, please contact our support team.

- · North America
 - 1 (844) 865-9273 support@thinkware.com
- · United Kingdom
 - 44 (0) 333-121-0008 support.eu@thinkware.com
- European Union (+49) 69-943-22200 support@thinkware.com



FAQs & Help Desk

Please refer to **CS Information QR** in the box for other countries.