



C2C (Mini O Plus)

Simple yet Extremely Powerful

A Full HD 1080p Wi-Fi camera with a magnetic base, designed for simple and quick installation.

Key Features

**Full
HD**

1080p



Supports MicroSD card slot,
up to 128GB



Supports 2.4GHz Wi-Fi
(IEEE802.11b, 802.11g, 802.11n)



Two-way audio



True Day/Night camera with
auto-switching. Infrared night
vision up to 7.5 meters.



Easy Installation

The C2C (Mini O Plus) comes with a magnetic base and mounting kit for easy placement on walls or ceilings.

Once set up, you can manually adjust it to cover just about any angle you need.



Full HD 1080p video with an ultra-wide-angle lens

The C2C (Mini O Plus) delivers Full HD 1080p video, and with a 135° ultra-wide-angle lens, it covers a wider range of space, so you can keep an eye on what's valuable to you.



Keep Them Safe, Day and Night

When it's dark, the C2C (Mini O Plus) automatically switches to night vision mode for around-the-clock Full HD video coverage, ensuring a night vision up to 7.5 meters.



Instant alerts (manual activation required)

The C2C (Mini O Plus) watches for movement. It will take a picture and send alerts to your smartphone when it detects motions.



Two-way audio

The camera comes with a built-in microphone and speaker, enabling two-way audio via the camera and your phone or tablet.



Specifications

CS-CV206-C0-3B2WFR

Camera

Image Sensor	1/2.7"2MP HD Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	2.8mm@F2.0, view angle: 115° (Horizontal), 135° (Diagonal)
Lens Mount	M12
Day & Night	IR-cut filter with auto-switching
DNR	3D DNR
WDR	Digital WDR

Compression

Video Compression	H.264
H.264 Type	Main Profile
Video Bit Rate	HD, Balanced and Smooth bit rate.

Image

Max. Resolution	1920×1080
Image Settings	Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)
BLC	Support

Network

Storage	Supports MicroSD card (max. 128GB)
Smart Alarm	Motion detection
Wi-Fi Pairing Protocol	SmartConfig (Wi-Fi One-Key Configuration)/AP paring
Interface Protocol	EZVIZ Cloud proprietary protocol
General Features	Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror Image, Password Protection, Watermark
Minimum Network Requirements	2 Mbps

Wi-Fi

Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11 Mbps, 11g: 54 Mbps, 11n: 150 Mbpss

General

Power Supply	DC 5V±10%
Power Consumption	MAX. 3W
IR Range	MAX. 7.5 meters
Product Dimensions	128mm x 58mm x 38mm
Packaging Dimensions	149mm x 87.5mm x 91.5mm
Weight	0.265 lb. (120g)

Package Contents:

- C2C (Mini O Plus) X 1
- 3 Meters USB Cable X 1
- Power Adapter X 1
- Foam Sticker X 2
- Metal Plate (3.5mm Hole Diameter) X 1
- Quick Start Guide X 1

Requirements

- Operating Conditions: -10°C ~ 50°C, Humidity 95% or less (non-condensing)

Certificates

FCC/UL/IC/NOM/CE/RoHS/WEEE/REACH

Specifications are subject to change without notice. EZVIZ is a registered trademark of Hangzhou EZVIZ Network Co., Ltd.
Other brands and product names are trademarks or registered trademarks of their respective holders.

<https://www.ezvizlife.com/>