

Marine Shocker™ Instructions

For use in interior spaces up to 400 cubic feet

Read all the instructions before use! To ensure the best results, follow all steps exactly as directed.

Step-by-Step Instructions

1. Prepare the Cabin

- Move the boat out of direct sunlight or block sunlight from entering the designated cabin space.

2. Open the Package

- Open the container and remove all contents.
- Carefully read all information on the foil packet.
- Open the foil packet at the notched edge, being careful not to damage the contents inside.
- Remove the CLO2DMG Technology™ white pouch and discard the small desiccant pouch. Save the foil packet until the treatment is complete.

3. Activate Marine Shocker™

- Shake the CLO2DMG Technology™ white pouch thoroughly to mix ingredients.
- Place the pouch back into the provided container.
- Place the container in the designated treatment area. For added protection, place it on a plate or container lid to prevent possible spillage, staining, or bleaching.

4. Add Water

- Using the provided measuring cup, add one full cup of cold water over the pouch to activate.
- DO NOT replace the lid on the container until the treatment is complete and the product is ready for disposal.
- Note: In some cases, the product may clump over time, which could cause a popping or sputtering effect. If you hear this, there's no need to be alarmed. The product will still activate and function as intended.

5. Secure the Cabin

- Lock the cabin to prevent entry during treatment.
- **WARNING:** Do not allow people or pets inside the cabin while the Marine Shocker™ is active.

6. Treatment Duration

- Allow the Marine Shocker™ to work for 4 to 24 hours.

7. After Treatment

- Open all doors for ventilation.
- Place the lid back on the container and dispose of it in an outdoor waste container.
- Allow the cabin to ventilate for at least 30 minutes before re-entry.

Tips for Best Results

- Open all interior compartments (cabinets, glove box, armrests, etc.).
- Pull down all visors.
- Stand floor mats on their sides.
- Clean out ashtrays and remove trash.
- Replace air filters before use.
- Before proceeding to Step 7, set the fan to recirculate and run it for 15 minutes.
- For best results, the minimum temperature for activation should be: 50°F.

Additional Information

Safety Note:

- The product is safe and non-toxic when used as directed. It degrades into a saline solution. All components are biodegradable and eco-friendly.

WARNING:

- While Marine Shocker™ is non-toxic, Chlorine Dioxide can be an irritant. Avoid inhaling the Chlorine Dioxide directly. (Do not do a smell test.)

- To prevent spills or accidental inhalation of fumes, **activate the product only at point of use.**
- **Do not walk with the product after activation from point A to point B,** as this may result in exposure to concentration of fumes.
- For added safety, wear a mask and protective eyewear during handling or when ventilating the cabin.

Important:

- Ensure the lid is securely placed on the container before removing it from the cabin to avoid spills. Any spilled liquid may bleach surfaces it comes into contact with.
- If the carpets have been washed, make sure they are completely dry before use. Moisture in the cabin will extend the presence of chlorine dioxide molecules.

Money-Back Guarantee

- Retain the foil packet and visit our FAQ page on www.BiocideSystems.com.

Contact Us

1-877-RX BIOCIDE / 1-877-792-4624

www.BiocideSystems.com

Proudly Made in the USA!