

2K Wired Video Doorbell with Wi-Fi chime

DH-VDKP01-WG





Series Overview

The WiFi Video Doorbell is a new addition to the Dahua Wireless series. It not only delivers 2K high-resolution imagery, but also captures more details than conventional fixed lenses through its ultra-wide fisheye lens. The doorbell features passive IR motion detection and transmits videos and audios to mobile devices, allowing you to remotely perform visual confirmation and communicate with visitors. Furthermore, it is compatible with 2.4 GHz Wi-Fi 6 networks, enhancing its connectivity options.

The Wireless Chime is an indoor device that chimes when your videodoorbell is pressed. Through the DMSS app, the ringtones and volumecan be customized to your ideal settings and it can be paired with either of the two models of Dahua video doorbells. Highly convenient, it can be bound to multiple video doorbells at the same time, so you an place multiple Wireless Chime around your home to always hearwhenever someone presses your video doorbell. Whether you're in the kitchen, office or bedroom, you'll never miss a thing if your phone is out of reach.



4MP

Clear images with sharp details



H.265

Advanced H.265 compression technology



Supports Micro SD Card

Low-cost storage



One-click Proactive Call

Proactive bidirectional call anytime, anywhere



Al Human Detection

Focuses on what matters and reduces false alarms



Al Vehicle Detection

Focuses on what matters and reduces false alarms



Abnormal Sound Alarm

Detects abnormal sounds and sends alarms in time



Wi-Fi 6

Seamless integration of speed and anti-interference



Bluetooth Pairing

Fast pairing with Bluetooth



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.













Specifications Doorbell

Camera

Image Sensor 1/3" CMOS

Max. Resolution 2560 (H) × 1440 (V)

Illumination Distance Up to 10 m (32.81 ft) (IR)

Illuminator Number 2 (IR LED) Fixed-focal Lens Type Focal Length 2.3 mm Max. Aperture F2.2

Field of View H: 120°; V: 66°; D: 143°

Intelligence

Human Detection Yes Vehicle Detection Yes

Audio and Video

Video Compression H.265; H.264; H.264H; H.264B

Main stream: 2560 × 1440@(1–15 fps)/920 × 1080@(1–15 fps)/1280 × 720@(1–15 fps) Sub stream: 640 × 360@(1–15 fps)

Video Frame Rate *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

H.264: 32 kbps-8192 kbps; Video Bit Rate H.265: 32 kbps-8192 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR

Motion Detection OFF/ON (4 areas, rectangular)

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic Built-in Speaker Yes, built-in speaker Audio Compression G.711a; G.711Mu; PCM

Network

IEEE 802.11b/g/n/ax 2.4000-2.4835 GHz, 2.4 G, Wi-Fi

EIRP≤20 dBm

Wi-Fi Pairing Bluetooth pairing

Micro SD card (support max. 256 GB) Storage

Management Software DMSS

Mobile Client Android;iOS

General

CE-LVD: EN62368-1;

CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; Certifications

CE-RED: Radio Equipment Directive 2014/53/EU

USB (5 VDC±5%, 2 A) or binding post power supply (10–24 VDC/14–24 VAC, 1.0 A). Power Supply

Power Consumption

Basic: 1.7 W (5 VDC); 2.1 W (10–24 VDC); 2.2 W (14–24VAC, active power) Max.: 5.3 W (5 VDC); 6.8 W (10–24 VDC); 6.8 W (14–24 VAC, active power) (IR + white light + alarm on)

-20 °C to +55 °C (-4 °F to +131 °F)

Operating Temperature

Operating Humidity ≤95% (RH), non-condensing

Protection

Camera Button One-click Call Button

Casing Material Plastic

135 mm \times 45 mm \times 24.2 mm (5.31" \times 1.77" \times 0.95") (L \times W \times H) **Product Dimensions**

Net Weight 0.11 kg (0.24 lb)



Specifications Chime

Audio

Built-in Speaker Built-in Speaker

Network

Management Software DMSS

IEEE 802.11b/g/n/ax 2.4000-2.4835 GHz, 2.4 G, Wi-Fi

EIRP≤20 dBm

Network Update

Power

Power Supply 100-240 VAC 50/60 Hz

Power Consumption

Structure

Appearance Color White Plastic + Grey Cloth Net Weight 0.1 kg (0.22 lb) Gross Weight 0.2 kg (0.44 lb)

Plastic + Cloth Bare machine: 96 mm \times 50 mm \times 30.3 mm (3.78" \times 1.97"× 1.19") (L \times W \times H) **Product Dimensions**

187 mm × 81 mm × 57 mm (7.36" × 3.19" × 2.24")

 $(L \times W \times H)$

Packaging Dimensions **Environment**

Casing Material

Operating Temperature -10 °C to +45 °C (14 °F to +113 °F) 20%-95% (RH), non-condensing

Operating Humidity

Certification

CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive Certifications

2014/30/EU;

CE-RED: Radio Equipment Directive 2014/53/EU

What's in the box



Tools: Installation Kit × 1

 $\mathsf{Pin} \times 1$

Mounting Bracket \times 1

Quick Start Guide × 2 Legal and regulation

QR Code × 2

Documents:

Power:

Power Cable × 1

♣.EU×1



