



• Picture is for reference only

# The Tower 250

User's Manual  
Benutzerhandbuch  
Mode d'emploi  
Manual del usuario  
Manuale dell'utente  
Manual do Utilizador

安裝說明書  
用戶手冊  
ユーザーズマニュアル  
Руководство пользователя  
kullanıcı elkitabı  
(EEE Yönetmeliğine Uygundur)  
คู่มือการใช้



© 2024 Thermaltake Technology Co., Ltd. All Rights Reserved. 2024.09  
All other registered trademarks belong to their respective companies. [www.thermaltake.com](http://www.thermaltake.com)



## TT Premium



### TT Premium

To continue achieving the corporate mission of delivering the perfect user experience, Thermaltake developed "TT Premium" with the essence of combining supreme quality products with a new logo design. TT Premium is far more than just a guarantee of quality. Behind the name, it represents the passion in DIY, Modding and Thermaltake's desire to be the most innovative brand in the PC hardware market. To satisfy the demand of the high-end PC users, TT Premium follows its core values of Excellent Quality, Unique Design, Diverse Combinations and Boundless Creativity to provide a high performance PC product for every enthusiast. <http://ttpremium.com>

## Tt LCS-Liquid Cooling Support Certification



Tt LCS Certified is a Thermaltake exclusive certification applied to only products that pass the design and hardcore enthusiasts standards that a true LCS chassis should be held to. The Tt LCS certification was created so that we at Thermaltake can designate to all power users which chassis have been tested to be best compatible with extreme liquid cooling configurations to ensure you get the best performance from the best features and fitment.

## Join Tt Community To Receive Benefits



Dear Valued Customer,  
Thank you for choosing Thermaltake.  
As a new user we value your thoughts and opinions and your feedback is important to us. We at Thermaltake would like to use this opportunity to invite you to join our Community Forums. Register today to start enjoying the full benefits of our community.



Benefits of being a member:

- Quick and responsive user support
- Receive help and advice with new builds
- Keep up to date with new product releases
- Share your thoughts and builds with the community
- Enter monthly contests and giveaways

**Brand official website**  
<http://www.thermaltake.com/>

**Global Facebook**  
<https://www.facebook.com/ThermaltakeInc>

**Taiwan Facebook**  
<http://www.facebook.com/ThermaltakeTW>

**Global community forums**  
<http://community.thermaltake.com>

# CONTENTS



## Chapter 1. Product Introduction

|     |                          |    |
|-----|--------------------------|----|
| 1.0 | Specification .....      | 01 |
| 1.1 | Accessory .....          | 02 |
| 1.2 | Warning and Notice ..... | 03 |


## Chapter 2. Installation Guide

|     |                                            |    |
|-----|--------------------------------------------|----|
| 2.0 | Remove Panels .....                        | 06 |
| 2.1 | Power Supply Unit (PSU) Installation ..... | 07 |
| 2.2 | Motherboard Installation .....             | 09 |
| 2.3 | 3.5" & 2.5" HDD Installation .....         | 10 |
| 2.4 | VGA Card Installation .....                | 12 |
| 2.5 | Air Cooling Installation .....             | 13 |
| 2.6 | AIO Liquid Cooling Installation .....      | 14 |
| 2.7 | I/O Connection .....                       | 15 |
| 2.8 | Remove Filters .....                       | 16 |


|                   |                                                                               |                                                           |                        |
|-------------------|-------------------------------------------------------------------------------|-----------------------------------------------------------|------------------------|
| Case Type         | Mini Tower                                                                    |                                                           |                        |
| Dimension (H*W*D) | 506 x 300 x 281 mm (19.9 x 11.8 x 11.5 inch)                                  |                                                           |                        |
| Side Panel        | Tempered Glass x 3                                                            |                                                           |                        |
| Material          | SPCC                                                                          |                                                           |                        |
| Cooling System    | <b>Top (exhaust):</b><br>120 x 120 x 25 mm CT120 fan (2000 rpm, 25.8 dBA) x 2 |                                                           |                        |
| Drive Bays        | 1 x 3.5" or 2 x 2.5"                                                          |                                                           |                        |
| Expansion Slots   | 3                                                                             |                                                           |                        |
| Motherboards      | 6.7" x 6.7" (Mini ITX)                                                        |                                                           |                        |
| I/O Port          | USB 3.2 (Gen 2) Type-C x 1, USB 3.0 x 2, HD Audio x 1                         |                                                           |                        |
| PSU               | Standard SFX or ATX PSU (optional)                                            |                                                           |                        |
| Fan Support       | Top                                                                           | 2 x 120 mm, 1 x 120 mm                                    |                        |
|                   | Right Side                                                                    | 3 x 120 mm, 2 x 120 mm, 1 x 120 mm                        | 2 x 140 mm, 1 x 140 mm |
|                   | Rear                                                                          | 2 x 120 mm, 1 x 120 mm                                    | 2 x 140 mm, 1 x 140 mm |
|                   | Power Cover                                                                   | 1 x 120 mm                                                | 1 x 140 mm             |
| Radiator Support  | Right Side (AIO)                                                              | 1 x 360 mm, 1 x 240 mm, 1 x 120 mm                        | 1 x 280 mm, 1 x 140 mm |
| Clearance         | CPU cooler height limitation                                                  | 210 mm                                                    |                        |
|                   | VGA length limitation                                                         | 245 mm (With power cover)<br>360 mm (Without power cover) |                        |
|                   | PSU length limitation                                                         | 200 mm                                                    |                        |

| Figure                                                                                | Part Name                | Q'ty | Used For                    |
|---------------------------------------------------------------------------------------|--------------------------|------|-----------------------------|
|    | Screw #6-32 x 6 mm       | 4    | Power Supply                |
|    | Screw #6-32 x 6 mm       | 14   | Motherboard / 3.5" HDD      |
|    | Screw M3 x 5 mm          | 8    | 2.5" SSD / HDD              |
|    | Screw #6-32 x 29 mm      | 4    | Case Fan on the Power Cover |
|    | Screw T5 x 10 mm         | 8    | Case Fan                    |
|    | Stand-off #6-32 x 6.5 mm | 3    | Motherboard                 |
|    | Nut setter               | 1    | Motherboard Stand-off       |
|    | Zip Ties                 | 10   | Cable Management            |
|    | Buzzer                   | 1    | Motherboard Alarm           |
|    | Side Plate Clip          | 6    | Side Panel                  |
|    | Bottom Front Panel       | 1    | LCD Display                 |
|  | ATX PSU Bracket          | 1    | ATX PSU                     |
|  | Velcro-1 meter           | 1    | Cable Management            |


## Chassis dimension




## Motherboard Compatibility: ITX




## CPU cooler max height: 210mm





## PSU max length: 200mm








VGA max length: 245 mm (With Power Cover)  
360 mm (Without Power Cover)




Radiator max length: 400 mm




**SFX****ATX**




1




3.5" HDD








2






SSD / 2.5" HDD







Motherboard Header Diagram

