

60cm Series 9 Contemporary Warming Drawer

Series 9 | Contemporary



Serve meals hot and directly from a pre-heated plate thanks to our panel-ready, warming drawer.

- Integrates with surrounding cabinetry for a seamless look
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	290 mm
Width	596 mm
Depth	567 mm

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer comes with the option of a stylish black glass panel or elegant grey glass panel, for seamless pairing with our Minimal or Contemporary style ovens.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof for proofing dough, Dehydrate for drying foods such as meat, fruit and herbs and Slow Cook, ideal for finishing of seared meats, casseroles, stews and braises.

Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking. You can even rest meat after a traditional roast in the oven and proof dough for bread making and pizza.

Added Convenience

Handle-free, push-to-open with intuitive touch controls, our warming drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Easy To Clean

Cleaning and care of the warming drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Safe And Sound

With automatic switch-off and delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

Sized To Suit

With enough room to gently heat 16 place settings, 20 cappuccino cups or 42 espresso cups, our tall warming drawer is an ideal kitchen companion.

SPECIFICATIONS

Accessories (included)

Wire shelf	1
------------	---

Capacity

Accessory rack maximum allowable weight	19kg
Cappuccino cups	20
Espresso cups	42
Maximum allowable weight	25 kg
Place settings	16
Usable depth	408 mm
Usable height	237 mm
Usable width	535 mm

Cleaning

Easy clean smooth-glass base	•
------------------------------	---

Controls

Audio feedback	•
Automatic pre-set temperatures	•

Automatic timers	30', 45', 1h, 2h, 4h, 6h	Supply frequency	50 Hz	Where applicable:
Delayed start	•	Supply voltage	220 V	
Electronic capacitive touch controls	•			
On/Off indicator	•	Product dimensions		All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.
Pre-set heating functions	•	Adjustable front door panel to align with surrounding cabinetry	•	
Push-to-open drawer	•	Depth	567 mm	
Standby mode	•	Height	290 mm	
		Width	596 mm	
Functions				Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.
Cups	•	Safety		
Dehydrate	•	Automatic turn off after 12 hours	•	
Number of functions	6	Full extension slides	•	
Plates	•			
Rapid proof	•			 A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1800 625174 Wwww.fisherpaykel.com
Slow cook	•			
Warm	•			
		SKU	84229	
Performance		The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020		
Heated glass base and fan	•	Other product downloads available at fisherpaykel.com		
Low temperature cooking	•			
Temperature levels	6			
Temperature range	35°C-85°C	↓	2D-DWG Warming Drawer	
		↓	2D-DXF Warming Drawer	
		↓	Installation Guide Warming Drawer	
		↓	User Guide Warming Drawer	
Power requirements				
Amperage	10 A			
Power cord length	1800 mm			
Power outlet	3-prong grounding-type			