

OWNER'S MANUAL F63 Treadmill

Please carefully read this entire manual before operating your new treadmill.

TABLE OF **CONTENTS**

Product Registration	1
Important Safety Instructions	2
Important Electrical Information	3
Important Operation Instructions	4
Assembly instructions	9
Folding Instructions	14
Transport Instructions	14
Operation of Your New Treadmill	15
Bluetooth® Connectivity	19
Charging Function	20
Programmable Features	21
General Maintenance	28
Service Checklist - Diagnosis Guide	31
Manufacturer's Limited Warranty	33



WARNING: This product can expose you to chemicals including Toluene and Acrylamide which are known to the State of California to cause Cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Before returning your Sole product to any retailer, or if you require any assistance with assembly or technical support please call us first for assistance at 866-780-7653. Thank you for your Sole purchase.



CONGRATULATIONS ON YOUR NEW TREADMILL AND WELCOME TO THE SOLE FAMILY!

Thank you for your purchase of this quality treadmill from **SOLE**. Your new treadmill has been manufactured by one of the leading fitness manufacturers in the world and is backed by one of the most comprehensive warranties available. **SOLE** will do all we can to make your ownership experience as pleasant as possible for many years to come.

If there is a question as to where to obtain service, contact our service department at 866-780-7653.

Please take a moment at this time to record below the name of the dealer, their telephone number, and the date of purchase for easy contact in the future. We appreciate your confidence in **SOLE** and we will always remember that you are the reason that we are in business. Please complete and mail your registration card today and enjoy your new treadmill.

Yours in Health, **SOLE** Fitness

Name of Dealer	
Telephone Number of Dealer	
Purchase Date	

PRODUCT REGISTRATION

RECORD YOUR SERIAL NUMBER.

Please record the Serial Number of this fitness product in the space provided below.

Serial Number



REGISTER YOUR PURCHASE

The self-addressed product registration card must be completed in full and returned to **SOLE**. You can also go to **www.soletreadmills.com** under the support tab to register online.

IMPORTANT **SAFETY INSTRUCTIONS**

WARNING - Read all instructions before using this appliance.

DANGER - To reduce the risk of electric shock disconnect your SOLE treadmill from the electrical outlet prior to cleaning and/or service work.

WARNING - To reduce the risk of burns, fire, electric shock, or injury to persons, install the treadmill on a flat level surface with access to a 110-volt, 15-amp grounded outlet with only the treadmill plugged into the circuit.

DO NOT USE AN EXTENSION CORD UNLESS IT IS A 14AWG OR BETTER, WITH ONLY ONE OUTLET ON THE END: DO NOT ATTEMPTTO DISABLETHE GROUNDED PLUG BY USING IMPROPER ADAPTERS, OR IN ANY WAY MODIFY THE CORD SET.

A serious shock or fire hazard may result along with computer malfunctions. See Grounding Instructions, page 3.1

- Do not operate treadmill on deeply padded, plush or shag carpet. Damage to both carpet and treadmill may result.
- Do not block the rear of the treadmill. Provide a minimum of 3 1/2 feet clearance between the rear of the treadmill and any fixed object.
- Keep children under the age of 13 away from this machine. There are obvious pinch points
 and other caution areas that can cause harm.
- Keep hands away from all moving parts.
- Never operate the treadmill if it has a damaged cord or plug. If the treadmill is not working properly, call your dealer.
- Keep the cord away from heated surfaces.
- Do not operate where aerosol spray products are being used or where oxygen is being administered. Sparks from the motor may ignite a highly gaseous environment.
- Never drop or insert any object into any openings.
- Do not use outdoors.
- To disconnect, turn all controls to the off position, remove tether cord, then remove the plug from the outlet.
- Do not attempt to use your treadmill for any purpose other than for the purpose it is intended.
- The pulse sensors are not medical devices. Various factors, including the user's movement, may affect the accuracy of heart rate readings. The pulse sensors are intended only as exercise aids in determining heart rate trends in general.
- Use handrails provided: they are for your safety.
- Wear proper shoes. High heels, dress shoes, sandals or bare feet are not suitable for use on your treadmill. Quality athletic shoes are recommended to avoid leg fatigue.
- This appliance is not intended for use by persons with reduced physical, sensory or mental
 capabilities, or lack of experience and knowledge, unless they have been given supervision
 or instruction concerning use of the appliance by a person responsible for their safety.

Remove tether cord after use to prevent unauthorized treadmill operation.

SAVETHESE INSTRUCTIONS - THINK SAFETYI

IMPORTANT ELECTRICAL INSTRUCTIONS

WARNINGI

Route the power cord away from any moving part of the treadmill including the elevation mechanism and transport wheels.

NEVER remove any cover without first disconnecting AC power.

If voltage varies by ten percent (10%) or more, the performance of your treadmill may be affected. Such conditions are not covered under your warranty. If you suspect the voltage is low, contact your local power company or a licensed electrician for proper testing.

NEVER expose this treadmill to rain or moisture. This product is NOT designed for use outdoors, near a pool or spa, or in any other high humidity environment. The maximum operating temperature specification is 40 degrees C, and humidity is 95% non-condensing (no water drops forming on surfaces).

Circuit Breakers: Avoid AFCI/GFCI circuit breakers if possible. These breakers may trip occasionally during exercise because of the high inrush currents of the treadmill drive electronics and motor. This is an issue that affects all treadmill brands.

New laws in your area may require these breakers. If you do have these breakers and outlets in your home, and are experiencing nuisance tripping, you should check if there are any other devices plugged into the same circuit. Some examples of devices that may also cause tripping are fluorescent lights with electronic ballasts, coffee maker, space heater, hair drier. Optimally the treadmill should be the only device plugged into the circuit.

Our treadmills have surge suppressors built in to help avoid nuisance tripping. We have tested several AFCI/GFCI breakers and outlets with our products. Brands we have tested are: Eaton (Cutler Hammer Series). Leviton (Smart lock pro) and Schneider Electric (Canadian home series). These breakers do not trip in our testing, when connected to our treadmills, as long as no other devices are plugged into the same circuit.


GROUNDING INSTRUCTIONS

This product must be grounded. If the treadmill should malfunction or breakdown, grounding provides a path of least resistance for electric current, reducing the risk of electric shock. This product is equipped with a cord having an equipment-grounding plug. The plug must be plugged into an appropriate outlet that is properly installed and grounded in accordance with all local codes and ordinances.

DANGER- Improper connection of the equipment-grounding conductor can result in a risk of electric shock. Check with a qualified electrician or serviceman if you are in doubt as to whether the product is properly grounded. Do not modify the plug provided with the product if it will not fit the outlet; have a proper outlet installed by a qualified electrician.

This product is for use on a nominal 110-volt circuit, and has a grounding plug that looks like the plug illustrated below. A temporary adapter that looks like the adapter illustrated below may be used to connect this plug to a 2-pole receptacle as shown below if a properly grounded outlet is not available. The temporary adapter should be used only until a properly grounded outlet, (shown below) can be installed by a qualified electrician. The green colored rigid ear lug, or the like,

extending from the adapter, must be connected to a permanent ground such as a properly grounded outlet box cover. Whenever the adapter is used, it must be held in place by a metal screw.



IMPORTANT OPERATION INSTRUCTIONS

- **NEVER** operate this treadmill without reading and completely understanding the results of any operational change you request from the computer.
- Understand that changes in speed and incline do not occur immediately. Set your desired speed on the computer console and release the adjustment key. The computer will obey the command gradually.
- NEVER use your treadmill during an electrical storm. Surges may occur in your household power supply that could damage treadmill components. Unplug the treadmill during an electrical storm as a precaution.
- Use caution while participating in other activities while walking on your treadmill; such as watching television, reading, etc. These distractions may cause you to lose balance or stray from walking in the center of the belt; which may result in serious injury.
- **NEVER** mount or dismount the treadmill while the belt is moving. **SOLE** treadmills start at a very low speed and it is unnecessary to straddle the belt during start up. Simply standing on the belt during slow acceleration is proper after you have learned to operate the unit.
- Always hold on to a handrail or hand bar while making control changes (incline, speed, etc.).
- Do not use excessive pressure on console control keys. They are precision set to function
 properly with little finger pressure. Pushing harder is not going to make the unit go faster or
 slower. If you feel the buttons are not functioning properly with normal pressure contact
 your SOLE dealer.

IMPORTANT SAFETY INSTRUCTIONS

A safety tether cord is provided with this unit and should be used at all times. It is for your safety should you fall or move too far back on the tread-belt. Pulling this safety tether cord will stop tread-belt movement.

To Use:

- Place the safety key into position on the console control head. Your treadmill will not start and operate without this. Removing the safety key also secures the treadmill from unauthorized use.
- 2. Fasten the plastic clip onto your clothing securely to assure good holding power.
 Note: The clip should be attached securely to make certain it does not come off. Be familiar with its function and limitations. The treadmill will stop, depending on speed, with a one to two step coast anytime the safety key is pulled off the console. Use the red Stop switch in normal operation.
- If the console displays "Safety key removed, machine stopped. Please replace the key to Operate", put the Safety key back to continue using the treadmill.

IMPORTANT SAFETY INSTRUCTIONS

READ BEFORE UNPACKING YOUR FOLDING TREADMILL

Serious injury could occur if this folding treadmill is not unpacked properly.

There is a deck restraint SHIPPING strap installed around the treadmill base that prevent the treadmill from unfolding accidentally during shipping. If this strap is not removed properly the treadmill could spring open unexpectedly and cause injury if someone is standing near the treadmill when the strap is removed.

To ensure your personal safety during removal of the shipping strap please make sure the treadmill is positioned flat on the ground, in the orientation it would be in if you were using the treadmill. Do not tilt the treadmill up on its side while removing the shipping strap: this could cause the treadmill's folding mechanism to spring open. To remove the strap, pull up on the strap and cut it with a pair of scissors.

There is a safety pin locked on the treadmill base that prevents the treadmill from unfolding accidentally during shipping. This safety pin has to be removed before powering on or using the incline function to avoid any damages to the machine. When removing the safety pin, pull it away from the treadmill base completely.


PREVENTATIVE MAINTENANCE CHART

Vacuum Under Motor Cover & Check Wiring (Every Other Month)	Clean & Inspect Deck for Lubrication (Every Other Month)	Lubricate Deck (Every 90 hours or sooner if dry)	Inspect Belt Tracking (Monthly) Adjust if necessary	Date

5.

F63 ASSEMBLY PACK CHECKLIST

HARDWARE STEP 2




#99. 5/16" × 3/4" Hex Head Bolt (8 pcs):



#100. Ø5/16" × Ø18 × 1.5T Flat Washer (8 pcs)

3

HARDWARE STEP 3




#166. 3/8" × 1-3/4" Button Head Socket Bolt (4 pcs)



#188. Ø10 x 1.5T Split Washer (4 pcs)

4

HARDWARE **step 4**



#168, 3.5 × 16m/m Sheet Metal Screw (2 pcs)


5

HARDWARE STEP 5



#167. M5 × 30m/m Phillips Head Screw (4 pcs) 6


HARDWARE STEP 6



#125. 5/16" × 3/4" Button Head Socket Bolt (4 pcs)

7


HARDWARE STEP 7



#168. 3.5 × 16 m/m Sheet Metal Screw (6 pcs).

8

HARDWARE **STEP 8**



#168. 3.5 × 16m/m Sheet Metal Screw (4 pcs)


9

HARDWARE STEP9



#126. M5 × 15m/m Phillips Head Screw (4 pcs)


ASSEMBLY TOOLS



F63 ASSEMBLY INSTRUCTIONS

1


ASSEMBLY STEP 1



 Remove the treadmill from the carton and position it aside on a smooth, leveled floor. The rear should be at least 3' from any wall. You must remove the plastic wrap and Styrofoam from beneath the unit before removing the Velcro belt. Tilting the unit sideways after removing the belt may cause the unit to fold and bounce upwards. This can cause serious injury.

2

ASSEMBLY STEP 2



HARDWARE STEP 2


#99.5/16" × 3/4" Hex Head Boit (8 ocs) #100.05/16" × 8/18 × 1.5T Flat Washer (8 ocs)

- 1. You may need assistance holding the Uprights for this step.
- Connect the Computer Cable (Middle) (117) to the Computer Cable (Lower) (118) then insert Right and Left Uprights (4) and (5) into the Frame Base (2) and use 13m/m Wrench (90) to tighten 8 pcs of Hex Head Bolts (99) and 8pcs of Flat Washers (100). Do not tighten the bolts completely until Step 6 is finished.

Before attaching the hardware in Step 3, make sure the cables you just connected don't get pinched in between the steel tubing. If they do, this may cause issues that prevent the treadmill from operating properly.

3

ASSEMBLY STEP 3



HARDWARE STEP 3

#166.3/8" × 1-3/4" 8.tton Head Socket Bolt (1 ocs: #188.010 × 1.5T Split Washer (1 ocs:


To complete this step, it is recommended that you find something to rest the console on at an appropriate height or have someone hold the console while you connect the cables.

- Connect the Computer Cable (Middle) (117) to the Computer Cable (Upper) (116) then insert.
- Console Assembly (Bottom) (22) into the Right and Left Uprights (4) and (5) and use M6 L Allen Wrench (103) to tighten 4 pcs of Button Head Socket Bolt (166) and 4 pcs of Split Washer (188). Do not tighten the bolts completely until Step 6 is finished.

Before attaching the hardware in Step 4, make sure the cables you just connected don't get pinched in between the steel tubing. If they do, this may cause issues that prevent the treadmill from operating properly.

4

ASSEMBLY STEP 4



 Install Fan Plate Assembly (24) on the Console Assembly (Bottom) (22) and use M5 Allen Wrench Head Screw Wrench (102) to tighten 2 pcs of Sheet Metal Screw(168).

HARDWARE STEP 4

#168.3.5 × 16m/m Sheet Metal Screw (2 pcs) 5

ASSEMBLY STEP 5

22

HARDWARE STEP 5

#167. Mb × 30m/m Phillips Head Screw (1 ocs)


- Connect the Computer Cable (Upper) (21-09) to the Computer Cable (Lower) (22-16), and connect the Computer Cable (Upper) (21-10) to the Computer Cable (Lower) (22-17), and connect the Computer Cable (Upper) (21-11) to the Computer Cable (Lower) (22-18), and connect the Computer Cable (21-17) to the Computer Cable (Upper) (116).
- Place Console Assembly (Top) (21) to Console Assembly (Bottom) (22) and use Combination M5 Allen Wrench & Phillips Head Screw Driver (102) to tighten 4 pcs of Phillips Head Screw (167).

Before attaching the hardware in Step 6, make sure the cables you just connected don't get pinched in between the steel tubing. If they do, this may cause issues that prevent the treadmill from operating properly.

102

б

ASSEMBLY STEP 6



HARDWARE STEP 6


#125.5/16" x 3/4" Sutton Head Socket Bolt (1 ocs)

 Install Handrail Support (9) between Left and Right Uprights (5) and (4) and use Combination M5 Allen Wrench & Phillips Head Screw Driver (102) to tighten 4 pcs of Button Head Socket Bolts (125).

NOTE: Please Tighten All Screws After All Components Assembly Complete.

7

ASSEMBLY STEP 7




 Install Console Mast Cover Outer (L) (119), Console Mast Cover Inner (L) (120), Console Mast Cover Outer (R) (121) and Console Mast Cover Inner (R) (122) in Left and Right Uprights (5) and (4) and use Combination M5 Allen Wrench & Phillips Head Screw Driver (102) to tighten 6 pcs of Sheet Metal Screw (168).

HARDWARE STEP 7

#168. 3.5 × 16m/m Sheet Metal Screw % ocsi 8

ASSEMBLY STEP 8




HARDWARE STEP 8

#168.3.5 × 16m/m Sheet Metal Screw 21 ocs:

- Insert Tablet Holder (177) into the Console Assembly (Top) (21)
 and use Combination M5 Allen Wrench & Phillips Head Screw
 Driver (102) to tighten 4 pcs of Sheet Metal Screw (168).
- 2. Install Handrail Support (9) on Beverage Holder (109).

9

ASSEMBLY STEP 9




Install Frame Base Cover left (38) and right (39) in Left and Right Uprights (5) and (4) and use Combination M5 Allen Wrench & Phillips Head Screw Driver (102) to tighten 4 pcs of

Phillips Head Screw (126) into Frame Base (2).

HARDWARE STEP 9

#126. Mb × 15m/m Phillips Head Screw PLocs: NOTE: Please pull Locking Pin Assembly (157) out and insert End Cap (115) into while you use the machine.



FOLDING **INSTRUCTIONS**


Do not attempt to move the unit unless it is in the folded and locked position. Be sure the power cord is secured to avoid possible damage. Use both handrails to maneuver the unit to the desired position.

■ TO FOLD THE TREADMILL

Make certain that the treadmill is at minimum incline. Lift the treadmill's running deck until it is secured by the cylinder in the center back of the base.

■ TO UNFOLD THE TREADMILL

Using your foot firmly push against the cylinder to release the folding mechanism.



TRANSPORTATION INSTRUCTIONS

The treadmill is equipped with transport wheels that are engaged when the treadmill is folded. After folding simply roll the treadmill away.

OPERATION OF YOUR TREADMILL

GETTING FAMILIAR WITH THE CONTROL PANEL



Power the treadmill on by plugging it into an appropriate wall outlet, then turn on the power switch located at the front of the treadmill below the motor hood. Ensure that the **Safety Key** is installed, as the treadmill will not power on without it.



When the power is turned on, the message window displays the current version of the software. Then the **Time** and **Pace Windows** will display Odometer readings for a short time. **Time Window** will show how many hours the treadmill has been in use and the **Pace Window** will show how many miles (or Kilometers if the treadmill is set to metric readings) the treadmill has gone. The treadmill will then enter idle mode, which is the starting point for operation.

START OPERATION

- 1. Attach the Safety Key to wake the display up, if it's not already on.
- Press the Start key to begin belt movement. Adjust to the desired speed using the Speed ▲/▼
 keys on either the console. You may also use the speed keys 2, 3, 4, 5, 7, 9 or 12 to adjust the
 speed.
- 3. To slow down the tread-belt, press and hold the **Speed** ▼ key on the console to the desired speed. You may also press the speed adjust keys, 2 through 12.
- 4. To stop the tread-belt, press Stop key or pull away Safety Key.







PAUSE/STOP/RESET FEATURE

- 1. When the treadmill is running, the pause feature may be utilized by pressing the red Stop key once. This will slowly decelerate the tread-belt to a stop. The incline will go to zero percent. The Time, Distance and Calorie readings will hold while the unit is in the pause mode. After 5 minutes the display will reset and return to the start up screen.
- To resume your exercise, while in Pause mode, press the Start key. The speed and incline will return to their previous settings.
 - Pause is executed when the **Stop** button is pressed once. If the **Stop** button is pressed for the second time, the program will end and a workout summary will be displayed. If the **Stop** button is pressed for the third time, the console will return to the idle mode (start up) screen. If the **Stop** button is held down for more than 3 seconds, the console will reset.

INCLINE FEATURE

- Incline may be adjusted anytime after belt movement.
- Press and hold the Incline ▲/▼ keys on the console to achieve your desired level of effort.
 You may also choose a more rapid increase / decrease by selecting desired key, 1, 3, 5, 7, 9, 12 and 15, on the console (incline).
- The Incline Window display will indicate incline position as adjustments are made.





DOT MATRIX CENTER DISPLAY

Eighteen columns of dots – each 8 units high - indicate each segment of a workout for the F63 and eighteen columns of dots – each 8 units high - indicate each segment of a workout for the . The dots are only to show an approximate level of effort in speed or incline. They do not necessarily indicate a specific value - only an approximate percent to compare levels of intensity. In operation, the speed/incline dot matrix window will build a profile "picture" as values are changed during a workout. When the word "Speed" is lit above the dot matrix, it indicates that the Speed profile is being displayed. When the word "Incline" is lit above the dot matrix, it indicates the Incline profile is being displayed.



You may change the Dot Matrix profile view between Speed and Incline by pressing the Enter button. After pressing Enter to view the two profiles, pressing it for the third time will automatically alternate the Speed and Incline displays, showing each one for five seconds.

MESSAGE WINDOW DISPLAY

The Message Window will initially display Program Name. Each time the Display button is pressed, the next set of information will appear. The order of information displayed will be: Program, Laps, Verticle, Segment Time, Max Speed (in mph), and Data Scan mode. In Data Scan mode, the displayed information will change every 4 seconds in the Message Window.

1/4 MILETRACK

The 1/4 mile track is displayed around the dot matrix window. The flashing dot indicates your progress. The number of laps you complete are accumulated in the lap counter, which is viewed in the **Message Window**.

CALORIE DISPLAY

Displays the cumulative calories burned at any given time during your workout.

Nate: This is only a rough guide used for comparison of different exercise sessions, which cannot be used for medical purposes.

BACKLIGHT BRIGHTNESS ADJUSTMENT FUNCTION

LCD screen brightness adjustment operation mode:

- In idle mode, press and hold the DISPLAY button for 5 seconds to enter the brightness adjustment function.
- 2. The LCD does not display all of them, only displays the moving string "BRIGHTNESS" LEVEL" in the message bar, and displays the numbers 1~10 in Dot matrix.
- Press SPEED+/- or INCLINE+/- button to adjust the brightness, adjust the number range 1~10.

17

- 4. Press ENTER to confirm and leave back to the IDLE MODE display.
- Factory default: 10

PULSE FEATURE

The **Pulse (Heart Rate) Window** will display your current heart rate in beats per minute during the workout. You must use both stainless steel sensors on the front cross bar to display your pulse or wear the wireless chest strap. The pulse value will display anytime the upper display is receiving a pulse signal.



TURNING OFFTREADMILL

- The display will automatically turn off, by going into sleep, after 15 minutes of inactivity when in the Pause / Stop mode. Almost all power for the treadmill will be off except for some circuits that are needed to detect if any key is pressed, indicating the console should "wake up". When the console is "asleep" the treadmill draws very little power, for about as much as a television turned off.
- 2. Removing the **Safety Key** is similar to entering "sleep" mode. Turning off the main power switch in the front of the treadmill will completely remove any power.

ATTENTION

SLEEP MODE Your console comes in "Sleep mode" with different features by choice:

ON The unit goes energy-saving state after 15 minutes of inactivity.

OFF The console will stay lit while the power is on.

On LCD displays, press and hold the Stop, Enter, and Display keys for 5 seconds to turn ON or OFF the Sleep mode.

New Sole+ App to be used in conjunction with select Apple & Android devices!

In order to help you achieve your exercise goals, your new exercise machine comes equipped with a Bluetooth* transceiver that will allow it to interact with selected phones or tablet computers via the Sole+ App.

Just download the free Sole + App from the Apple Store or Google Play, and then follow the instructions in the App to sync with your exercise machine.

You can press the "DISPLAY" button from the APP to view the display of the current workout data. When your exercise is complete pressed in the APP "END & SAVE WORKOUT" to store the workout data.

The Sole + App also allows you to sync your workout data with one of many fitness cloud sites we support: Apple Health, Google Fit, Strava, MapMyFitness or Fitbit, with more to come.

Syncing the App with your exercise machine:

- 1. Download the App by scanning the QR code on the right.
- Open the App on your device (phone or tablet) and make sure Bluetooth" is enabled on your device(phone or tablet).
- In the App click the Bluetooth icon to search for your Sole + equipment (shown right).
- 4. Under the Bluetooth scan result list, select the machine for connect. When the App and equipment are synced, the Bluetooth" icon on the equipment's console display will light up. Click "DISPLAY", you may now start using your Sole + App.
- 5. When your exercise is complete pressed in the APP "END & SAVE WORKOUT" to store the workout data, and you will be prompted to sync your data with each available fitness cloud site. Please note you will have to download the applicable compatible fitness App. such as Apple Health, Google Fit, Strava, MapMyFitness or Fitbit, etc., in order for the icon to be active and available.

Note: Your device will need to be running on a minimum operating system of IOS 13.1 or Android 8.0 for the Sole + App to operate properly.

The exercise equipment can also play music wirelessly via Bluetooth. Turn on your mobile phone or tablet's Bluetooth function. Search for the name "Bt-speaker" in your device's Bluetooth menu. Tap to connect. Now your device can transmit music to the exercise equipment.

The exercise equipment's Bluetooth device (BLE 5.0) can also be connected to the Bluetooth wireless heart rate chest strap transmitter (BLE 5.0). The chest strap transmitter can receive signals even when the App is already in use. You can wear the Bluetooth wireless heart rate chest strap first then commence connection. While in connection, the console will show heart rate value via Bluetooth.

The icon lights up when connecting to a Bluetooth heart rate chest strap successfully and the heart rate will then be displayed. The icon will be off if the Bluetooth heart rate chest strap is disconnected.



Charge Portable Devices with USB port

USB Port Charging function:

Charge your personal device during your workout using the fitness equipment's onconsole USB port.

To charge your mobile electronics make sure the fitness equipment power is on.

Step 1: Connect your USB charging cable (not included) to the USB Power Port and to your device.

Step 2: Check to make sure your device icon indicates it is charging.



NOTE:

* USB charging cable is not included, make sure compatible USB charging cable is being used.

** Your device "charging" icon may or may not indicate it is charging. Depending on the amount of current your particular device requires for charging the icon may not be on but your device is still charging, but possibly at a lower charge rate.

***The USB port on the console is capable of powering USB devices. It provides up to **5Vdc/1.0** amp of power and meets USB 2.0 regulations. You will not be able to save your workout data to a USB via this port; it is used for charging purposes only.


PROGRAMMABLE FEATURES

The F63 have ten built-in programs: one Manual program, five preset profiles (P1-P5), two user defined programs (U1 & U2) and two Heart Rate programs (HR1 & HR2).

Hill

The HIII program simulates going up and down a hill. The workload will steadily increase and then decrease during the program.






Fat Burn


The Fat Burn program is designed, as the name implies, to maximize the burning of fat. There are many schools of thought on the best way to burn fat but most experts agree that a lower exertion level that stays at a steedy work losd is the best. The absolute best way to burn fat is to keep your heart rate at around 60% to 70% of its maximum potential. This program does not use heart rate but simulates a lower, steedy exertion workout.






Cardio


The **Cardio** program is designed to increase your cardiovascular function and endurance. This is exercise for your heart and lungs. It will build up your heart must eland increase blood flow and lung capacity. This is achieved by incorporating a higher level of exertion with slight fluctuations in work.






Strength

The **Strength** program is designed to increase muscular strength in your lower body. This program will steadily increase in workload to a high level and forces you to sustain it. This is designed to strengthen and tone your legs and glutes (muscles of the butt).







НП

The HIIT program takes you through high levels of intensity followed by periods of low intensity. This program increases your endurance by depleting your oxygen level followed by periods of recovery to replenish oxygen. Your cardiovascular system gets programmed to use oxygen more efficiently this way. This program also forces your body to become more efficient due to spikes in heart rate, between recovery periods. This aids in heart rate recovery from intense activities.

21





SELECTING A PROGRAM


 Press the Program ▲/▼ keys to view the programs on the screen then press the Enter key to select the program you would like to perform. The display will prompt you through the programming steps or you can just press the Start key to begin the program using the preset program values for age, weight and other program specific information.








- If Enter was pressed, the Message Window will display Age. You may use any of the ▲/▼ keys to adjust your age. After adjusting press the Enter key.
 - **Nate**: You may press **Start** at any time during the programming to start the program with the information you've already input.
- The Message Window will now be displaying a value, which is your body weight. Entering the
 correct body weight will affect the calorie count. Use any of the ▲/▼ keys to adjust, then press
 Enter.
 - **Calorie Display Note**: No exercise machine can give you an exact calorie count because there are too many factors which determine exact calorie burn for a particular person. Even if someone is the exact same body weight, age and height, their calorie burn may be very differ- ent then yours. The **Calorie** display is to be used as a reference only to monitor improvement from workout to workout.
- 4. The Time Window and Message Window will now be displaying a value, which is total workout time desired. Use any of the ▲/▼ keys to adjust, and then press Enter. After adjusting, press the Enter key.
- 5. The Message Window will display the preset max speed of the selected program. Use any of the ▲/▼ keys to adjust, and then press Enter. Each program has various speed changes throughout; this allows you to limit the highest speed the program will reach at it's peak.
- Press Start to begin the program. The program will begin with a 3 minute warm-up. If you want
 to bypass this and go directly to the beginning of the program, press Start again.








USER PROGRAMS

- 1. Select User 1 or User 2 via the Program ▲/▼ keys then press Enter. Note that the dot matrix display portion will have a single row of dots at the bottom (Unless there is a previously stored program). If there is a program stored under the button that is pressed, it will be retrieved. If not, you have the option of programming in your first name. The Message Window will display and flash the letter "A". To change it, press the any ▲ key, then "B" will be displayed; if the any ▼ key is pressed, the letter "Z" will be displayed. After selecting the appropriate letter, press Enter. The letter "A" will again be displayed and blinking. Repeat the procedure until all letters of your first name are programmed (7 characters maximum). When your name is displayed, press Stop and it will be stored under either User 1 or User 2.
- Next the Message Window is flashing Age. Use the Incline ▲/▼ keys to adjust. Press Enter. This is a must to continue even if age is not adjusted.
- The Message Window will now be blinking a body weight value. Enter your body weight and press Enter.








Nate: While in a User program, if you change the speed, all segment speeds from there on will also change. **Examples:** If you increase your current speed. I mph, theremaining segment speeds will increase by 1 mph. If you decrease your current speed. 3 mph, theremaining segment speeds will decrease by .5 mph, etc.





HEART RATE PROGRAMS

Before we get started, a word about Heart Rate:

The old motto, "no pain, no gain", is a myth that has been overpowered by the benefits of exercising comfortably. A great deal of this success has been promoted by the use of heart rate monitors. With the proper use of a heart rate monitor, many people find that their usual choice of exercise intensity was either too high or too low and exercise is much more enjoyable by maintaining their heart rate in the desired benefit range.


To determine the benefit range in which you wish to train, you must first determine your Maximum Heart Rate. This can be accomplished by using the following formula: 220 minus your age. This will give you the Maximum Heart Rate (MHR) for someone of your age. To determine the effective heart rate range for specific goals you simply calculate a percentage your MHR. Your Heart rate training zone is 50% to 90% of your maximum heart rate. 60% of your MHR is the zone that burns fat while 80% is for strengthening the cardio vascular system. This 60% to

80% is the zone to stay in for maximum benefit.

For someone who is 40 years old their target heart rate zone is calculated:

220 – 40 = 180 (maximum heart rate) 180 x 0.6 = 108 beats per minute (60% of maximum) 180 X 0.8 = 144 beats per minute (80% of maximum)

So for a 40 year old the training zone would be 108 to 144 beats per minute.



If you enter your age during programming the console will perform this calculation automatically. Entering your age is used for the Heart Rate programs. After calculating your MHR you can decide upon which goal you would like to pursue.

The two most popular reasons for, or goals, of exercise are cardiovascular fitness (training for the heart and lungs) and weight control. The black columns on the chart above represent the MHR for a person whose age is listed at the bottom of each column. The training heart rate, for either cardiovascular fitness or weight loss, is represented by two different lines that cut diagonally through the chart. A definition of the lines' goal is in the bottom left-hand corner of the chart. If your goal is cardiovascular fitness or if it is weight loss, it can be achieved by training at 80% or 60%, respectively, of your MHR on a schedule approved by your physician. Consult your physician before participating in any exercise program.

RATE OF PERCEIVED EXERTION

Heart rate is important but listening to your body also has a lot of advantages. There are more variables involved in how hard you should workout than just heart rate. Your stress level, physical health, emotional health, temperature, humidity, the time of day, the last time you ate and what you ate, all contribute to the intensity at which you should workout. If you listen to your body, it will tell you all of these things.

The rate of perceived exertion (RPE), also know as the Borg scale, was developed by Swedish physiologist G.A.V. Borg. This scale rates exercise intensity from 6 to 20 depending upon how you feel or the perception of your effort.

The scale is as follows: Rating

Perception of Effort

6 Minimal

7 Very, very light.

8Very,very light +

9 Very light

10 Very light +

11 Fairly light

12 Comfortable

13 Somewhat hard

14 Somewhat hard +

15 Hard

16 Hard +

17 Very hard.

18 Very hard +

19 Very, very hard.


20 Maximal

You can get an approximate heart rate level for each rating by simply adding a zero to each rating. For example a rating of 12 will result in an approximate heart rate of 120 beats per minute. Your RPE will vary depending up the factors discussed earlier. That is the major benefit of this type of training. If your body is strong and rested, you will feel strong and your pace will feel easier. When your body is in this condition, you are able to train harder and the RPE will support this. If you are feeling tired and sluggish, it is because your body needs a break. In this condition, your pace will feel harder. Again, this will show up in your RPE and you will train at the proper level for that day.

USING HEART RATE TRANSMITTER (OPTIONAL)

If you purchase a wireless chest strap transmitter from Sole, here are the instructions on how to wear it:

- Attach the transmitter to the elastic strap using the locking parts.
- Adjust the strap as tightly as possible while ensuring that the strap is not too tight to remain comfortable.
- 3. Position the transmitter with the SOLE logo in the middle of your body, facing away from your chest. Some people may have to position the transmitter slightly left of the center of their chest. Attach the end of the elastic strap by inserting the round end. Using the locking parts, secure the transmitter and strap around your chest.



- 4. Position the transmitter immediately below the pectoral muscles.
- 5. Sweat is the best conductor for measuring minute heartbeat electrical signals. However, you can use plain water to pre-wet the electrodes. The electrodes are the two ribbed oval areas on the reverse side of the belt and both sides of the transmitter. We also recommend wearing the transmitter strap a few minutes before your workout to warm it up. Because of body chemistry, some users have a more difficult time achieving a strong, steady signal initially. Warming up with the transmitter will help decrease this problem. As noted, wearing clothing over the chest strap transmitter will not affect performance.
- 6. Your workout must be within rangerange to achieve a strong and steady signal. The range length may vary, so stay close enough to the console to maintain strong and reliable readings. Wearing the transmitter immediately against bare skin assures you of proper operation. If you wish, you may wear the transmitter over a shirt. To do so, moisten the areas of the shirt where the electrodes will rest.

Nate: The transmitter automatically activates when it detects activity from the user's heart and automatically deactivates when it does not receive any activity. Although the transmitter is water resistant, maistare can create false signals, so you should take precautions to dry the transmitter after use to prolong buttery life completely. The estimated fransmitter battery life is 2500 hours. The replacement battery is a Panasonic CR2032.

ERRATIC OPERATION

Contion! Do not use this treadmill for Heart Rate unless a steady, solid /actual Heart Rate value is being displayed. High, wild, random numbers being displayed indicate a problem.

Areas to look for interference which may cause erratic heart rate:

- Microwave ovens, TVS, small appliances, etc.
- 2. Fluorescent lights.
- 3. Some nousehold security systems.
- 4. Perimeter fence for a pet.
- Some beople have problems with the transmitter blicking up a signal from their skin. If you have problems
 try webring the transmitter upside cown. Normally the transmitter will be oriented so the SOLE logo is
 right side up.
- The antenna that picks up your heart rate is very sensitive. If there is an outside noise source, turning the whole machine 90 degrees may de tone the interference.
- Loose treadmill console or bolts in the upright tube.
- 8. Another Individual wearing a paramitter within 3 of your machine's console.

If you continue to experience problems contact your dealer.

To check if your Garmin device can be used for heart rate transmission, please refer to the list of supported devices provided on **www.soletreadmills.com**

WARNING! - DO NOT USE THE HEART RATE PROGRAM IF YOUR HEART RATE IS NOT REGISTERING PROPERLY ON THE TREADMILL'S DISPLAY!

HEART RATE PROGRAMMING

CAUTIONI

Heart Rate programs are intended for wireless transmitter chest strap only. Do not use **Pulse Grip** bar for **Heart Control**. You must receive a strong/steady value in the **Heart Rate Window**(See Using Heart Rate Transmitter section for instructions on how to use).

The HR1 program has a default level that is 60% of your projected heart rate maximum. This program is geared for individuals with fat loss as a goal. The HR2 program has a default of 80% of your projected heart rate maximum. It is geared for individuals with a goal of improving cardiovascular & lung function.

- Select HR1 or HR2 via the Program +- keys then press Enter.
- The Message Window will now be blinking showing user's age. Adjust and press Enter or press.
 Enter to accept the default value. Adjusting Age will change the Target HR value.
- The Message Window will be blinking, showing the default user's bodyweight for this program.
 You may adjust it and press Enter if you want or just press Enter to accept the default value.
- 4. Now you are asked to adjust the HR1 or HR2 value. The default is 60% (HR1); (220 age x 0.60); or 80% (HR2); (220 age x 0.80). You may select a higher or lower number also. Adjust the number by pressing the **Speed+** keys (console or handrails) and press **Enter** to continue.
- The Time Window and Message Window will now be blinking. Adjust the time and press. Enter.
- 6. Now you are finished editing the settings and can begin your workout by pressing the **Start** key. You can also go back and modify your settings by pressing the **Stop** key to go back one level, or screen.
- If you want to increase or decrease the speed at any time during the program press the Speed +(console or handrail) keys.
- 8. During the HR program you will be able to scroll through the data in the Message Window by pressing the Display key. When the program ends the Message Window will show a summary of your workout. The summary will be displayed for a short time then the console will return to the start-up display.
- 9. Press Start to begin program.

The program will now control the treadmill to steadily increase your heart rate to the target value. This process is automatic and could take upwards of five minutes, depending on how far your HR needs to go and what kind of physical shape you are in. People who are more fit will take longer to reach the target.

GENERAL MAINTENANCE

BELT & DECK

Your treadmill uses a very high-efficient low-friction deck. Performance is maximized when the deck is kept as clean as possible. Use a soft, damp cloth, or paper towel, wipe the edge of the belt and the area between the belt edge and the frame. Also reach as far as practical directly under the belt edge. This should be done once a month to extend belt and bed life. A mild soap and water solution along with a nylon scrub brush will clean the top of the textured belt. **Allow to dry before using**.

BELT DUST

This occurs during normal break-in or until the belt stabilizes. Sometimes the black dust from the belt will appear on the floor behind the treadmill, this is normal.


GENERAL CLEANING

Dirt, dust, and hair can block air inlets and accumulate on the running belt. Please vacuum underneath your treadmill on a monthly basis to prevent excess build-up of dirt that can get sucked up and get into the inner workings under the motor cover. Every other month, you should remove the motor cover and carefully vacuum out dirt and hair that may accumulate, UNPLUGTHE POWER—CORD BEFORE THIS TASK.

BELT ADJUSTMENTS

Tread-belt Tension Adjustment - Belt tension is not critical for most users. It is very important though for joggers and runners in order to provide a smooth, steady running surface. Adjustment must be made from the rear roller with the M6 L Allen wrench (103) provided in the parts package. The adjustment bolts are located at the end of the step rails as shown in the diagram below. **Nate**: Adjustment is through small hole in end cap.

Tighten the rear roller only enough to prevent slippage at the front roller. Turn the tread-belt tension adjusting bolts 1/4 turn each and inspect for proper tension by walking on the belt and making sure it is not slipping or hesitating with each step. When an adjustment is made to the belt tension, you must be sure to turn the bolts on both sides evenly or the belt could start tracking to one side instead of running in the middle of the deck.




DO NOT OVERTIGHTEN – Over tightening will cause belt damage and premature bearing failure. If you tighten the belt a lot and it still slips, the problem could actually be the drive belt located under the motor cover - that connects the motor to the front roller. If that belt is loose it feels similar to the walking belt being loose. Tightening the motor belt should be done by a trained service person.

TREAD-BELT TRACKING ADJUSTMENT

The treadmill is designed so that the tread-belt remains reasonably centered while in use. It is normal for some belts to drift near one side while in use, depending on a user's gait and if they favor one leg. But if during use the belt continues to move toward one side, adjustments are necessary.

TO SET TREAD-BELT TRACKING

A 6 mm Allen wrench (103) is provided for this adjustment. Make tracking adjustments on the left side bolt. Set belt speed at 3 mph. Be aware that a small adjustment can make a dramatic difference which may not be apparent right away. If the belt is too close to the left side, then turn the bolt only a 1/4 turn to the right (clockwise) and wait a few minutes for the belt to adjust itself.



Continue to make 1/4 turns until the belt stabilizes in the center of the running deck. If the belt is **too close to the right side**, turn the bolt counter-clockwise. The belt may require periodic tracking adjustment depending on use and walking/running characteristics. Some users may affect tracking differently. Expect to make adjustments as required to center the tread-belt. Adjustments will become less of a maintenance concern as the belt is used. Proper belt tracking is an owner responsibility common with all treadmills.

ATTENTION:

DAMAGETO THE RUNNING BELT RESULTING FROM IMPROPERTRACKING / TENSION ADJUSTMENTS IS NOT COVERED UNDER THE SOLEWARRANTY.

BELT/DECK LUBRICATION

First, you want to clean between the belt and deck to remove any debris that may be trapped. Use a clean, non-fraying rag, t-shirt, or light towel. Halfway between the end of the treadmill and motor cover, shove the garment under the belt until you can grasp it on both sides of the belt. Drag the garment the length of the entire belt 1-2 times. Remove the garment.

Do not lubricate with anything other than Sole Fitness approved lubricant. 100% Food grade Silicone lubricant for treadmills. (DO NOT USE SILICONE CAULKING FOR BATHROOM AND KITCHEN PROJECTS OR A LUBRICANT THAT HAS A SPRAY/FOAM BASE)

Your treadmill comes with one tube of "Lube" and extra tubes can be ordered directly from Sole Fitness or your authorized Sole Fitness dealer. You may also use a Lube-n-Walk kit that can be purchased through both aforementioned sellers. You need to use 2-3 ounces of lubrication each application.

Keeping the deck lubricated at the recommended intervals ensures the longest life possible for your treadmill. If the lubricant dries out, the friction between the belt and deck rises and places undue stress on the drive motor, drive belt and electronic motor control board, which could result in catastrophic failure of these expensive components. Failure to lubricate the deck at regular intervals may void the warranty.

The belt & deck come pre-lubricated and subsequent lubrication should be performed every 90 hours of use, or every 90 days, regardless of usage as it can dry out, or if you notice that the deck is dry. It is recommended that you reach between the belt and deck to verify there is lubrication present, every other month. If you check and there isn't any lubrication present, follow the procedure below even though the "Lube" indicator isn't lit on the console. Otherwise, lubricate when the console's lubrication reminder lights after 90 hours of use. Use the following procedure to apply the silicone lubricant:

- Turn the power switch off and unplug the power cord from the wall outlet
- Measure 18" from the edge of the motor cover; kneel down and reach under the belt approximately 4-6" from one edge. Squirt a line of lubricant about 1/8" wide x 15" long in an "S" pattern perpendicular to the motor cover.
- 3. Repeat the process on the opposite side.
- Plug the electrical cord back into the outlet and turn the power switch on.
- 5. Walk on the belt at a moderate speed for five minutes to evenly distribute the silicone lube.
- If the "Lube" message appears on the console, perform the following procedure to reset the message:
 - a. To enter the Engineering Mode Menu press and hold down the Start, Stop and Enter keys, then at the same time insert the Safety Key. Keep holding the keys down until the Message Window displays Engineering Mode Menu. Press the Enter button to access.
 - Press the Speed ▲ button (or Speed ▼ button to go backwards) until "Functions" appears; press Enter.
 - c. Press the Speed ▲ button until "Maintenance" message appears: press Enter to reset the lube message.
 - d. Press Stop to exit Engineering Mode and resume use of your treadmill.

SERVICE CHECKLIST - DIAGNOSIS GUIDE

Before contacting your dealer for aid, please review the following information. It may save you both time and expense. This list includes common problems that may not be covered under the treadmill's warranty.

PROBLEM	SOLUTION/CAUSE
FIXOBLLIN	30LU HUN CAUSE

Display does not light	1. Tether cordination position. 2. Circuit bresker on frontigril tripped. Pusin circuit bresker in until it locks. 3. Plug is disconnected. Make sure plug is firmly pushed into AC household wall outlet. 4. Household circuit bresker may be tripped. 5. Tresdmill defect. Contact your SOLE dealer.
Tread-belt does not stay centered Treadmill belt hesitates when walked/run on	The user may be walking while favoring or putting more weight on either the left or right foot. If this walking pattern is natural, track the belt's ightly officenter to the side opposite from the belt movement. See General Maintenance section on Tread-belt Tension . Adjust as necessary.
Motor is not responsive after pressing Start	 If the belt moves, but stops after a short time and the disp by shows "E1", run calibration. If you press Start and the belt never moves, then the disp by shows "E1", contact service.
Treadmill will only achieve approximately 7 mph but shows higher speed on display	This indicates motor should be receiving power to operate. Low AC voltage to treadmill. Do not use an extension cord. If an extension cord is required it should be as a not as possible and heavy duty 16 gauge minimum. Low household voltage. Contact an electrician pryour SOLE dealer. A minimum of 110 volt AC current is required.
Tread-belt stops quickly/suddenly when tether cord is pulled	High belt/deck friction. See General Maintenance section on lubrication.
Treadmill trips on board 15 amp circuit	High belt/deck friction. See General Maintenance
Computer shuts off when console is touched (on a cold day) while walking/running	Treadmill may not be grounded. Staticle extricity is "trashing" the computer. Refer to Grounding Instructions on page 3.
House circuit breaker trips, but not the treadmill circuit breaker	Check that the treadmill is the only appliance in the circuit. See "Important Electrical Information" in the front of this manual for more details.

CALIBRATION PROCEDURE

- Remove the Safety Key.
- Press and hold down the **Start and Speed** ▲ buttons and at the same time replace the **Safety Key.** Continue to hold the **Start and Speed** ▲ keys until the window displays "Factory settings", then press the **Enter** key.
- 3. You will now be able to set the display to show Metric or English settings (Miles vs. Kilometers). To do this, press the incline▲/▼ key to show which you want, then press Enter. (The maximum speed value is displayed in the speed window, and the maximum elevation value is displayed in the incline window.)
- Grade return On (This allows the incline to return to zero when Stop button is pressed. For sale
 in Europe, EU standards require this to be off)
- 5. Press **Start** button to begin calibration. The process is automatic; the speed will start up without warning, so do not stand on the belt.

ADJUSTING THE SPEED SENSOR

If the calibration does not pass you may need to check the speed sensor alignment.

- Remove the motor cover hood by loosening the 4 screws that hold it in place (you do not need to remove them completely).
- 2. The speed sensor is located on the left side of the frame, right next to the front roller pulley (the pulley will have a belt around it that also goes to the motor). The speed sensor is small and black with a wire connected to it.
- 3. Make sure the sensor is as close as possible to the pulley without touching it. You will see a magnet on the face of the pulley; make sure the sensor is aligned with the magnet. There is a screw that holds the sensor in place that needs to be loosened to adjust the sensor. Re-tighten the screw when finished.



MAINTENANCE MENU.

- Press and hold the Start, Stop and Enter key at the same time, until the display shows "Engineering mode" (it may say maintenance menu, depending on version).
 Press the Enter key.
- You can now scroll through the menu using the Speed ▲/▼ keys. Use the Stop key to return to previous menu selection. The menu selections are:
 - A. **Key Test** Will allow you to test all the keys to make sure they are functioning.
 - B. Display Test. Tests all the display functions.
 - ← Functions Press Enter to access settings, use Speed ▲/▼ keys to saroll.
 - Sleep Mode. Turn on to have the console power down automatically after 15 minutes of inactivity.
 - II. Pause Mode Turned on to a low 5 minutes of pause, turn off to have console pause in definitely
 - III. Maintenance Reset lube message and odometer readings.
 - IV. Units Choose from English or Metric display readings.
 - V. **Key Tone** Will turn on/off beeping noise that is made when keys are pressed.
 - C. Security Allows you to lock the keypad so no unauthorized use of the machine is a lowed. When the child lock is enabled, the console will not allow the keypad to operate unless you press and hold the Start and Enter buttons for 3 seconds to unlock the console.
 - E. Exit

MANUFACTURER'S LIMITED WARRANTY

TREADMILLWARRANTY

Effective February 1, 2023

SOLEssment all its two milk parts, for a period of time fixed below, burning devicts is acquived and overance operand to absence of a two puriods (19) months from the organization of parts at SOLE's copied and control of puriods of the period of a dealer or service organization, these was reminerable or a mixture of a dealer or service organization, these was reminerable or mixtured by SOLE of willy or a consumer Thomas many period applies of the following componence.

France Welbarrente — L'et me Drive Motor — L'et me Decis — 2 fears — 2 fears — 2 fears — 2 fears — L'apor — L'hear — Connetic cons * 90 Eays

Cosmodia home in qualific, but not limited to the following crips, so wole overlays, and labels/docsb-

NORMAL RESPONSIBILITIES OF THE CONSUMER.

This same my applies only to produce in ordinary however bld low, and the consumer is responsible for the items lated below:

- Thin swifterbying station it and most be completed and not minute very lived on the card within 10 days of the day and purchase to validate
 the manufacturers in the days are myor. Toutside of the 10 day period, the warranty can be registered if you have proof of purchase (twincising),
 particular registered to repair and once confirmation).
- Proper use of the triadmilling accordance with the instructions provided in this manual, including general maintenance (i.e. or l. tracking, by the nicion, vacuuming under moter cover, and lebroacion, Ser all components under Contral Manuerance section).
- 3. Proper installation in accordance with restructions provided with the assignful and with all local plot the codes.
- Proper connection to a grant dedictive supply of sulfaces, voltage, replacement of botton lusts, reper of cosmoning tions and rick as in notice to the
- to ring.

 5. Decretes for the king the teachrill accessible for servicing including any item the teacher part of the teachrilla. The time it was shipped from the factors.
- 6. Damages of the Essentill Enishdumgshipping installation of ollowing its allation.
- 7. Bout in maintenance of this unit as assertice in this manual (for All Comprehents under General Maintenance).
- Provide products or extends any issues via must be requested by the service team cian. Assist with troub exhapting/diagnosing prior to a home.

 visit.

EXCLUSIONS

This warrancy does not cover the following:

- CONSEQUENTIAL COLLATORAL, ON INTIDENTAL DAMAGES SUCH AS PROFESTY DAMAGE AND INCIDENTAL EXPENSES RESULTING FROM ANY
 DREACH OF THIS WORTHEN OR ANY IMPLIED WAYS ANTIC
 - **Motor** Some materials not allow the experience institutes of insidential according to the identity of experience and experi
- Service call to moursement to the construct Service call tour currentment in the dealer that does not involve malturation on defects in
 exercinate rip or material, for units that are dependently period, for units that are dependently encoursement, period, for
 executiff not veget ingreen period, to period, for the definition of inary household use.
- 3. Damages caused by services performed by persons other than authorized SCLE shrytelecompanies; use of parts other than onginal SOLE earts; on contrast such as contrast on (RUST), discoloration of parts of parts in a ntersance (see general maintenance instructions execution), including tack of core stem, begrinal of the dock, hadequate power supply, hatters lideauters, or elemental damage (i.e. power supply, lightning storms, water damage, or limit damage).
- 4. Products with original sonal numbers that hew even removed practiced.
- Products the head promotion, transferred, barboned, ong world a third party. (Warrenties PO NOT transfert)
- Product the donether awarency significant at for librar SOLE SOLE swortwithings, to voluest profit in purchase if newarrancy swords
 we station the product.
- 7. THISWARRANTY IS EXPRESSLY IN LIEU OF ALL OT TERWARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF METCHANDAULITY.
 AND ACTUAL TRUESS FOR A PAST CULAR PURPOSE.
- 8. Product use in any environment other than a visidential viriting.
- 9. Watterbird outside of North America may vary. Picase contact, your local idealor for details. Shipping the iges may apply to Alacse and Hawaii.
- (b). Warranty will be void if the unit is not in actimates on relied, invulated environment. (Evangle: Garage, outside, Laccort, etc.)

SERVICE

Keepyaur hill of sace Twelve (12) months from the date on the bill of value or gateon (18) months from the date of tackety shipping as determined by the sense intermediately have been acquired. If so vice is deformed, it is injourned, interest to estain and seep all receipts. This was ten was transported egal nights from may also have other nights. Vary from state to state Service under this example obtained by following these segs, in order.

- To Contact yourselling authorized SCLD dealer Ob-
- 2. Submit all service requests including serial number, contact information and a brief description of the problem online at https://www.ooktreacmills.com/acres contact.html
- There is a question as to whose to obtain service, contact our service department at 866-796-7853.
- 4. In ollocal softice, savailable, SOLE will epair one-place, he parts, at SOLEs option, within the samenty period at no charge for carts. All transportation codes, both to our factory and upon estum to the owner the expensibility of the owner. The owner is expensible for adequate parts aging upon estum to SOLE SOLE is not exponsible for damages that excur during shipping. Make all the grit damage claims with the appropriate forget carrier DO NOTISHEANY UNITED OUR TACTORYWITHOUT ART JRN AUTHORIZATION NUMBER, All units artiving to the out at return authorization number will be refused.

7.	The version department assists in troubleshooting prior to sinding a field technician, SOLE may request pictures and video via email of issues to help with diagraxing.	
	Before returning your Sole product to any retailer, or if you require any	
assistance with assembly or technical support please call us first for		
	assistance at 866-780-7653. Thank you for your Sole purchase.	

