


2x4 LED CEILING PANEL WITH SELECTABLE CCT

Install Guide and Manual



EASY INSTALLATION RECESSED INSTALLATION

Required Tools: Drill, Ladder, Hammer, Pliers, Tape Measure, Pencil, Philips Screwdriver.


Prior to install, remove the existing light fixture (if any) from the ceiling.




1. Turn off the switch and circuit breaker before installing this LED light fixture.
2. Turn the Ceiling Panel face down on a flat surface.
 - Unscrew the (2) driver covers and set aside the screws.
3. Pop out (2) knockouts (choice of 5).



4. Connect conduit to each knockout.
 - Pass wires through.




5. Connect the supply wires to the Ceiling Panel wires with included wire nuts.
 - Black to Black (live);
 - White to White (neutral);
 - Green to Green (ground).



DIM- (pink)
DIM+ (purple)


6. OPTIONAL for using a dimmer (not included):
 - Connect the DIM+ and DIM- wiring of your Ceiling Panel to your dimmer with included wire nuts.



CCT Selection
Switch




7. Replace driver covers.
 - Tighten the screws.
8. BEFORE PROCEEDING
On back of panel, slide the CCT Selection Switch to choose from three color temperatures (4000K, 5000K, 6000K).
 - Light will use the selected CCT setting when switched on.




Protective
Bracket

9. Locate the (4) protective brackets on back of panel.
 - Bend up 90°.



10. Twist 90° so hook faces outside edge of Ceiling Panel.




11. Install Ceiling Panel in ceiling, using protective brackets.
12. Turn on circuit breaker and test the light.

WARNING

- To reduce the risk of fire, electric shock or serious injury:
- Installation should be performed by a professional, qualified electrician familiar with the construction and operation of this product and the hazards involved.
 - Abide by related regional and local laws or regulations.
 - Proper grounding is required to ensure safety.
 - Not suitable for a wet environment.
 - LED must be installed in an appropriate environment to work. Harsh environments may damage the light or shorten its lifespan.
 - Check for damage during shipping prior to install. If the product is damaged, do not use it.
 - Turn off the switch and circuit breaker before installing this LED light fixture. Recommended: Use an appropriate meter to accurately verify no voltage on the lines. After verifying there is no voltage, disconnect wires and remove existing light fixture from the ceiling (if any).
 - After verifying no voltage, disconnect wires and remove existing light fixture from ceiling (if any).
 - To ensure efficient light, regularly clean the light panel. Don't clean with harsh solvents; use a dry cloth.
 - Use safety precautions. Safety eyeglasses and gloves are recommended.

WIRING DIAGRAM



To make the light panel dimmable, connect a compatible dimmer (not included) to the dimming signal wires of the luminaire. Suitable for Constant Current Reduction Dimming 0-10V.

2x4 LED CEILING PANEL WITH SELECTABLE CCT

Install Guide and Manual



EASY INSTALLATION SUSPENSION INSTALLATION

Required Tools: Drill, Ladder, Hammer, Pliers, Tape Measure, Pencil, Philips Screwdriver.

Note: 2-piece suspension kits required (not included).





1. Turn off the switch and circuit breaker before installing this LED light fixture.
2. Turn the Ceiling Panel face down on a flat surface.
 - Unscrew the (2) driver covers and set aside the screws.
3. Pop out (2) knockouts (choice of 5).



4. Connect conduit to each knockout.
 - Pass wires through.

5. Connect the supply wires to the Ceiling Panel wires with included wire nuts.
 - Black to Black (live);
 - White to White (neutral);
 - Green to Green (ground).




6. **OPTIONAL** for using a dimmer (not included):
 - Connect the DIM+ and DIM- wiring of your Ceiling Panel to your dimmer with included wire nuts.




CCT Selection Switch




7. Replace driver covers.
 - Tighten the screws.
8. **BEFORE PROCEEDING**
On back of panel, slide the CCT Selection Switch to choose from three color temperatures (4000K, 5000K, 6000K).
 - Light will use the selected CCT setting when switched on.



9. Drill (2) holes in the ceiling. Place the anchors into hole. Insert the wire rope and screw.
 - Refer to suspension kit's install manual for complete details.



10. Adjust the support rope/wire so Ceiling Panel hangs horizontally.
 - Suspension kit is not included.



11. Install Ceiling Panel in ceiling, using protective brackets.
12. Turn on circuit breaker and test the light.

WARNING

- To reduce the risk of fire, electric shock or serious injury:
- Installation should be performed by a professional, qualified electrician familiar with the construction and operation of this product and the hazards involved.
 - Abide by related regional and local laws or regulations.
 - Proper grounding is required to ensure safety.
 - Not suitable for a wet environment.
 - LED must be installed in an appropriate environment to work. Harsh environments may damage the light or shorten its lifespan.
 - Check for damage during shipping prior to install. If the product is damaged, do not use it.
 - Turn off the switch and circuit breaker before installing this LED light fixture. Recommended: Use an appropriate meter to accurately verify no voltage on the lines. After verifying there is no voltage, disconnect wires and remove existing light fixture from the ceiling (if any).
 - After verifying no voltage, disconnect wires and remove existing light fixture from ceiling (if any).
 - To ensure efficient light, regularly clean the light panel. Don't clean with harsh solvents; use a dry cloth.
 - Use safety precautions. Safety eyeglasses and gloves are recommended.

SPECIFICATIONS

Voltage	100-277V
Wattage	50W
Suitable for Locations Ingress	Damp
Housing	SPCC+PS Lens
Weight	8.15lbs
Warranty	10 years

To make the light panel dimmable, connect a compatible dimmer (not included) to the dimming signal wires of the luminaire. Suitable for Constant Current Reduction Dimming 0-10V.