

WT5400 / WT6400 Accessories Guide

Revised April 2025



I. Accessories that POWER wearable terminals

1 Chargers

1.1	Wearable Terminal Cradles	3
1.2	Combined Wearable Terminal and Battery Charger	3
1.3	Battery Chargers	4

2 Batteries

2.1	Spare Li-ion standard capacity batteries	4
2.2	Spare Li-ion extended capacity batteries	4

3 Power supply, cables, and adapters

3.1	Power supply and cable matrix	5
3.2	Headset cables	5
3.3	Vibrating cable	5

II. Accessories that ENABLE productivity solutions

4 Wearable mounts

4.1	Wrist Mounts	6
4.2	Hip Mount	6

5 Replacement Wrist Straps

5.1	Single Dial Straps	7
5.2	Double Dial Straps	7
5.3	Velcro Straps	7
5.4	X-Straps	7

6 Other Accessories

6.1	Arm Sleeves	8
6.2	Screen Protector	8

7 Corded Ring Scanners

WT5400 / WT6400 Cradles



WT5400 / WT6400 Single Slot Charge Cradle

SKU# CRD-WT5X6-1S1BC-01

Single Slot Charge Only Sharecradle, Allows Charging Of 1 Wearable Terminal And 1 Spare Battery.

- Sold separately: Power supply [SKU# PWR-BGA12V50W0WW](#), DC cable [SKU# CBL-DC-388A1-01](#), and Country-specific AC line cord



WT5400 / WT6400 10-Slot Charge Cradle

SKU# CRD-WT5X6-10SC-01

10-Slot Charge Only cradle, Allows Charging Of 10 Wearable Terminals.

- Sold separately: Power Supply [SKU# PWR-BGA12V108W0WW](#), DC Line Cord [SKU# CBL-DC-381A1-01](#), Country Specific 3 wire AC Line Cord and Rack/Wall Mounting bracket for multi-slot cradles [SKU# BRKT-SCRD-SMRK-01](#).



WT5400 / WT6400 5-Slot Charge Cradle

SKU# CRD-WT5X6-5S5BC-01

5-Slot Charge Only Sharecradle With Spare Battery Charger, Allows Charging Of 5 Wearable Terminals And 5 Spare Batteries.

- Sold separately: Power Supply [SKU# PWR-BGA12V108W0WW](#), DC Line Cord [SKU# CBL-DC-381A1-01](#), Country Specific 3 wire AC Line Cord and Rack/Wall Mounting bracket for multi-slot cradles [SKU# BRKT-SCRD-SMRK-01](#).



WT6400 5-Slot Ethernet Cradle

SKU# CRD-WT64-5S5BE-01

5-Slot Ethernet Sharecradle With Battery Charger, Allows Charging Of 5 WT6400 Wearable Terminals, 5 Batteries And Allows Ethernet Communication. Note: Not Compatible With WT5400.

- Sold separately: Power Supply [SKU# PWR-BGA12V108W0WW](#), DC Line Cord [SKU# CBL-DC-381A1-01](#), Country Specific 3 wire AC Line Cord and Rack/Wall Mounting bracket for multi-slot cradles [SKU# BRKT-SCRD-SMRK-01](#).

Battery Charger




WT5400 / WT6400 4-Slot Battery Charger

SKU# SAC-WT5X6-4SC-01

4-Slot Spare Battery Charger, Allows Charging Of 4 Spare Batteries For Wearable Terminal. LEDs on the cradle indicate charge status of each battery.

- Sold separately: Power supply [SKU# PWR-BGA12V50W0WW](#), DC cable and Country-specific AC line cord [SKU# 23844-00-00R](#)



WT5400 / WT6400 20-Slot Battery Charger

SKU# SAC-WT5X6-20SC-01

20-Slot Spare Battery Charger, Allows Charging Of 20 Batteries For Wearable Terminal. LEDs on the cradle indicate charge status of each battery.

- Sold separately: Power supply [SKU# PWR-BGA12V108W0WW](#), DC cable [SKU# CBL-DC-381A1-01](#), Country-specific AC line cord and Rack/Wall Mounting bracket for multi-slot cradles [SKU# BRKT-SCRD-SMRK-01](#).

Batteries



WT5400 / WT6400 Lithium Ion, Standard Capacity Battery

SKU# BTRY-WT5X6-35MA-01

- Standard Capacity Lithium-Ion Battery, 3500mAh, Supports Operation Between -20C/-4F And 50C/122F. PowerPrecision+ advanced battery technology, provides higher level of intelligence on battery state of charge and state of health.



WT5400 / WT6400 Lithium Ion, Extended Capacity Battery

SKU# BTRY-WT5X6-50MA-01

- Extended Capacity Lithium-Ion Battery, 5000mAh, Supports WT6400 Operation Between -30C/-22F and 50C/122F and WT5400 Operation Between -20C/-4F and 50C/122F. PowerPrecision+ advanced battery technology, provides higher level of intelligence on battery state of charge and state of health.

Accessories that power and connect to devices



Power supply, cables, and adaptors

Power supply and cable matrix

SKU#	Description	Note
CBL-EC5X-USBC3A-01	USB-C to USB-C Communications and Charge Cable, 1.2M Long; Supports 3.0 Superspeed and Fast Charge	For use with WT5400 only
CBL-TC5X-USBC2A-01	USB-A to USB-C Communications and Charge Cable, 1M Long	
CBL-NGWT-USBCHG-01	WT6300 / WT6400 USB Charging Cable. Allows Communication And Charging of the Wearable Terminal Via USB	For use with WT6400 only
PWR-WUA5V12W0US	Power Supply, 100-240 VAC, 5V, 2.5A With US Plug.	For use with CBL-TC5X-USBC2A-01 and CBL-NGWT-USBCHG-01
PWR-BGA12V50W0WW	Level VI AC/DC Power Supply (Brick, replacement for PWRS-14000-148R) AC Input: 100-240V, 2.4A DC Output: 12V, 4.16A, 50W Requires: DC line cord and Country specific grounded AC line cord.	Sold separately. Use as: - Power supply for Single Slot Terminal Charger and Four Slot Battery Charger SKU# CRD-WT5X6-1S1BC-01 and SAC-WT5X6-4SC-01 - DC Line Cord between power supply and charger - AC Line Cord between power supply and outlet (country specific)
CBL-DC-388A1-01	DC Line Cord for running the single slot cradles or battery chargers from a single Level VI power supply PWR-BGA12V50W0WW, Level VI replacement for PWRS-14000-148R.	
23844-00-00R	US AC line cord, 7.5 feet long, grounded, three wire for power supplies.	
PWR-BGA12V108W0WW	Level VI AC/DC Power Supply (Brick, Replacement for PWRS-14000-241R) AC Input: 100-240V, 2.8A DC Output: 12V, 9A, 108W Requires: DC line cord and Country specific grounded AC line cord.	Sold separately. Use as: - Power supply for Multi-slot Sharecradles and 20-slot battery charger SKU# CRD-WT5X6-10SC-01, CRD-WT5X6-5S5BC-01, CRD-WT64-5S5BE-01 and SAC-WT5X6-20SC-01 - DC Line Cord between power supply and charger - AC Line Cord between power supply and charger - Rack/Wall Mounting bracket for 20-slot ring scanner cradle and 40-slot battery charger
CBL-DC-381A1-01	DC Line Cord for running multi-slot cradles from a single Level VI power supply PWR-BGA12V108W0WW, Level VI replacement for PWRS-14000-241R	
23844-00-00R	US AC line cord, 7.5 feet long, grounded, three wire for power supplies.	
BRKT-SCRD-SMRK-01	Rack/Wall Mounting bracket for multi-slot cradles.	
CBL-NGWT-AUQDLG-01	Audio Adapter Cable, Compatible With Quick-Disconnect Wired Headsets. Intended For Use When The Device Is Worn On The Hip.	- For use with WT6400 only - Compatible with HS2100
CBL-NGWT-AUQDST-02	Audio Adapter Cable, Compatible With Quick-Disconnect Wired Headsets. Intended For Use When The Device Is Worn On The Wrist.	- For use with WT6400 only - Compatible with HS2100
25-129938-02R	Training Cable with Quick Disconnect, Connects Two Wired Headsets To One Mobile Computer	For use with CBL-NGWT-AUQDLG-01 or CBL-NGWT-AUQDST-01
CBL-NGWT-HDVBAP-01	Vibrating Cable, Connects Directly To The Wearable Terminal And Provides Additional Haptic Feedback To The User	For use with WT6400 only

Wearable Mounts

WT5400 / WT6400 Single Dial Wrist Mount

SKU# SG-WT5X6-WMTSS-01

Wrist Mount With Single Dial Strap, Small.

SKU# SG-WT5X6-WMTSL-01

Wrist Mount With Single Dial Strap, Large.

SKU# SG-WT5X6-WMTSX-01

Wrist Mount With Single Dial Strap, Extra Large, For Wearing Over A Jacket

WT5400 / WT6400 Double Dial Wrist Mount

SKU# SG-WT5X6-WMTDS-01

Wrist Mount With Double Dial Strap, Small.

SKU# SG-WT5X6-WMTDL-01

Wrist Mount With Double Dial Strap, Large.

SKU# SG-WT5X6-WMTDX-01

Wrist Mount With Double Dial Strap, Extra Large, For Wearing Over A Jacket

WT5400 / WT6400 Velcro Wrist Mount

SKU# SG-WT5X6-WMTVS-01

Wrist Mount With Two Velcro Straps, Small.

SKU# SG-WT5X6-WMTVL-01

Wrist Mount With Two Velcro Straps, Large.

SKU# SG-WT5X6-WMTVX-01

Wrist Mount With Two Velcro Straps, Extra Large, For Wearing Over A Jacket

WT5400 / WT6400 Hip Mount

SKU# SG-WT5X6-HPMNT-01

Hip Mount, Allows Wearable Terminal To Be Worn On A Belt

Replacement Straps for Wrist Mounts

WT5400 / WT6400 Single Dial Replacement Straps



SKU# SG-NGWT-WSTPST-01

Replacement Wrist Strap With Single Dial, Small, With White Accents. Strap length can be adjusted between 128 mm to 191 mm (5 in to 7.5 in).

SKU# SG-NGWT-WSTPLN-01

Replacement Wrist Strap With Single Dial, Large, With Black Accents. Strap length can be adjusted between 164 mm to 265 mm (6.5 in to 10.5 in).

SKU# SG-NGWT-WSTPLX-01

Replacement Wrist Strap With Single Dial, Extra Large, With Blue Accents. Strap length can be adjusted between 218 mm to 375 mm (8.5 in to 14.8 in).

WT5400 / WT6400 Double Dial Replacement Straps



SKU# SG-WT5X6-WSTDS-01

Replacement Wrist Strap With Double Dial, Small, With White Accents. . Strap length can be adjusted between 128 mm to 191 mm (5 in to 7.5 in).

SKU# SG-WT5X6-WSTDLE-01

Replacement Wrist Strap With Double Dial, Large, With Black Accents. Strap length can be adjusted between 164 mm to 265 mm (6.5 in to 10.5 in).

SKU# SG-WT5X6-WSTDLE-01

Replacement Wrist Strap With Double Dial, Extra Large, With Blue Accents. Strap length can be adjusted between 218 mm to 375 mm (8.5 in to 14.8 in).

WT5400 / WT6400 Velcro Replacement Straps



SKU# SG-WT5X6-WSTVS-01

Replacement Velcro Wrist Straps, Small. Strap length 290mm (11.4 in).

SKU# SG-WT5X6-WSTVL-01

Replacement Velcro Wrist Straps, Large. Strap length 340 mm (13.4 in).

SKU# SG-WT5X6-WSTVX-01

Replacement Velcro Wrist Straps, Extra Large. Strap length 440mm (17.3 in).

WT5400 / WT6400 Replacement X-Straps



SKU# SG-NGWT-WSTVLS-02

Replacement X-strap Wrist Strap, Small. Strap length 132 mm (5.3 in).

SKU# SG-NGWT-WSTVLM-02

Replacement X-strap Wrist Strap, Medium. Strap length 187 mm (7.5 in).

SKU# SG-NGWT-WSTVLL-02

Replacement X-strap Wrist Strap, Large. Strap length 225 mm (9 in).


Other Accessories for WT5400 and WT64000



Arm Sleeves

SKU# [SG-WT4027050-01R](#)

Optional Arm Sleeves For Wrist Mount (Pack Of 5).



Screen Protector

SKU# [MISC-WT5X6-SCRN-05](#)

WT5400/WT6400 Screen Protectors (Pack Of 5).

Corded Ring Scanners (WT6400 only)



RS5000x Standard Trigger Version

SKU# [RS5000X-TCFSSWR](#)

RS5000x Corded Wearable Scanner, SE4770, Short Cable, Standard Finger Trigger, Worldwide. Freezer rated to -30C. For use with WT6000, WT6300 and WT6400 wearable terminals only.



RS5000x with Larger Trigger
for use with Freezer Gloves

SKU# [RS5000X-TCFSXWR](#)

RS5000x Corded Wearable Scanner, SE4770, Short Cable, Freezer Finger Trigger, Worldwide. Freezer rated to -30C. For use with WT6000, WT6300 and WT6400 wearable terminals only.