PANTUM

The New Era for Printing

Making multifunction more convenient and affordable.

Ideally suited for the home and small business user. The new M6518NW series delivers fast and high quality printouts, scans and copies through convenient features all at an affordable cost.

3 IN I

One-Step Driver Installation and Direct Printing

20000 Page Maximum Monthly Duty Cycle

600 MHZ **128** MB Processor Speed Memory

Office Document Direct Print from Mobile Devices

Support Airprint® Mopria®,Pantum App

Fast Print and Copy Speeds

PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS

M6518NW Series
Monochrome Laser Multifunction Printer

MODEL	■ M6500NW
PRINTING	
Print speed	22ppm (A4 / 23ppm(Letter)
Resolution (print, copy & scan) [1]	1200x1200 dpi
First print out time	Less than 7.8s
Processor	600 MHZ
Memory	128MB
Duplex mode	Manual
Connectivity	High-Speed USB 2.0 Net: IEEE 802.3 10/100Base-TX WiFi: IEEE 802.11b/g/n
Maximum Monthly Duty Cycle	20,000 pages
Printer language	GDI
COPYING	
Copy speed	22ppm (A4 / 23ppm(Letter)
First copy out time	Less than 10 seconds
Zoom	25% - 400%
Max. copy pages	1 - 99 pages
Additional function	ID copy, Receipt copy, N-up copy, Clone copy
SCANNING	
Scanner type	Flatbed
Max. scan size	216 x 297mm
Color scanning	Yes
Output function	Scan to E-mail, PC, FTP iOS,Android
PAPER HANDLING	
Paper input capacity	150 pages
Paper output capacity	100 pages
Media types	Plain, Thick, Transparency, Cardstock, Label, Envelope and Thin
Media sizes	A4,A5,A6,JIS B5,ISO B5,B6, Letter, Legal, Executive,Statement, Monarch envelope, DL envelope,C5 envelope,C6 envelope,NO.10 envelope, Japanese Postcard,Folio,O-cio,Big 16k, 32k,16k,Big 32k,ZL,Yougata4, Postcard, Younaga3, Nagagata3, Yougata2
Media weight	60~163g/m²
OTHER	
Operating system compatibility	Microsoft Windows Server2003/Server2008/Server2012/XP Vista/Win7/Win8/Win8.1/Win10（32/64 Bit） Mac OS 10.7-10.15 Linux（Ubuntu 12.04&14.04&16.04&18.04）（32/64 Bit）
Dimensions（WxDxH)	417x305x244mm(16.4"×12.0"×9.6")
Weight (with toner cartridge)	7.5Kg (16.5lb)
Power	110V Model: AC100~127V(±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V(-15%,+10%); 50Hz/60Hz; 3A
Recommended temperature	10-32℃ (50°F-90°F)"
Humidity range	20 - 80%
SUPPLIES	
Toner cartridge [2]	PG-208KEV/PG-209KEV (Standard capacity toner: 1,600 pages)