QUICK REFERENCE GUIDE > CID834DTB4

Induction Cooktop, 83cm, 4 Zones with Integrated Ventilation

Series 9 | Minimal

Black Glass



A true two-in-one appliance, this cooktop combines the precision of induction cooking with powerful extraction in one seamless, stylish cooktop.

- Seamless kitchen integration, without the need for overhead ventilation
- Four cooking zones, including simple pairing of two zones to create a SmartZone
- With nine fan speeds plus boost, select the perfect extraction rate for your cooking

• Minimal style, sleek black glass finish to suit any kitchen design

DIMENSIONS

Height	218mm
Width	830mm
Depth	515mm

FEATURES & BENEFITS

SEAMLESS INTEGRATION

Offering true design freedom, this cooktop can be placed anywhere – eliminating the need for bulky overhead ventilation and helping to create a seamless flow between kitchen and living spaces. Installed raised or flush, it's perfect for islands, or homes with high ceilings.

ELEGANT DESIGN

The subtle black glass and durable matte black detailing blend elegance with durability. With premium styling, these cooktops seamlessly blend with other appliances for a cohesive, considered kitchen design.

PRECISE CONTROL

Fisher & Paykel induction cooktops offer extremely accurate temperature control from very high to very low heats, so you can sear, sauté and temper like a pro. Touch&Slide controls react immediately when you adjust the temperature, so you can go from a boil to a simmer in seconds.

EFFECTIVE EXTRACTION

Designed for busy homes, the integrated ventilation works effectively and unobtrusively in the background. Featuring nine fan speeds, plus a boost function, for quickly removing odours and steam.

SAFETY OF INDUCTION

Induction cooktops only start heating your pot or pan once you've placed it on the surface and stop as soon as you remove it – so they are safer for everyone.

EASE OF USE

Designed for simple removal, the grease filter tray effectively captures spills, while the single glass cooking surface can be easily wiped clean. A flush ventilation grille allows pots to effortlessly slide across the cooktop surface.

SUPERIOR EFFICIENCY

Less heat is wasted during induction cooking because only the cookware is heated, not the cooktop surface. This makes induction cooking more energy-efficient than electric or gas cooktops.

SPECIFICATIONS

Accessories (sold separately)

Square grille & butterfly valve

Recirculation kit Replacement recirculation filter 82236 KRCID834 (optional) 50182 FRO-DD (optional)

82393 DO-G-SS (optional)

Cleaning

Dishwasher safe grease filter	•
Flat easy clean glass surface	•
Flush grille	•
Pan detection system	•

Controls

Auto cut-off timer for each	•
Minute timer	•
Soft-touch electronic controls	•
Touch and slide controls	

QUICK REFERENCE GUIDE > CID834DTB4

Downdraft performance	
Air outlet size	220mm W x 90 mm H
Air speeds	9 + boost
Ducted externally	•
Ducting direction	Side, Rear
Maximum air flow (Boost)	660m³/hr
Maximum air flow (Level 9)	623m³/hr
Maximum noise level (Boost)	70dBA
Maximum noise level (Level 9)	69dBA
Minimum air flow	192m³/hr
Minimum noise level	38dBA
Motor type	•
Ducting Accessories (optional)	
Ducting Accessories (optional) Duct 1m Connector 222x89	82389 D1-C-222-89
	82389 D1-C-222-89 82392 DA-219-98-150
Duct 1m Connector 222x89	
Duct 1m Connector 222x89 Ducting adaptor	82392 DA-219-98-150
Duct 1m Connector 222x89 Ducting adaptor Elbow 90° horizontal 222x89	82392 DA-219-98-150 82390 E90-H-222-89
Duct 1m Connector 222x89 Ducting adaptor Elbow 90° horizontal 222x89 Elbow 90° vertical 222x89	82392 DA-219-98-150 82390 E90-H-222-89
Duct 1m Connector 222x89 Ducting adaptor Elbow 90° horizontal 222x89 Elbow 90° vertical 222x89 Performance	82392 DA-219-98-150 82390 E90-H-222-89
Duct 1m Connector 222x89 Ducting adaptor Elbow 90° horizontal 222x89 Elbow 90° vertical 222x89 Performance Gentle heat	82392 DA-219-98-150 82390 E90-H-222-89 82391 E90-V-222-89
Duct 1m Connector 222x89 Ducting adaptor Elbow 90° horizontal 222x89 Elbow 90° vertical 222x89 Performance Gentle heat Heat settings	82392 DA-219-98-150 82390 E90-H-222-89 82391 E90-V-222-89
Duct 1m Connector 222x89 Ducting adaptor Elbow 90° horizontal 222x89 Elbow 90° vertical 222x89 Performance Gentle heat Heat settings Induction cooking technology	82392 DA-219-98-150 82390 E90-H-222-89 82391 E90-V-222-89
Duct 1m Connector 222x89 Ducting adaptor Elbow 90° horizontal 222x89 Elbow 90° vertical 222x89 Performance Gentle heat Heat settings Induction cooking technology Pause function	82392 DA-219-98-150 82390 E90-H-222-89 82391 E90-V-222-89
Duct 1m Connector 222x89 Ducting adaptor Elbow 90° horizontal 222x89 Elbow 90° vertical 222x89 Performance Gentle heat Heat settings Induction cooking technology Pause function PowerBoost	82392 DA-219-98-150 82390 E90-H-222-89 82391 E90-V-222-89

Maximum power	7.4kW
Supply frequency	50Hz
Supply voltage	220 - 240V
Product dimensions	
Depth	515mm
Height	218mm
Width	830mm
Safety	
Keylock	•
Pan detection system	•
Safety time out	•
Surface hot indicators	•
Warranty	
Parts and labour	2 years
Zone ratings	
Left front	2100W
Left front zone (PowerBoost	3000W
Left rear	2100W
Left rear zone (PowerBoost	3000W
Right front	2100W
Right front zone (PowerBoost	3000W
Right rear	2100W
Right rear zone (PowerBoost	3000W
SmartZone	3700W

Number of elements	4
SKU	82228

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Zones

QUICK REFERENCE GUIDE > CID834DTB4

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide



Installation Guide



Data Sheet Induction Hob



Planning Guide Induction Cooktop with Integrated Ventilation



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T +65 6741 0777 Wwww.fisherpaykel.com