

# MULTI SPLIT CASSETTE units


with 4-way airflow

Heiko cassette air conditioners are a great solution for installation in the home, office, or restaurant. The range includes units with different capacities to match the size of the building area. The cassette air conditioners are available with a 4-way airflow panel (optional). Heiko units are unobtrusive, installation-friendly and will fit in well with any décor.

TEMPERATURE SETPOINT from 16 to 30°C



High energy  
efficiency



SMART  
airflow



Airflow  
control



Quiet  
operation


**TURBO MODE**

ONE-TOUCH  
FULL POWER


**SLEEP  
FUNCTION**

SLEEP FUNCTION  
MAKE YOUR SLEEP  
COMFORTABLE

**AUTO  
COOLING  
HEATING  
DRYING  
FAN**



Indoor unit



Cover  
PB-700HE4  
(option)



Wireless controller  
R-NRS01 (option)



Wired controller  
YR-C01 (option)

| Indoor unit           |                                   | CA035-A1        |                 | CA050-A1        |
|-----------------------|-----------------------------------|-----------------|-----------------|-----------------|
| Capacity              | Cooling                           | kW              | 3.5             | 5               |
|                       | Heating                           | kW              | 4.0             | 5.5             |
| Electrical parameters | Power supply                      | f/V/Hz          | 1/220-240/50/60 | 1/220-240/50/60 |
| Performance           | Airflow                           | m³/h            | 620/520/420/350 | 700/600/500/400 |
|                       | Sound power level                 | dB(A)           | 52              | 57              |
|                       | Sound pressure level              | dB(A)           | 35/32/30/28     | 42/37/35/31     |
| Installation          | Package dimensions (W/D/H)        | mm              | 570/570/260     | 570/570/260     |
|                       | Dimensions with packaging (W/D/H) | mm              | 718/680/380     | 718/680/380     |
|                       | Net/gross weight                  | kg              | 18.5/22         | 18.5/22         |
|                       | Liquid pipe diameter              | mm              | 6,35            | 6,35            |
|                       | Gas pipe diameter                 | mm              | 9,52            | 12,7            |
| Controller            |                                   | Wireless option | YR-NRS01        | YR-NRS01        |
|                       |                                   | Wired option    | YR-C01          | YR-C01          |
| Cover                 | Type                              | Option          | PB-700HE4       | PB-700HE4       |
|                       | Package dimensions (W/D/H)        | mm              | 700/700/60      | 700/700/60      |
|                       | Dimensiozn with packaging (W/D/H) | mm              | 740/750/115     | 740/750/115     |
|                       | Net/gross weight                  | kg              | 2.8/4.8         | 2.8/4.8         |