

RACKS BRAX.[®]

COMPATIBILITY POCKET GUIDE

FOR



*FAST ON!
FAST OFF!*

AWNING AND ACCESSORY MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW
TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

XTM[®] 270° AWNING 3

XTM[®] AWNING 1.4 x 2.0 m 4

XTM[®] AWNING TENT 2.0 x 2.5 m 5

XTM[®] CAR AWNING 2.0 x 2.5 m 6

XTM[®] COMPACT 4WD AWNING 2.0 x 2.0 m 7

XTM[®] INSTANT SHOWER TENT 8



XTM® 270° AWNING

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*
ADAPTOR NEEDED	8192 – HD Awning Adaptor Plate (DOUBLE)*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM XTM® WILL NOT WORK WITH THE HD HITCH RANGE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts ⁺
✓ LOCKED GARAGES ✓ WORKSHOP WALLS	
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts ⁺
✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA	

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

XTM® AWNING 1.4 x 2.0 m**HITCHES** REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM XTM® WILL WORK WITH THE HD HITCH RANGE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts*
✓ LOCKED GARAGES ✓ WORKSHOP WALLS	
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts*
✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA	

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

XTM[®] AWNING TENT *2.0 x 2.5 m*

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM XTM [®] WILL WORK WITH THE HD HITCH RANGE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts*
✓ LOCKED GARAGES ✓ WORKSHOP WALLS	
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts*
✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA	

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

XTM® CAR AWNING 2.0 x 2.5m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM XTM® WILL WORK WITH THE HD HITCH RANGE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts*
✓ LOCKED GARAGES ✓ WORKSHOP WALLS	
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts*
✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA	

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

XTM® COMPACT 4WD AWNING 2.0 x 2.0 m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM XTM® WILL WORK WITH THE HD HITCH RANGE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts*
✓ LOCKED GARAGES ✓ WORKSHOP WALLS	
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts*
✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA	

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

XTM® INSTANT SHOWER TENT

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM XTM® WILL WORK WITH THE HD HITCH RANGE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts*
✓ LOCKED GARAGES ✓ WORKSHOP WALLS	
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts*
✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA	

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.