STZW402 - KI[™] Z-WAVE

ELECTRONIC THERMOSTAT FOR SMART HOME













CONNECTED COMFORT

KI Z-Wave thermostats can easily be integrated into your home's **Z-Wave** network, so you can adjust the temperature setpoint of rooms in your home from a distance.

- INTEGRATES EASILY
 WITH A SMART HOME HUB
- CONTROL WITH A MOBILE APPLICATION DEPENDING ON THE HUB
- ELECTRICITY SAVINGS
 ENERGY SAVINGS OF 10-15% DEPENDING
 ON USF*

COMPATIBILITY

- · Z-Wave hub required
- · Z-Wave Plus certified

COLOR

· white

FINISH

• molded plastic

WATTAGE AND VOLTAGE

- 150 W to 2000 W @ 120 V
- 300 W to 4000 W @ 240 V

CONTROL

- two functions available: comfort and economy
- two- or four-wire connection
- outdoor temperature display[†]
- · frost-free warning
- display in Celsius or Fahrenheit
- · backlit screen with adjustable intensity

ACCURACY

- accurate ambient temperature control of ± 1 °F
- CSA C828-13
- · temperature sensing with thermistor

TEMPERATURE RANGE

• 41 to 86 °F

WARRANTY

- · three years
- * independent study
- † depending on the central controller and its application

COMPATIBLE WITH







For home automated system compatibilities and instructions on connecting to your KI thermostat, visit www.stelpro.com.

TECHNICAL SPECIFICATIONS VOLTAGE AMPERAGE PRODUCT **FREQUENCY** CODE MINIMUM MAXIMUM VOLTS AMPERES H7 2000/4000 120/240 16.7 50/60 STZW402WB+ 150/300

Dimensions: 47/8 in. wide, 47/8 in. high and 13/8 in. deep



